



**CAB6/5R/SO/AB 6 Core Alarm Cable  
conductors) 500mtr Reel  
Benelux**

**(Solid  
ADI**

**Construction**

Group	Signal Cores	Power Cores
Conductor		
Material	Tinned annealed solid Cu	n/a
Nominal Diameter	Ø 0.50mm = 1x Ø0.50mm	n/a
Area	0.196mm <sup>2</sup>	n/a
Insulation		
Material	PVC	n/a
Nominal Diameter	Ø 1.0mm	n/a
Min wall	0.2mm	n/a
Colours	see colour table	n/a
Mylar Layer		
Coverage	n/a	
Drain Wire		
Material	n/a	
Nominal Diameter	n/a	
Area	n/a	
Screen		
Material	n/a	
Coverage	n/a	
Rip cord	Polyester 1100 Desitex 40 Nm breaking strain.	
Sheath		
Material	PVC	
Colour	White	
Nominal Diameter	Ø 3.9mm	
Min wall	Ø 0.4mm	
Sheath Marking		
Printing	n/a	
Color	n/a	
Frequency	n/a	

**Packaging**


Reel	Constructed Reel	10 7/8" Flange 3"x 6" Tin
------	------------------	---------------------------

**Labelling**

Barcode	5060399120265 Pink
Artwork No:	6427

**Weight (nominal)**

12.8Kgs
---------

<i>Not to scale</i> 	Issue 02 Date 03/07/2014 CRJ	CQR Security Tarran Way Ind Est Moreton Wirral CH46 4TH <a href="http://www.cqr.co.uk">www.cqr.co.uk</a>
--	------------------------------------	--

Electrical characteristics		
Group	Signal Cores	Power Cores
Max conductor DC Nominal resistance	87.8 $\Omega$ /Km	n/a
Rated Voltage	50V	n/a
Insulation resistance @20°C	$\approx$ 200 M $\Omega$ /Km	n/a

Thermal Characteristics	
Rated Temperature	-10°C to +70°C

Colour Table		
Signal	Power	Status
	Red	✗
	Black	✗
White		✓
Red		✓
Yellow		✓
Green		✓
Grey		✓
Orange		✓
Turquoise		✗
Brown		✗
Violet		✗
Black		✗
Blue		✗
Pink		✗
White / brown stripe		✗
White / violet stripe		✗
White / green stripe		✗
White / blue stripe		✗
White / grey stripe		✗
White / yellow stripe		✗
White / black stripe	✗	
White / red stripe	✗	
Customer		
ADI Benelux		

Standards
N/A