



P SERIES 24/7 DIGITAL SIGNAGE



LANDSCAPE/PORTRAIT
ORIENTATION



OPS SLOT



24/7 USAGE



SCREEN SHARE

VESTEL

With its versatile, **super-slim design** and **exceptional picture quality**, our 24/7 P Series display is designed to adapt to you.



PR 24/7 DIGITAL SIGNAGE

PN 24/7 DIGITAL SIGNAGE

4K

700
NIT

4K

500
NIT



LANDSCAPE/PORTRAIT
ORIENTATION



OPS SLOT



24/7 USAGE



SCREEN SHARE

HDR

HDR



PIXEL SHIFT



SCHEDULER



AUTO-LAUNCH

PANEL						
	PR43	PR50	PR55	PR65	PN43	PN50
Screen Size	43"	50"	55"	65"	43"	50"
Backlight	S-DLED					
Brightness	700 cd/m² (typ.)				500 cd/m² (typ.)	
Resolution	3840 x 2160 (UHD)					
Contrast Ratio	1200:1 (typ.)	5000:1 (typ.)	1200:1 (typ.)			5000:1 (typ.)
Dynamic Contrast	70000:1				50000:1	
Lifetime	50000 Hours (min.)					
Response	8 ms (typ.)	9.5 ms (typ.)	8 ms (typ.)			9.5 ms (typ.)
Active Area	941x530mm	1095x616mm	1210x680mm	1428x804mm	941x530mm	1095x616mm
View. Angle	178 Vertical, 178 Horizontal					
Colour Value	1.07B (8-Bit+FRC)	1.07B	1.07B (8-Bit+FRC)			1.07B
Screen Treatment	3H					
Haze Level	1%	3%	1%			3%
Refresh rate	60 Hz					
Orientation	Horizontal/Vertical					
Operation	24/7					
Usage	Indoor					
CONNECTIVITY						
	PR43	PR50	PR55	PR65	PN43	PN50
RGB Input	VGA					
RGB Output	-					
Video Input	4 x HDMI, 1 x USB				2 x HDMI, 3 x USB	
Video Output	1 x HDMI				-	
Audio Input	Line In L/R					
Audio output	Headphone, Optic SPDIF					
External Control	RS232, Ethernet (RJ45)					
External Sensor	RJ12					
Network	WiFi, Ethernet (RJ45)					

MECHANICAL						
	PR43	PR50	PR55	PR65	PN43	PN50
Product Dimensions	963Wx83Dx 555H mm	1121Wx83Dx 646H mm	1236Wx83Dx 709H mm	1456Wx96Dx 834H mm	963Wx83Dx 555H mm	1121Wx83Dx 646H mm
Package Dimensions	1050Wx178Dx 718H mm	1215Wx165Dx 775H mm	1369Wx165Dx 874H mm	1650Wx190Dx 997H mm	1050Wx178Dx 718H mm	1215Wx165Dx 775H mm
Product Weight	10.4 kg	12.8 kg	17 kg	24.4 kg	10.4 kg	12.8 kg
Package Weight	13.5 kg	16.8 kg	22 kg	31.25 kg	13.5 kg	16.8 kg
Vesa Mounting	200x200 mm M6		400x400 mm M6	400x600 mm M6	200x200 mm M6	
Bezel Width	B:9 T/L/R: 6 mm	B:13 T/L/R: 9 mm	B:11 T/L/R: 9 mm	B:14 T/L/R: 10 mm	B:9 T/L/R: 6 mm	B:13 T/L/R: 9 mm
ENVIRONMENTAL OPERATING CONDITIONS						
	PR43	PR50	PR55	PR65	PN43	PN50
Temp.	0-40°C					
Humidity	10-90%					
POWER						
	PR43	PR50	PR55	PR65	PN43	PN50
Supply	110v AC - 240v AC 50/60 Hz					
Deep Standby	≤0.5 W					
ACCESSORY						
	PR43	PR50	PR55	PR65	PN43	PN50
Standard	QSG, Power cable, IR extender cable, Mounting Kit, Remote Control, 2 x AAA Battery					
FEATURES						
	PR43	PR50	PR55	PR65	PN43	PN50
Main	Scheduler, USB Autoplay, Auto-Launch, HDMI CEC, HDMI Wakeup, Panel Lock, OSD rotation, Pixel Shift, External Control, RTC					
Mechanical	Joystick Control, IR sensor Cable, OPS module slot, Secure USB cover, Detachable Power Cable					
Speaker	2 x 8 W	2 x 10 W			2 x 8 W	