

**TITLE:**

3182Y Flex Power PVC (Round)

**CODE:**

SFX/2192Y-2C-0.75-PVC-BLK-U-100

**DESCRIPTION:**

100m 2192Y 0.75mm Flat Flex Black PVC (H03VVH2-F 2X0.75)

**SUPPLIED AS:**

Reel of 100m

- Used to connect appliances to mains electricity supplies
- Can be used in light duty domestic and office wiring applications
- Polyvinyl chloride plastic has excellent aging properties and will usually exceed a 25-30 year service life
- Conforms to European Harmonisation Standards
- Improved performance and protection against fire
- Stable, flexible durable and robust cable



enquiries@securiflex.co.uk | www.securiflex.co.uk | 03333 44 66 23



## Product Specification

### Cable Construction

Cable Construction	2 Cores
CPR	Eca
Conductor	Fine Stranded Copper (Class 5)
Overall Diameter (mm)	3.40 x 5.50

### Insulation

Insulation	PVC
Insulation Colour	Blue,Brown

### Outer/Jacket Specification

Jacket	PVC
Overall Colour	Black
Overall Diameter (mm)	3.40 x 5.50
Jacket Colour	Black

### Electrical Characteristics

Max Conductor DC resistance @ 20°C	26.000/km
Rated Temperature (°C)	-20°C to +80°C
Rated Voltage (V)	300/300V



enquiries@securiflex.co.uk | www.securiflex.co.uk | 03333 44 66 23



**FLEXIBLE POWER  
CABLE**



Flexible power Cable

**CONSTRUCTION PRODUCTS REGULATIONS:**

Sorry, No CPR information is available for this product



[enquiries@securiflex.co.uk](mailto:enquiries@securiflex.co.uk) | [www.securiflex.co.uk](http://www.securiflex.co.uk) | 03333 44 66 23

TERMS AND CONDITIONS APPLY - WHILE EVERY EFFORT HAS BEEN MADE TO ENSURE THE ACCURACY AND COMPLETENESS OF THE INFORMATION, NO GUARANTEE IS GIVEN NOR RESPONSIBILITY TAKEN FOR ERRORS OR OMISSIONS IN THIS DATA SHEET.

