

**TITLE:**

3182Y Flex Power PVC (Round)

CODE:

SFX/2192Y-2C-0.75-PVC-WHT-U-100

DESCRIPTION:

100m 2192Y 0.75mm Flat Flex White PVC (H03VVH2-F 2X0.75)

SUPPLIED AS:

Reel of 100m

- Used to connect appliances to mains electricity supplies
- Can be used in light duty domestic and office wiring applications
- Polyvinyl chloride plastic has excellent aging properties and will usually exceed a 25-30 year service life
- Conforms to European Harmonisation Standards
- Improved performance and protection against fire
- Stable, flexible durable and robust cable



**IMAGE
COMING
SOON**



**IMAGE
COMING
SOON**



**IMAGE
COMING
SOON**



**IMAGE
COMING
SOON**





Product Specification

Cable Construction

Cable Construction	2 Cores
CPR	Eca
Conductor	Fine Stranded Copper (Class 5)
Overall Diameter (mm)	3.40 x 5.50

Insulation

Insulation	PVC
Insulation Colour	Blue,Brown

Outer/Jacket Specification

Jacket	PVC
Overall Colour	White
Overall Diameter (mm)	3.40 x 5.50
Jacket Colour	White

Electrical Characteristics

Max Conductor DC resistance @ 20°C	26.00Ω/km
Rated Temperature (°C)	-20°C to +80°C
Rated Voltage (V)	300/300V





**FLEXIBLE POWER
CABLE**



CONSTRUCTION PRODUCTS REGULATIONS:

Sorry, No CPR information is available for this product

Flexible power Cable



enquiries@securiflex.co.uk | www.securiflex.co.uk | 03333 44 66 23

TERMS AND CONDITIONS APPLY - WHILE EVERY EFFORT HAS BEEN MADE TO ENSURE THE ACCURACY AND COMPLETENESS OF THE INFORMATION, NO GUARANTEE IS GIVEN NOR RESPONSIBILITY TAKEN FOR ERRORS OR OMISSIONS IN THIS DATA SHEET.

