

PAC 511 DCi

Controllers

The PAC 511 DCi is an intelligent IP access controller for securing and managing a single door. It can be deployed within a PAC access control system to support on-site access control, lift control and door functions either singularly or part of a larger PAC networked system. It relies on management software for many additional features but has in-built databases and processing ability to execute local access control and features associated with door management and lift control.

- Manages access through 1 door with a maximum of 2 readers (PAC or Wiegand) for full read-in and read-out capability
- Controls door lock via Fail Safe and Fail Secure modes
- Available in two variants:
 - DIN mount PAC 511 DCi for installation in optional PAC 4- or 6-way DIN cabinets
 - Boxed with pre-wired 3Amp PSU in a metal cabinet with lock and tamper switch for ease of install
- Up to 20,000 keyholder records in its onboard database
- Supports ongoing access control and lift control functions if communication to the management platform is lost
- One-Touch™ test mode
- Local anti-passback for accurate tracking of personnel



Part Number(s)	909032511 – 511 Controller - DCi, DIN mount	909030511 – 511 Controller - DCi, enclosure, 3.6A PSU <u>US markets</u> 909032511 – 511 Controller - DCi, enclosure, 3.6A PSU (USA)
Number of Doors Supported	One door with up to two access control devices as per the following options: <ul style="list-style-type: none"> • An access control reader per door • An access control reader and Push To Exit (PTE) device per door • Two access control readers per door (read-in and read-out) 	
Number of ID Devices Supported	20,000	
Supported ID Device Formats	PAC (Cards and Tokens) Key PAC (Cards and Tokens) PAC Ops™ Lite (Cards and Tokens) PAC Ops™ (Cards and Tokens) Any card format supported by Wiegand	
Event Storage	20,000 events	

PAC 511 DCi

Controllers

Configuration	via PC with PAC Access Central or Easinet Residential software	
Distance to Input Devices	70m / 230ft (reader powered from controller) 500m / 1,640ft (locally powered reader)	
Access Controller Input Devices	PAC readers (LF, HF, MT, Architect and Biometric) & Wiegand readers PTE devices Door contacts Alarm inputs	
Input Connection Features	1 × tamper alarm input 1 × override input 1 × TCP/IP input (RJ-45) 1 × RS-485 input 1 × input per door channel	
Output Connection Features	1 x 5Amp ancillary relays, supporting programmable outputs. 3 x inputs for proactive monitoring: <ul style="list-style-type: none"> • Tamper • Over-ride • Customer programmable input 	
Recommended Cabling	0.22mm 8-core alarm cable	
System Power	12–24 V DC	
Power Input	220-240V AC, 50Hz 110-120V AC, 60Hz (US)	
Dimensions	181 (w) × 65 (h) × 125 (d) mm 7.13 (w) × 2.56 (h) × 4.92 (d) in.	Boxed : 335 (w) × 335 (h) × 90 (d) mm Boxed: 13.19 (w) × 13.19 (h) × 3.54 (d) in.
Weight	909032511 — 0.61kg / 1.34lb	909030511 — 4.4kg / 9.7lb
Operating Temperature	0°C to +35°C / 32°F to 95°F	
Operating Humidity	10% to 85% Relative Humidity	
Warranty	5 years against electronic failure	
Standards Compliance	UKCA, CE, UL, FCC, IC, RoHS & WEEE compliant	