

**TITLE:**

RG59 Coaxial Cable

**CODE:**

SFX/59-PREM-LSZH-D-BLK-100

**DESCRIPTION:**

100m RG59 Coaxial Dca Premium  
Black UV LSZH

**SUPPLIED AS:**

Reel of 100m

- Even with the introduction of IP cameras, coax is still a preferred choice for many installers in the security industry
- Coax is a simple solution that does not require any additional products such as baluns to create an image
- Low smoke zero halogen plastic is good for use inside public buildings and spaces as will not emit toxic gases if the cable catches fire
- Suitable for general purpose CCTV applications and high frequency signal transmission



**IMAGE  
COMING  
SOON**



**IMAGE  
COMING  
SOON**



**IMAGE  
COMING  
SOON**



**IMAGE  
COMING  
SOON**





## Product Specification

25-YEAR WARRANTY



### Cable Construction

CPR	Dca -s:1b -a:1 -d:2
Conductor Diameter (mm)	0.58 ±0.008
Inner Conductor	Bare Copper
Overall Diameter (mm)	6.10 ±0.10
Compliance and Standards	CE2014/30/EU, RoHS2 2011/65/EU, LVD 2014/35/EU

### Insulation

Insulation	Solid PE
Insulation Colour	Clear
Insulation Thickness (mm)	1.60 ±0.01

### Outer/Jacket Specification

Jacket	UV LSZH
Overall Colour	Black
Overall Diameter (mm)	6.10 ±0.10
Jacket Colour	Black RAL 9005
Jacket Thickness (mm)	0.85 ±0.10

### Electrical Characteristics

Outer Conductor DC resistance @ 20°C	<420/km
Rated Temperature (°C)	-40°C to 70°C



enquiries@securiflex.co.uk | www.securiflex.co.uk | 03333 44 66 23



COAX CABLE



## CONSTRUCTION PRODUCTS REGULATIONS:

Sorry, No CPR information is available for this product

Coax Cable



enquiries@securiflex.co.uk | www.securiflex.co.uk | 03333 44 66 23

TERMS AND CONDITIONS APPLY - WHILE EVERY EFFORT HAS BEEN MADE TO ENSURE THE ACCURACY AND COMPLETENESS OF THE INFORMATION, NO GUARANTEE IS GIVEN NOR RESPONSIBILITY TAKEN FOR ERRORS OR OMISSIONS IN THIS DATA SHEET.

