

DC115

OVERHEAD CONT. 5 WIRE

Industrial Contact

The DC115/DC118 are designed to be installed in commercial and industrial environments where a rugged sealed unit is required. It is ideal for metal doors, overhead doors, fences and gates. Each model features a high strength extruded aluminium housing and is completely encapsulated in an exclusive polyurethane potting compound.

Comprehensive Range

The range features wide gap distances and several models to meet any application need. Armoured cable is available.



Standard Features

- Mounting brackets available for gates, garage doors, freezers
- Rugged construction for long life
- Convenient surface mounting
- 2 m armoured cable
- Tamper loop provided
- DC115 is polarity-sensitive with reference to magnet direction

DC115

OVERHEAD CONT. 5 WIRE

Specifications

General

Application type	Surface Mount
Contact type	CO
Connectivity	5 wires, 2 m

Wired/wireless

Wired-wireless	Wired
----------------	-------

Physical

Material	Anodised aluminium finish
Dimensions magnet	76 x 12 x 25 mm
Dimensions contact / sensor	76 x 12 x 25 mm
Operating gap	9-62 mm

Standards & regulation

EN50131 grade	Grade 2
---------------	---------

Ordering Information

Part No.	Description
DC115	OVERHEAD CONT. 5 WIRE
DC118	Surface - overhead - door mount contact - wide gap
DC111	Balanced Triple Biased Ov.Con
DC1912	L Bracket for DC110, DC115, DC118

