


(1) 10-bit digital video channel with 1 bi-directional data channel /
daisy chain 8 video channels on one single mode fiber / dual
optical port self-healing ring configuration / single fiber operation



Description

The ComNet™ FVT/FVR1010SHR series of optical video links provides 10-bit digital video, 6.5 Mhz bandwidth, medium haul video quality, one bi-directional data channel and a “Dual Optical Port” (DOP) Self-Healing Ring (SHR) topology. Up to (8) video transmitters and multiple video receivers can be “Daisy Chained” on one optical fiber.

The Self-Healing Ring (SHR) topology using the Dual Optical Ports (DOP) provide fail safe operation in the event of loss of one fiber or one optical module. Each optical port uses wavelength division multiplexing (WDM) to both transmit and receive on one optical fiber. The data channel supports RS232, RS422 and 2 wire and 4 wire RS485. Plug-and-play design ensures ease of installation and no electrical or optical adjustments are ever required. Bi-color (Red/Green) LED indicators are provided for confirming operating status. Packaged in the exclusive ComNet ComFit housing, these units may be either wall or rack-mounted, or may be DIN-rail mounted by the addition of ComNet model DINBKT1 adaptor plate.

Features

- One 10-bit digital video channel
- One bi-directional data channel; or 8 contact closures*
- Daisy chain 8 video links on one single mode or multimode fiber
- Dual optical port Self-Healing Ring (SHR) configuration
- Exceeds all requirements for RS-250C medium haul transmission
- Compatible with all NTSC, PAL, or SECAM CCTV camera systems
- Tested and certified by an independent laboratory for full compliance with the environmental requirements (ambient operating temperature, mechanical shock, vibration, humidity with condensation, high-line/low-line voltage conditions and transient voltage protection) of NEMA TS-1/TS-2 and the Caltrans Specification for Traffic Signal Control Equipment.
- Voltage transient protection on all power and signal input/output lines provides unconditional protection from power surges and other voltage transient events.
- Automatic resettable fuses on all power lines
- Hot-swappable rack modules
- Interchangeable between stand-alone or rack mount use
 - ComFit
- Distances up to 30 miles (48 km)
- Bi-color (Red/Green) LED status indicators provide rapid indication of critical operating parameters
- Lifetime Warranty

* Requires an additional FDC8T/R232 unit sold separately.



(1) 10-bit digital video channel with 1 bi-directional data channel
FVT/FVR1010(M)(S)1SHR / daisy chain 8 video channels on one single mode fiber / dual
SELF-HEALING RING optical port self-healing ring configuration / single fiber operation

specifications

VIDEO

Video Input: 1 volt pk-pk (75 ohms)
 Overload: >1.5V pk-pk
 Bandwidth: 5 Hz - 6.5 MHz
 Differential Gain: <2%
 Differential Phase: < 0.7°
 Tilt: <1%
 Signal-to-Noise Ratio (SNR): 67 dB @ Maximum Optical Loss Budget
 Max. RG-59 COAX Distance: 100m (300ft) Camera to Fiber Optic Module to maintain 6Mhz Bandwidth

DATA

Data Interface: RS232, RS422 and RS485 (2W/4W)
 Data Format: NRZ, NRZI, Manchester, Bi-phase and Sensornet
 Data Rate: DC-250 Kbps (NRZ)

WAVELENGTH 1310/1550 nm, MM and SM

NUMBER OF FIBERS 1 in/1 out

OPTICAL EMITTER Laser Diode

LED INDICATORS - Fiber Status - Video Sync Presence
 - Received Data - Transmitted Data
 - Power

CONNECTORS

Optical: 2 ST connectors for the Dual Port configuration (Required for Daisy Chain Self-Healing Ring operation)
 Power: Terminal Block
 Video: BNC (Gold Plated Center-Pin)
 Data: Terminal Block

ELECTRICAL & MECHANICAL

Power: 8-15 VDC @ 3W
 Surface Mount: From Rack
 Rack Mount: 1
 Number of Rack Slots: Automatic Resettable Solid-State Current Limiters
 Current Protection: Meets IPC Standard
 Circuit Board: 6.1 × 5.3 × 1.1 in., (15.5 × 13.5 × 2.8 cm)
 Size (in./cm) (L×W×H) <2 lb./0.9 kg
 Shipping Weight:

ENVIRONMENTAL

MTBF: >100,000 hours
 Operating Temp: -40° C to +75° C
 Storage Temp: -40° C to +85° C
 Relative Humidity: 0% to 95% (non-condensing)[†]

† May be extended to condensation conditions by adding suffix '/C' to model number for conformal coating.



PART NUMBER	DESCRIPTION	FIBERS REQUIRED	FIBER	OPTICAL PWR BUDGET	MAX. DISTANCE [‡]	# RACK SLOTS
FVT1010M1SHR	Video Transmitter/Data Transceiver	1 In/1 Out	Multimode 62.5/125µm	16 dB	2 km (1.2 miles)	1
FVR1010M1SHR	Video Receiver/Data Transceiver					
FVT1010S1SHR	Video Transmitter/Data Transceiver	1 In/1 Out	Single Mode 9/125µm	16 dB	48 km (30 miles)	1
FVR1010S1SHR	Video Receiver/Data Transceiver					
Accessories	9 Volt DC Plug-in Power Supply, 90-264 VAC, 50/60 Hz (Included)					
Options	Add 'C' for Conformally Coated Circuit Boards (Extra charge, consult factory)					
	DIN-Rail Mounting Adaptor Plate Kit – With mounting hardware (Optional, order model DINBKT1)					

NOTE: This product requires a fiber installation with a minimum 35 dB connector return loss. The use of Super Polish Connectors is recommended.
 Complies with FDA Performance Standard for Laser Products, Title 21, Code of Federal Regulations, Subchapter J
 In a continuing effort to improve and advance technology, product specifications are subject to change without notice.
[‡]Distance may be limited by optical dispersion.



3 CORPORATE DRIVE | DANBURY, CT 06810 | USA
 T: 203.796.5300 | F: 203.796.5303 | TECH SUPPORT: 1.888.678.9427 | INFO@COMNET.NET
 8 TURNBERRY PARK ROAD | GILDERSOME | MORLEY | LEEDS, UK LS27 7LE
 T: +44 (0)113 307 6400 | F: +44 (0)113 253 7462 | INFO-EUROPE@COMNET.NET