



Analog

PTZ

HCP-6320A

1080p Analog HD 32x PTZ Dome Camera



Key Features

- Full HD (1920 x 1080, 30fps) resolution
- 0.2Lux@F1.6, B/W : 0.01Lux@F1.6
- Powerful 32x zoom (4.44 ~ 142.6mm), Digital 16x
- Day & Night (ICR), Defog, WDR (120dB), SSNR III
- Preset 700°/sec, Azimuth
- IP66 / IK10 (HCP-6320HA), IK10 (HCP-6320A + SHP-3701H only)
- RS-485, Coax control

Compatible Accessories (Optional)



SHP-3701H




SBP-301HM3



SHP-3701FB



SHP-1520FW



SPB-PTZ6




SBP-390WM2



SBP-300WM



SBP-300WM1



SBP-300B



SBP-300KM



SBP-300NB



SBP-300LM



SBP-300PM



SBP-300CM



HCP-6320A

1080p Analog HD 32x PTZ Dome Camera

Specifications

Video

Imaging Device	1/2.8" 2.38MP CMOS
Resolution	1920x1080
Min. Illumination	Color: 0.3 Lux (1/30sec, F1.6, 50IRE) , 0.005 Lux(2sec, F1.6, 50IRE) B/W: 0.03 Lux (1/30sec, F1.6, 50IRE), 0.0005 Lux(2sec, F1.6, 50IRE) Color: 0.2 Lux (1/30sec, F1.6, 30IRE), 0.003 Lux(2sec, F1.6, 30IRE) B/W: 0.01 Lux (1/30sec, F1.6, 30IRE), 0.0001 Lux(2sec, F1.6, 30IRE)
Video Out	BNC(AHD), CVBS(SD, DIP connector type)

Lens

Focal Length (Zoom Ratio)	4.44 ~ 142.6mm(32x) motorized varifocal
Max. Aperture Ratio	F1.6(Wide) ~ F4.4(Tele)
Min. Object Distance	Wide 1.5m(4.92ft), Tele 2.0m(6.56ft)
Focus Control	Auto / Manual / One push
Lens Type	DC Auto Iris

Pan / Tilt / Rotate

Pan Range	360° Endless
Pan Speed	Preset: 700°/sec, Manual: 0.024°/sec ~ 200°/sec
Tilt Range	210°(-15° ~ 195°)
Tilt Speed	Preset : 700°/sec, Manual : 0.024°/sec ~ 200°/sec
Preset Accuracy	±0.2°

Operational

Camera Title	Displayed up to 12 characters
Day & Night	Auto(ICR)
Backlight Compensation	BLC, HLC, WDR
Wide Dynamic Range	120dB
Digital Noise Reduction	SSNRIII
Digital Image Stabilization	Support
Defog	Support
Motion Detection	1ea, rectangular zone
Privacy Masking	12ea, rectangular zones
Gain Control	Low / Middle / High
White Balance	ATW / AWC / Manual / Indoor / Outdoor
Electronic Shutter Speed	ESC / Auto / Manual
Video Rotation	Digital Flip
Analytics	Motion detection, Appear/Disappear, Enter/Exit, Virtual Line
Serial Interface	RS-485: Samsung-T/E, Pelco-D/P, Panasonic, Bosch, AD, GE, Vicon, Honeywell
Alarm I/O	Input 4ea, Output 2ea
Alarm Triggers	Analytics
Alarm Events	Alarm output
Coaxial Protocol	ACP(AHD Coax Protocol), CVBS : Pelco-C(Coaxitron)

Environmental & Electrical

Operating Temperature / Humidity	-10°C ~ +55°C(+14°F ~ +131°F) / Less than 90% RH
Input Voltage	24VAC
Power Consumption	Max 20W

Mechanical

Color / Material	Ivory / Plastic
Product Dimensions / Weight	Ø152.0x218.0mm(5.98x8.58"), 1700g(3.75 lb)

HCP-6320A

1080p Analog HD 32x PTZ Dome Camera

CAD



Unit: mm [inch]

