



TITLE:

ISP Individual Foil Screen PE

CODE:

SFX/ISP2-PE-BLK-100


DESCRIPTION:

100m ISP2 2pr 22AWG Individual Foil Screen 600V Black PE (8723)

SUPPLIED AS:

Reel of 100m

- Wideley used in the security industry for CCTV telemetry purposes
- Also used in appliactions such as computing where extra screening is required to prevent cross talk between pairs
- Polyethylene plastic is excellent for use externally above ground or below ground inside ducting
- UV resistant



enquiries@securiflex.co.uk | www.securiflex.co.uk | 03333 44 66 23



Product Specification



Cable Construction

Cable Construction	2 Pairs
CPR	Fca
Conductor	Tinned Copper
Conductor Diameter (mm)	0.24 ±0.008 x 7 (0.33mm ²)
Stranded Diameter (mm)	0.64
Overall Diameter (mm)	4.10 ±0.20

Insulation

Insulation	SR-PVC
Insulation Colour	Red, Black, Green, White
Insulation Resistance @20°C	>200MO/km
Insulation Thickness (mm)	0.24

Outer/Jacket Specification

Jacket	PE
Overall Colour	Black
Overall Diameter (mm)	4.10 ±0.20
Jacket Colour	Black RAL 9005
Jacket Thickness (mm)	0.45
Nylon Rip-Cord	White 210D

Electrical Characteristics

Insulation Resistance @20°C	>200MO/km
Max Conductor DC resistance @ 20°C	<50O/km
Rated Temperature (°C)	-20°C to 80°C
Rated Voltage (V)	600V





BELDEN CABLE



CONSTRUCTION PRODUCTS REGULATIONS:

Sorry, No CPR information is available for this product

Belden Cable



enquiries@securiflex.co.uk | www.securiflex.co.uk | 03333 44 66 23

TERMS AND CONDITIONS APPLY - WHILE EVERY EFFORT HAS BEEN MADE TO ENSURE THE ACCURACY AND COMPLETENESS OF THE INFORMATION, NO GUARANTEE IS GIVEN NOR RESPONSIBILITY TAKEN FOR ERRORS OR OMISSIONS IN THIS DATA SHEET.

