

SFX/OFB4-LSZH-GRY

OFB4 4pr 24AWG Overall Foil and Braid Screen 600V Grey LSZH (9844)



Cable Construction	4 Pairs
Conductor	Tinned Copper
Conductor Diameter (mm)	0.19 ±0.008 x 8
Stranded Diameter (mm)	0.6
Insulation	HDPE
Insulation Thickness (mm)	0.55
Insulation Diameter (mm)	1.83 ±0.10
Insulation Colours	White/Blue, Blue/White; White/Orange, Orange/White; White/Green, Green/White; White/Brown, Brown/White
Al-PET Shield	≥115%
Drain Wire	
Conductor	Tinned Copper
Conductor Diameter (mm)	0.19 ±0.008 x 7
Braid	Tinned Copper
Braid Construction	0.12 ±0.008 x 24 x 8
Braid Coverage	≥90%
Nylon Rip-Cord	150D
Jacket	LSZH
Jacket Thickness (mm)	1.2
Overall Diameter (mm)	10.00 ±0.20
Jacket Colour	Grey RAL 7042
Sheath Printing	OFB4 4x2x24AWG Foil & Braid Screen LSF RoHS2 (PO) (m)
Reaction to Fire	Eca
Electrical Characteristics	
Max Conductor DC resistance @ 20°C	<83Ω/km
Rated Temperature	70°C
Rated Voltage	600V
Insulation Resistance @20°C	>200MΩ/km