



PowerManage User Guide

Building Technologies & Solutions

www.jci.com

2022-04

D-308632

Rev. 0

Version 4.10



D-308632

© 2022 Johnson Controls. All rights reserved.

Copyright

2022 Johnson Controls. All rights reserved. JOHNSON CONTROLS, TYCO, VISONIC and DSC are trademarks of Johnson Controls.

End User License Agreement

IMPORTANT - READ THIS END-USER LICENSE AGREEMENT ("**EULA**") CAREFULLY BEFORE OPENING, DOWNLOADING, INSTALLING, ACCESSING, OR OTHERWISE USING THE SOFTWARE.

THIS EULA IS A LEGAL AGREEMENT BETWEEN YOU AND TYCO FIRE & SECURITY GMBH ("**TYCO**") AND GOVERNS YOUR USE OF THE SOFTWARE ACCOMPANYING THIS EULA, WHICH SOFTWARE INCLUDES COMPUTER SOFTWARE AND MAY INCLUDE MEDIA, PRINTED MATERIALS, AND "ON-LINE" OR ELECTRONIC DOCUMENTATION (COLLECTIVELY, THE "**SOFTWARE**"). BY BREAKING THE SEAL ON THIS PACKAGE, DOWNLOADING THE SOFTWARE OR INSTALLING, ACCESSING OR OTHERWISE USING THE SOFTWARE, YOU AGREE TO BE BOUND BY THE TERMS OF THIS EULA. IF YOU DO NOT AGREE TO ALL OF THE TERMS AND CONDITIONS OF THIS EULA, DO NOT DOWNLOAD, INSTALL, ACCESS, OR OTHERWISE USE THE SOFTWARE. If this EULA is being agreed to by a corporation or other legal entity, then the person agreeing to this EULA on behalf of that corporation or entity represents and warrants that he or she is authorized and lawfully able to bind that corporation or entity to this EULA. You should print and retain a copy of this EULA for Your records.

1. **SCOPE OF LICENSE.** The Software may include computer code, program files and any associated media, hardware or software keys, printed material and electronic documentation. The Software may be provided to You on a stand-alone basis or pre-installed on a storage device (the media) as part of a computer system or other hardware or device ("**System**"). The Software is protected by copyright laws and international copyright treaties, as well as other intellectual property laws and treaties. All title and intellectual property rights in and to the Software (including but not limited to any images, photographs, and text incorporated into the Software), the accompanying printed materials, and any copies of the Software, are owned by Tyco and/or its suppliers.

2. **GRANT OF LICENSE.** This EULA grants You the following rights on a non-exclusive basis:

- a. **General.** During the term of this EULA, this EULA grants You and Your individual employees a revocable, non-transferable, non-sublicensable, nonexclusive license to use the object code version of the Software and any Documentation for Your internal use only, subject to all Scope Restrictions. The order document under which You have licensed the Software may contain additional terms limiting the scope of Your license, including, but not limited to, a specified number of users or specific systems, licensed facilities, geographic areas, etc. (collectively, "**Scope Restrictions**"). Once You have purchased licenses for the number of copies of the Software that You require, You may use the Software and accompanying material provided that You install and use no more than the licensed number of copies at one time. In the event the Software is furnished for use in connection with a particular Tyco (or a Tyco affiliate's) system or hardware product, it may only be used in conjunction with that Tyco (or Tyco affiliate's) system or hardware product. If the Software is furnished embedded in a Tyco (or a Tyco affiliate's) system or hardware product, the Software may not be extracted or used separately from that system or product. "**Documentation**" means Tyco's then-current generally available documentation for use and operation of the Software. Documentation is deemed included in the definition of Software for purposes of this EULA. The term "Software" will be deemed to include any updates, bug fixes, and new versions (collectively, "**Enhancements**") that Tyco may, in its discretion, make available to You. You are responsible for ensuring Your employees comply with all relevant terms of this EULA and any failure to comply will constitute a breach by You. The Software is licensed, not sold. Except for the limited license granted above, Tyco and its licensors retain all right, title and interest in the Software, all copies thereof, and all proprietary rights in the Software, including copyrights, patents, trademarks and trade secret rights.
- b. **Locally Stored Components.** The Software may include a software code component that may be stored and operated locally on one or more devices. Once You have paid the required license fees for these devices (as determined by Tyco in its sole discretion), You may install and/or use one copy of such component of the Software on each of the devices as licensed by Tyco. You may then use, access, display, run or otherwise interact with ("use") such component of the Software in connection with operating the device on which it is installed solely in the manner set forth in any accompanying documentation or, in the absence of such, solely in the manner contemplated by the nature of the Software.
- c. **Remotely Stored Components.** The Software may also include a software code component for operating one or more devices remotely. You may install and/or use one copy of such component of the Software on a remote storage device on an internal network with all of the devices and may operate such component with each device over the internal network solely in the manner set forth in any accompanying documentation or, in the absence of such, solely in the manner contemplated by the nature of the Software; provided however, You must still acquire the required number of licenses for each of the devices with which such component is to be operated.
- d. **Embedded Software/Firmware.** The Software may also include a software code component that is resident in a device as provided by Tyco (or a Tyco affiliate) for operating that device. You may use such component of the Software solely in connection with the use of that device, but may not retrieve, copy or otherwise transfer that software component to any other media or device without Tyco's express prior written authorization.
- e. **Backup Copy.** You may make a back-up copy of the Software (other than embedded software) solely for archival purposes, which copy may only be used to replace a component of the Software for which You have current valid license. Except as expressly provided in this EULA, You may not otherwise make copies of the Software, including the printed materials.

3. **OTHER RIGHTS AND LIMITATIONS.** Your use of the Software is subject to the following additional limitations. Failure to comply with any of these restrictions will result in automatic termination of this EULA and will make available to Tyco other legal remedies.

- a. **Restrictions.** Your use of the Software must be in accordance with the Documentation. You will be solely responsible for ensuring Your use of the Software is in compliance with all applicable foreign, federal, state and local laws, rules and regulations. You may not (i) copy or distribute the Software except to the extent that copying is necessary to use the Software for purposes set forth herein; provided You may make a single copy of the Software for backup and archival purposes; (ii) modify or create derivative works of the Software; (iii) decompile, disassemble, reverse engineer, or otherwise attempt to derive the trade secrets embodied in the Software, except and only to the extent that such activity may be expressly permitted, notwithstanding this limitation or another limitation contained in this EULA, either by applicable law or, in the case of open source software, the applicable open source license; (iv) use the Software for purposes of developing a competing product or service; (v) remove any copyright, trademark, proprietary rights, disclaimer, or warning notice included on or embedded in any part of the Documentation and Software; (v) assign, sublicense, rent, timeshare, loan, lease or otherwise transfer the Software, or directly or indirectly permit any third party to use or copy the Software. The Software may be subject to additional restrictions and conditions on use as specified in the documentation accompanying such Software, which additional restrictions and conditions are hereby incorporated into and made a part of this EULA. Under no circumstances will Tyco be liable or responsible for any use, or any results obtained by the use, of the services in conjunction with any services, software, or hardware that are not provided by Tyco. All such use will be at Your sole risk and liability.
- b. **Copyright Notices.** You must maintain all copyright notices on all copies of the Software.
- c. **Transfer.** You may only transfer Your rights under this EULA (i) as part of a permanent sale or transfer of all of the devices for which the Software is licensed as applicable; (ii) if You transfer all of the Software (including all component parts, the media and printed materials, any upgrades and this EULA); (iii) if You do not retain any copies of any portion of the Software; (iv) if the recipient agrees to the terms of this EULA; and (v) if the Software is an upgrade, such transfer must also include all prior versions of the Software. You agree that failure to meet all of these conditions renders such transfer null and void.
- d. **Subsequent EULA.** Tyco may also supersede this EULA with a subsequent EULA pursuant to providing You with any future component, release, upgrade or other modification or addition to the Software. Similarly, to the extent that the terms of this EULA conflict with any prior EULA or other agreement between You and Tyco regarding the Software, the terms of this EULA shall prevail.
- e. **Trademarks.** This EULA does not grant You any rights in connection with any trademarks or service marks of Tyco, its affiliates or its suppliers.

- f. **Software Keys.** The hardware/software key, where applicable, is Your proof of license to exercise the rights granted herein and must be retained by You. Lost or stolen keys will not be replaced.
- g. **Demonstration and Evaluation Copies.** A demonstration or evaluation copy of the Software is covered by this EULA; provided that the licenses contained herein shall expire at the end of the demonstration or evaluation period.
- h. **Registration of Software.** The Software may require registration with Tyco prior to use. If You do not register the Software, this EULA is automatically terminated and You may not use the Software.
- i. **Compliance with Laws.** The use of the Software may require your compliance with local and national laws and regulations. You are solely responsible for compliance with all applicable laws and regulations relating to the use of the Software, including but not limited to those laws and regulations pertaining to personal data protection, privacy and security.
- j. **Enhancements.** To the extent Tyco makes them available to You, Software Enhancements may only be used to replace all or part of the original Software that You are licensed to use. Software Enhancements do not increase the number of copies licensed to You. If the Software is an upgrade of a component of a package of Software programs that You licensed as a single product, the Software may be used and transferred only as part of that single product package and may not be separated for use on more than one computer or System. Software Enhancements downloaded via a Tyco authorized World Wide Web or FTP site may be used to upgrade multiple Systems provided that You are licensed to use the original Software on those Systems.
- k. **Tools and Utilities.** Software distributed via a Tyco-authorized World Wide Web or FTP site (or similar Tyco-authorized distribution means) as a tool or utility may be copied and installed without limitation provided that the Software is not distributed or sold and the Software is only used for the intended purpose of the tool or utility and in conjunction with Tyco products. All other terms and conditions of this EULA continue to apply.
4. **THIRD PARTY SOFTWARE.** To the extent any software licensed from third parties, including open source software, (collectively, "**Third Party Software**") is provided with or incorporated into the Software, You will comply with the terms and conditions of the applicable third party licenses associated with the Third Party Software, in addition to the terms and restrictions contained in this EULA. All relevant licenses for the Third Party Software are provided in the Documentation or product files accompanying the Software. By using the Software You are also agreeing to be bound to the terms of such third party licenses. If provided for in the applicable third party license, You may have a right to reverse engineer such open source software or receive open source code for such open source software for use and distribution in any program that You create, so long as You in turn agree to be bound to the terms of the applicable third party license, and Your programs are distributed under the terms of that license. If applicable, a copy of such open source code may be obtained free of charge by contacting your Johnson Controls representative. TYCO MAKES NO WARRANTY OF ANY KIND, WHETHER EXPRESS OR IMPLIED, WITH REGARD TO ANY THIRD PARTY SOFTWARE. ALL THIRD PARTY SOFTWARE IS PROVIDED "AS-IS," WITHOUT WARRANTIES OF ANY KIND. IN NO EVENT WILL TYCO BE LIABLE TO YOU OR ANY THIRD PARTY FOR ANY DIRECT, INDIRECT, PUNITIVE, EXEMPLARY, INCIDENTAL, SPECIAL, OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE THIRD PARTY SOFTWARE, EVEN IF TYCO HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES OR LOSSES.
5. **METERING DEVICES.** The Software may contain technology based metering devices and passive restraints to regulate usage. For example, the Software may contain a license file limiting use to the licensed number of concurrent users/devices or named users/devices or may temporarily restrict usage until license and other fees have been paid in full. You acknowledge that such restraints and metering devices are a reasonable method to ensure compliance with the license and have been factored into the license and other fees and the EULA as a whole. You agree that You will not directly or indirectly circumvent, override, or otherwise bypass such metering devices and restraints that regulate the use of the Software.
6. **TERM AND TERMINATION.** Unless provided otherwise in an accompanying order document, this EULA will commence on the earlier of the date You first download, install, access or use the Software (the "**Effective Date**") and continue in effect for the term specified in the order document or, if no term is specified, until it is terminated (the "**Term**") as provided in this Section. Either party may terminate this EULA on written notice to the other party if the other party is in material breach of its obligations hereunder and fails to cure the breach within thirty (30) days of such written notice. In addition, either party may, in its sole discretion, elect to terminate this EULA on written notice to the other party upon the bankruptcy or insolvency of the other party or upon the bankruptcy or insolvency of the other party upon the commencement of any voluntary or involuntary winding up, or upon the filing of any petition seeking the winding up of the other party. In the event of any claim of intellectual property infringement relating to the Software, Tyco may terminate this EULA on written notice to You and, as Your sole and exclusive remedy, refund the license fees paid, if any, hereunder (less depreciation calculated on a three (3)-year straight-line basis commencing on the date of initial delivery to You). Sections 9 and 10 shall remain unaffected. Upon any termination or expiration of this EULA, the license granted in Section 2 will automatically terminate and You will have no further right to possess or use the Software. On Tyco's request, You will provide Tyco with a signed written statement confirming that the Software has been permanently removed from Your systems.
7. **FEES; TAXES.** You will pay the fees, if any, associated with the Software. All amounts due hereunder shall be paid within thirty (30) days of the date of the invoice. Payments not made within such time period shall be subject to late charges equal to the lesser of (i) one and one-half percent (1.5%) per month of the overdue amount or (ii) the maximum amount permitted under applicable law. All taxes, duties, fees and other governmental charges of any kind (including sales and use taxes, but excluding taxes based on the gross revenues or net income of Tyco) that are imposed by or under the authority of any government or any political subdivision thereof on the fees for the Software shall be borne solely by You, unless You can evidence tax exemption and shall not be considered a part of a deduction from or an offset against such fees. If You lose tax exempt status, You will pay any taxes due as part of any renewal or payment. You will promptly notify Tyco if Your tax status changes. You will pay all court costs, fees, expenses and reasonable attorneys' fees incurred by Tyco in collecting delinquent fees.
8. **LIMITED WARRANTY.**
- a. **Warranty.** Tyco warrants that (i) for a period of thirty (30) days from delivery initial delivery of the Software to you (the "**Warranty Period**"), the Software will operate in substantial conformity with its Documentation. If, during the Warranty Period, you notify Tyco of any non-compliance with the foregoing warranty, Tyco will, in its discretion: (a) use commercially reasonable efforts to provide the programming services necessary to correct any verifiable non-compliance with the foregoing warranties; or (b) replace any non-conforming Software; or if neither of foregoing options is reasonably available to Tyco, (c) terminate this Agreement in whole or in part, and refund to You the fees, if any, paid for the non-conforming Software (less depreciation calculated on a three (3)-year straight-line basis commencing on the date of initial delivery to you). Tyco shall not be liable for failures caused by third party hardware and software (including your own systems), misuse of the Software, or Your negligence or willful misconduct. EXCEPT AS PROVIDED IN THIS SECTION, THE SOFTWARE IS PROVIDED ON AN "AS AVAILABLE," "AS IS" BASIS. TO THE MAXIMUM EXTENT PERMITTED BY LAW, TYCO AND ITS AFFILIATES, AND THEIR RESPECTIVE SUPPLIERS AND VENDORS DISCLAIM ALL OTHER WARRANTIES WITH RESPECT TO THE SOFTWARE, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF NON-INFRINGEMENT, TITLE, MERCHANTABILITY, QUIET ENJOYMENT, QUALITY OF INFORMATION, AND FITNESS FOR A PARTICULAR PURPOSE. TYCO AND ITS AFFILIATES AND THEIR RESPECTIVE SUPPLIERS AND VENDORS DO NOT WARRANT THAT THE SOFTWARE WILL MEET YOUR REQUIREMENTS, OR THAT THE OPERATION OF THE SOFTWARE WILL BE UNINTERRUPTED OR ERROR-FREE, OR THAT DEFECTS IN THE SOFTWARE WILL BE CORRECTED. NO ORAL OR WRITTEN INFORMATION OR ADVICE GIVEN BY TYCO OR ANY OF ITS PERSONNEL OR AGENTS SHALL CREATE ANY ADDITIONAL Tyco WARRANTIES OR IN ANY WAY INCREASE THE SCOPE OF Tyco'S OBLIGATIONS HEREUNDER.
- b. **Exclusive Remedy.** Tyco's entire liability and Your exclusive remedy under the warranty set forth in this Section 8 will be, at Tyco's option, to (i) attempt to correct Software errors with efforts Tyco believes suitable to the problem, (ii) replace at no cost the recording medium, Software or documentation with functional equivalents as applicable, or (iii) refund a pro-rated portion of the license fee paid for such Software (less depreciation based on a five-year life expectancy) and terminate this EULA, provided, in each case, that Tyco is notified in writing of all warranty problems during the applicable warranty period. Any replacement item will be warranted for the remainder of the original warranty period. No

remedy is provided for failure of the Software if such failure is the result of accident, abuse, alteration or misapplication with respect to the Software or any hardware on which it is loaded. Warranty service or assistance is provided at the original point of purchase.

9. LIMITATION OF LIABILITY. TO THE MAXIMUM EXTENT PERMITTED BY LAW, IN NO EVENT SHALL TYCO AND ITS AFFILIATES AND THEIR RESPECTIVE SUPPLIERS AND VENDORS BE LIABLE TO YOU OR ANY THIRD PARTY FOR ANY SPECIAL, INCIDENTAL, CONSEQUENTIAL, PUNITIVE, OR INDIRECT DAMAGES, WHICH SHALL INCLUDE, WITHOUT LIMITATION, DAMAGES FOR PERSONAL INJURY, LOST PROFITS, LOST DATA AND BUSINESS INTERRUPTION, ARISING OUT OF THE USE OR INABILITY TO USE THE SOFTWARE, EVEN IF THEY HAVE BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES. IN ANY CASE, THE ENTIRE AGGREGATE LIABILITY OF TYCO AND ITS AFFILIATES AND THEIR RESPECTIVE SUPPLIERS AND VENDORS UNDER THIS AGREEMENT FOR ALL DAMAGES, LOSSES, AND CAUSES OF ACTION (WHETHER IN CONTRACT, TORT (INCLUDING NEGLIGENCE), OR OTHERWISE) SHALL BE LIMITED TO FEES PAID BY YOU FOR THE SOFTWARE, IF ANY, DURING THE THREE (3) MONTHS IMMEDIATELY PRECEDING THE FIRST EVENT GIVING RISE TO LIABILITY. BECAUSE AND TO THE EXTENT THAT SOME JURISDICTIONS DO NOT ALLOW THE EXCLUSIONS OR LIMITATIONS OF LIABILITY ABOVE, THESE MAY NOT APPLY TO YOU.

10. CONFIDENTIALITY. You acknowledge that the ideas, methods, techniques, and expressions thereof contained in the Software (collectively, "**Tyco Confidential Information**") constitute confidential and proprietary information of Tyco, the unauthorized use or disclosure of which would be damaging to Tyco. You agree to hold the Software and Tyco Confidential Information in strictest confidence, disclosing information only to permitted individual employees who are required to have access in order to perform under this Agreement and to use such information only for the purposes authorized by this Agreement. You are responsible for and agree to take all reasonable precautions, by instruction, agreement or otherwise, to ensure that Your employees who are required to have access to such information in order to perform under this Agreement, are informed that the Software and Tyco Confidential Information are confidential proprietary information belonging to Tyco and to ensure that they make no unauthorized use or disclosure of such information. You may disclose Tyco Confidential Information if You are required to do so pursuant to a governmental agency, a court of law or to any other competent authority so long as You provide Tyco with written notice of such request prior to such disclosure and cooperate with Tyco to obtain a protective order. Prior to disposing of any media reflecting or on which is stored or placed any Software, You will ensure any Software contained on the media has been securely erased or otherwise destroyed. You recognize and agree a remedy at law for damages will not be adequate to fully compensate Tyco for the breach of Sections 1, 2, or 10. Therefore, Tyco will be entitled to temporary injunctive relief against You without the necessity of proving actual damages and without posting bond or other security. Injunctive relief will in no way limit any other remedies Tyco may have as a result of breach by You of the foregoing Sections or any other provision of this Agreement.

11. DATA COLLECTION AND USE. You acknowledge and agree that the Software and/or hardware used in connection with the Software may collect data resulting from or otherwise relating to Your use of the Software and/or hardware ("**Data**") for purposes of providing You with service/product recommendations, benchmarking, energy monitoring, and maintenance and support. Tyco shall be the exclusive owner of all Data. Tyco shall have the right to de-identify Your Data so that it does not identify You directly or by inference (the "**De-Identified Data**"). Tyco shall have the right and ability to use the De-Identified Data for its business purposes, including improvement of the Software, research, product development, product improvement and provision of products and services to Tyco's other customers (collectively, "**Tyco's Business Purposes**"). In the event Tyco does not own or is unable to own the De-Identified Data as a result of applicable law, or contractual commitments or obligations, You grant Tyco a non-exclusive, perpetual, irrevocable, fully-paid-up, royalty free license to use, copy, distribute, and otherwise exploit statistical and other data derived from Your use of the De-Identified Data for Tyco's Business Purposes.

12. FEEDBACK. You may provide suggestions, comments, or other feedback (collectively, "**Feedback**") to Tyco and its affiliates with respect to their products and services, including the Software. Feedback is voluntary and Tyco is not required to hold it in confidence. Tyco may use Feedback for any purpose without obligation of any kind. To the extent a license is required under Your intellectual property rights to make use of the Feedback, You grant Tyco and its affiliates an irrevocable, non-exclusive, perpetual, world-wide, royalty-free license to use the Feedback in connection with Tyco's and its affiliates' businesses, including enhancement of the Software, and the provision of products and services to Tyco's customers.

13. GOVERNING LAW AND JURISDICTION.

a. This EULA is governed by and construed in accordance with the laws of the State of Wisconsin, as applied to agreements entered into and wholly performed within Wisconsin between Wisconsin residents. In the event the foregoing sentence is determined by a court of competent jurisdiction to not be enforceable or applicable to an action or proceeding brought by either party relating to or under this EULA, the parties agree to the application of the laws of the country in which You entered into this EULA to govern, interpret, and enforce all of Your and Tyco's respective rights, duties, and obligations arising from, or relating in any manner to, the subject matter of this EULA, without regard to conflict of law principles. The United Nations Convention on Contracts for the International Sale of Goods does not apply to any such action or proceeding.

b. Jurisdiction. Any action or proceeding brought by either party hereto shall be brought only in a state or federal court of competent jurisdiction located in Milwaukee, Wisconsin and the parties submit to the in personam jurisdiction of such courts for purposes of any action or proceeding. In the event the foregoing sentence is determined by a court of competent jurisdiction to not be enforceable or applicable to an action or proceeding brought by either party relating to or under this EULA, the parties agree all rights, duties, and obligations of the parties are subject to the courts of the country in which You entered into this EULA.

14. GENERAL. This EULA constitutes the entire understanding and agreement between the parties with respect to the transactions contemplated in this EULA and supersedes all prior or contemporaneous oral or written communications with respect to the subject matter of this EULA, all of which are merged in this EULA. This EULA shall not be modified, amended or in any way altered except by an instrument in writing signed by authorized representatives of both parties. In the event that any provision of this EULA is found invalid or unenforceable pursuant to judicial decree, the remainder of this EULA shall remain valid and enforceable according to its terms. Any failure by Tyco to strictly enforce any provision of this EULA will not operate as a waiver of that provision or any subsequent breach of that provision. The following provisions shall survive any termination or expiration of this EULA: Sections 3.a (Restrictions), 3.i (Compliance with laws), 4 (Third Party Software), 6 (Term and Termination), 7 (Fees and Taxes) (to the extent of any fees accrued prior to the date of termination), 9 (Limitation of Liability), 10 (Confidentiality), 11 (Data Collection and Use), 12 (Feedback), 13 (Governing Law and Jurisdiction), 14 (General), 15 (Export/Import), and 16 (U.S. Government Rights). Tyco may assign any of its rights or obligations hereunder as it deems appropriate. **IT IS EXPRESSLY UNDERSTOOD AND AGREED THAT IN THE EVENT ANY REMEDY HEREUNDER IS DETERMINED TO HAVE FAILED OF ITS ESSENTIAL PURPOSE, ALL LIMITATIONS OF LIABILITY AND EXCLUSIONS OF DAMAGES SET FORTH HEREIN SHALL REMAIN IN EFFECT.**

15. EXPORT/IMPORT. The Software is licensed for use in the specific country authorized by Tyco. You may not export or import the Software to another country without Tyco's written permission and payment of any applicable country specific surcharges. You agree to comply fully with all relevant and applicable export and import laws and regulations of the United States and foreign nations in which the Software will be used ("**Export/Import Laws**") to ensure that neither the Software nor any direct product thereof are (a) exported or imported, directly or indirectly, in violation of any Export/Import Laws; or (b) are intended to be used for any purposes prohibited by the Export/Import Laws. Without limiting the foregoing, You will not export or re-export or import the Software: (a) to any country to which the United States or European Union has embargoed or restricted the export of goods or services or to any national of any such country, wherever located, who intends to transmit or transport the Software back to such country; (b) to any user who You know or have reason to know will utilize the Software in the design, development or production of nuclear, chemical or biological weapons; or (c) to any user who has been prohibited from participating in export transactions by any federal or national agency of the U.S. government or European Union. You will defend, indemnify, and hold harmless Tyco and its affiliates and their respective licensors and suppliers from and against any and all damages, fines, penalties, assessments, liabilities, costs and expenses (including attorneys' fees and expenses) arising out of any Your breach of this Section.

16. U.S. GOVERNMENT RIGHTS. The Software is a "commercial item" as that term is defined at 48 CFR 2.101 (October 1995), consisting of "commercial computer software" and "commercial computer software documentation," as such terms are used in 48 CFR 12.212 (September 1995), and is provided to the U.S. Government only as a commercial end item. Consistent with 48 CFR 12.212 and 48 CFR 227.7202-1 through 227.7202-4 (June 1995), all U.S. Government End Users acquire the Software with only those rights set forth herein.

17. SPECIAL PROVISIONS FOR POWERMANAGE SOFTWARE. If the Software consists of or includes Tyco's PowerManage IP/GPRS-based Security Management Platform software, then the following additional provisions shall apply to Your use of the Software:

- a. Subject to purchasing the requisite number of licenses, You may use the Software to provide services to Your, and Your authorized dealer's end user customers ("**Customers**") to remotely access and use the end user functionality of the PowerManage Software, as installed on Your hardware, for the sole purpose of remotely configuring, managing and monitoring their intrusion systems, provided that You comply with all applicable privacy and other laws governing Your providing such services and access to Customers.
- b. You will not, and will not permit any dealer, Customer or other person reasonably within Your control to, rent, lease, sub-license, loan, copy, modify, adapt, merge, translate, reverse engineer, decompile, disassemble or create derivative works based on the whole or any part of the Software.
- c. You may establish terms and conditions for the engagement of Your dealers and the provision of services using the Software to Customers, provided that all such agreements are consistent with the terms of this EULA. You will be solely liable to Your dealers and Customers under the terms and conditions of such agreements. Tyco will not be bound by, and You will indemnify and hold harmless Tyco and its affiliates from any claims or demands of any third party arising out of or related to, the grant of any warranties, indemnities, or other terms and conditions greater in scope than those set forth in this EULA.
- d. You shall include statements in Your welcome kit and/or its agreement(s) with Customer's to remind them to keep secure their login and password details and comply with all applicable security policies.
- e. You shall be solely responsible for: (i) all services You offer and supply to Your dealers and Customers; (ii) all of Your, Your dealer and Customer content, posted, printed, stored, received, routed or created through the use of the Software, including both its content and accuracy; (iii) managing the provision of the service offered by You to Your Customers using the Software; and (iv) compliance with all privacy and other laws applicable to Your use of the Software and provision of services.
- f. You agree that You will comply with applicable all laws and regulations relating to the protection and privacy of the Personal Information of Customers and will utilize appropriate security, technical and organizational measures to protect against unauthorized or unlawful processing of Personal Information and against accidental loss or destruction of, or damage to, Personal Information, in connection with Your use of the Software. Personal Information means any information concerning an identifiable individual (including an End User), including information obtained from an End User through the use of Software, such as photos and video.
- g. You agree to indemnify Tyco and its affiliates for any claims, damages and expenses (including reasonable attorney's fees) related to Your or Your dealer's failure to comply with this Section 17.

Table of Contents

What's new in versions 4.8 and 4.10	11
4.8 updates.....	11
4.10 updates.....	11
Getting started	12
Introduction to PowerManage	12
Introduction to the PowerManage web help	12
Compatible systems	12
Regular tasks to perform	13
Setting up PowerManage.....	14
Server parameter configuration methods	14
PowerManage architecture	15
Navigating the user interface.....	16
Navigating the MY PROCESSES pane	21
Using the search filter	22
Logging on to the PowerManage system	24
Changing your logon password	24
Resetting a forgotten password	24
Configuring the server parameters by using the PowerManage web application	25
Configuring the server parameters by using the PowerManage Management Console.....	25
Panels page	26
Navigating the Panels page	26
Adding panels to the server.....	30
Adding a panel to the server	31
Servicing panels	32
Refreshing a panel configuration.....	33
Pushing a basic configuration to one or more panels	33
Assigning a panel to a different group	33
Reassigning one or more panels that are marked for service	33
Marking one or more panels for service on the Panels page	34
Resolving faults in one or more panels.....	34
Suspending faults in one or more panels.....	34
Creating a new report on the Panels page.....	34
Interactive users page.....	35
Navigating the Interactive users page	35
Running an inspection on the Panels page.....	35
Panel hub	36
Navigating the Panel hub.....	36
Devices tab.....	40
Navigating the Devices tab.....	40
Enabling METEO data for a group	48
Info tab	51
Navigating the Info tab	51
State tab.....	53

Configuration tab	55
Navigating the Configuration tab	55
Locations tab	59
Processes tab	59
Reports tab	60
Logs tab	61
Navigating the Logs tab	61
Remote inspections tab	63
Navigating the Remote inspections tab	63
Users Tab	65
Installers Tab	66
Assigning Installers	66
Events tab	67
Firmware tab	68
Navigating the Firmware tab	68
Upgrading the firmware of an individual panel in the panel hub	69
Keypad tab	70
Remote Inspection page	71
Navigating the Remote Inspection page	71
Remote inspection tests	73
Remote inspection values	74
Creating a remote inspection for a batch of panels	74
Scheduling one or more remote inspections for a batch of panels	75
Canceling a remote inspection	75
Running a remote inspection manually	75
Events page	76
Navigating the Events page	76
Examining event video on the Events page	77
Examining events on the Events page	78
Viewing an event or multiple events on the Events page	79
Reports page	80
Navigating the Reports page	80
Creating new reports	81
Creating a new report for all panels in the server	82
Stopping or removing a report from the Reports page	82
Firmware page	83
Navigating the Firmware page	83
Mass upgrading the firmware of a device	84
System drop-down menu	85
Settings page	85
Navigating the Settings page	85
General tab	87
Receiver tab	88
Resolve tab	89
Interactive tab	90

Message brokers tab	91
Creating a GET or POST request template	95
Substituting values in your GET or POST request template	96
GET or POST request example	97
Groups page	99
Navigating the Groups page	99
Processes page.....	108
Navigating the Processes page.....	108
Users page.....	110
Navigating the Users page.....	110
Roles page	115
Navigating the Roles page	115
Central stations page	118
Navigating the Central stations page	118
Basic configurations page	122
Navigating the Basic configurations page	122
Installers page	125
Navigating the Installers page.....	125
Dashboard page	129
PowerManage 4.8 updates	130
PIR camera zone association.....	130
Associating a PIR camera with a sensor.....	132
Using video on demand with ITv2 integration	132
PIR camera images during a system test.....	132
Upgrading 4G/LTE modems.....	133
Interactive user management	135
Panel search by customer information	137
Authorization settings for interactive users	139
Panel connection channel status.....	140
Viewing panel connection channels.....	140
Reading the diagnostics of a panel	141
Enabling or disabling temperature and light statistics for a group of panels with smart devices	143
Viewing GSM signal statistics	145
Integration session access keys for type 2 ITv2 panels.....	145
Customer information on the Panels page.....	146
Configuring the removal of events, processes, and reports from the server in rotation	147
Server CUSTOMER INFO tab in the system settings.....	148
PowerManage 4.10 updates	149
LTE modems upgrade for V18 panels.....	149
Dual path push notifications	149
Installers management.....	149
INSTALLER tab in panel pane	150
Incremental upgrade	150
VOD history	150
Offline handler tuning for DSC panels.....	151

CAUTION152

Process creator real name152

Log forwarding.....153

GSM/PowerG RSSI, temperature, and light statistic in reports153

Three separate private remark fields in panel info tab155

Stream new events – ON156

Customizable sounds156

Device ID filtering157

AC Fail false warning fix.....157

Recent history and Last visit widgets158

Interactive Users158

Secondary node group synchronization158

What's new in versions 4.8 and 4.10

4.8 updates

- [Associate PIR camera with up to eight sensors.](#)
- [Upgrade 4G/LTE modems for cellular panels.](#)
- [Interactive Users page includes additional management features.](#)
- [Panel search by customer information.](#)
- [Greater authorization settings for interactive users.](#)
- [View panel connection channel status.](#)
- [Panel diagnostics.](#)
- [Enable and disable temperature and light statistics for groups of panels with smart devices.](#)
- [View GSM signal statistics in the panel hub.](#)
- [Integration access keys are now unique to each of the four panels.](#)
- [View customer information on the panels page.](#)
- [Set the rotation time period to remove events, processes or reports from the server.](#)
- [Edit customer information in the system settings.](#)

4.10 updates

- [LTE modem upgrades.](#)
- [Custom event description defined on the dual path.](#)
- [Installers managed in the System page menu or in the INSTALLER tab.](#)
- [Incremental upgrade functionality.](#)
- [Multiple Video On Demand clips stored on the User Interface.](#)
- [Offline handler tuning for DSC panels.](#)
- [View the name and email of process creator.](#)
- [Tyco's technical support can configure the server for log forwarding.](#)
- [Include temperature, light and GSM RSSI statistics in reports.](#)
- [Multiple remark fields in the INFO tab.](#)
- [Stream new events turned on by default.](#)
- [Event sounds can be customized according to category.](#)
- [DEVICE ID search option added in the Panels pane.](#)
- [AC failure false warning fixed.](#)
- [Recent history and last visit widgets.](#)
- [Interactive Users in the main menu.](#)
- [Secondary node group synchronization.](#)

Getting started

Introduction to PowerManage

Use the PowerManage service management platform to manage panels remotely in real time from a central monitoring station (CMS) and with an internet protocol (IP) receiver.

Advantages of the PowerManage server:

- Receiver: PowerManage serves as an IP receiver for regular events and video events.
- Resolve: PowerManage enables home control and services such as reports, tests and panel configuration.
- Interactive: PowerManage enables users and installers to access the panel with the mobile application.

Introduction to the PowerManage web help

The PowerManage documentation provides monitoring service provider operators and IT managers instruction on managing the following:

- The PowerManage service management platform
- Security alarm panels
- Panel configurations
- Groups of monitored panels
- Alarms and events
- System tasks

Compatible systems

PowerManage supports the following security systems:

- Visonic PowerMaster and PowerMax panels
Note: Some PowerManage features do not exist in older panel versions.
- Neo panels with version 1.11 and later and communicators with version 4.11 and later
- PowerSeries Pro systems up to version 1.3
- SIA-IP protocol communication based monitoring systems
- Dual-path communicator

Supported NEO panels versions:

- HS2128: v.1.36
- HS2016: v.1.11, v.1.2, v.1.31, and 1.33.
- HS2016-4: v.1.11, v.1.2, v.1.31, and 1.33.
- HS2032: v.1.11, v.1.2, v.1.31, and 1.33.
- HS2064: v.1.11, v.1.2, v.1.31, and 1.33.

Supported NEO communicator versions:

- TL2803GRE: v.5.41, v.4.11 (Ethernet only), v.5.01, v. 5.02, v.5.03, v.5.11, v.5.21, and v.5.3.

Supported PSP panels versions:

- HS3248: v.1.30.xx.xxx
- HS3032: v.1.02.01.001, v.1.11.01.002, and v.1.20.01.029.
- HS3128: v.1.02.01.001, v.1.11.01.002, and v.1.20.01.029.
- HS3248: v.1.02.01.001, v.1.11.01.002, and v.1.20.01.029.

Supported Visonic panels versions:

- PowerMaster-10: v.20.213/214, v.E20.214, v.L20.213, v.R19.412, v.K18.415, v.K18.055, v.K17.133, v.K16.012, and v.I12.012.

- PowerMaster-30: v.20.213/214, v.E20.214, v.L20.213, v.R19.412, v.K18.415, v.K18.055, v.K17.133, v.K16.012, and v.I12.012.
- PowerMaster-360R: v.20.213/214, v.E20.214, v.L20.213, v.R19.412, v.K18.415, v.K18.055, v.K17.133, v.K16.012, and v.I12.012.
- PowerMax PRO (C17.108)

PowerLink software versions:

- x.x.94.14
- x.x.93.17
- x.x.92.6
- x.x.46
- 7.4/5.27

Regular tasks to perform

- View and handle security and maintenance events. For more information, see [Events page](#).
- Configure panels
- Diagnose and resolve panels
- Perform inspections, reports, and firmware upgrades. For more information about remote inspections, see [Remote inspections page](#). For more information about reports, see [Reports page](#). For more information about firmware upgrades, see [Firmware page](#).
- Enable and disable homeowner and installer access to panels by using the user and installer mobile applications. For more information, see user and installer apps in [Navigating the Installers page](#).
- Add new panels to the server. For more information, see [Adding a panel to the server](#).

Setting up PowerManage

1. Plan the permission framework.
 - a. To group similar panels together and perform common actions to large groups of panels at once, create panel groups. For more information on adding groups see [Adding a new group](#).
 - b. Add server users. For more information, see [Adding a new user](#).
 - c. To define the permissions of the server users, create roles to connect to each server user. For more information on creating roles and defining permissions, see [Roles page](#).
2. To organize the user hierarchy of the server, define the administrator and the operator accounts on [Users page](#).

Server parameter configuration methods

Configure the PowerManage server parameters with one of the following methods:

- The PowerManage application web site. For more information, see [Configuring the server parameters by the web application](#).
- The PowerManage Management Console. For more information, see [Configuring the server parameters by the console](#).

Related topics

[PowerManage architecture](#)

[Navigating the user interface](#)

[Navigating the MY PROCESSES pane](#)

[Using the search filter](#)

[Logging on to the PowerManage system](#)

PowerManage architecture




Figure 1: PowerManage architecture

Table 1. PowerManage architecture components

Callout	Description	Function
1	PowerManage server	The PowerManage server.
2	Receiver	<p>The PowerManage receives events from the panels by IP or GPRS communication and displays them on the server. The PowerManage then forwards the events to automation applications or central monitoring stations using the following protocols:</p> <ul style="list-style-type: none"> • Panels to server protocols: <ul style="list-style-type: none"> • Standard protocols, such as SIA, CID, and FIBRO • Proprietary protocols, such as power-net • Server to automation protocols: <ul style="list-style-type: none"> • Standard protocols, such as MLR-2 or FEP • Proprietary protocol, such as VISNAP
3	Resolve	Enables the server operator to control and view panel parameters, as well as run tests and create reports.
4	One-click	Click to view recent events and any related images or video clips in PowerManage.
5	VDCP protocol	Enables the operation of large numbers of panels simultaneously and enables PowerManage to connect to third party applications through a two-way interface. The two-way interface is a Python based program.
6	Interactive app	The user application enables homeowners to perform most operations that are permitted to a panel user. For example, homeowners can view the security system status, remotely arm or disarm the system, receive image verification and view historical logs on a mobile device or remote PC.
		The installer mobile application enables the installer to view and configure the panel remotely without visiting the customer's residence.

Navigating the user interface




Figure 2: Navigating the user interface

Table 2. User interface elements

Callout	Description	Function
1	Logo	Identifies the server that PowerManage is running on. Cloud means PowerManage is running on a cloud based server. The PowerManage logo means that it is running on a physical server. Click to view the version, build number, local time and time zone of the server. The PowerManage software version displays beside the PowerManage logo.
		To change the PowerManage logo to a custom logo, contact technical support.
2	Navigation pane	To view a page, click the page name in the navigation pane.
		If a menu option does not display for a server user, it can be due to any of the following reasons: <ul style="list-style-type: none"> The required privileges are not defined in the user's role. For more information on roles, see Roles page. The PowerManage server has licensing logic that removes some of the server's functionality. If pages are missing and it is not due to undefined privileges, contact technical support.
3	Search bar	Search a page by using by free typing or a number of search filter options. For more information, see Using the search filter .
4	User icon	Click the user icon to open a list with the following options: <ul style="list-style-type: none"> Settings: To define the following settings, from the user icon list, click Settings:

		<ul style="list-style-type: none"> • Language for the server user • Temperature standard units • Theme: light or dark • Automatic log out timeout • Alarm supervision settings • Turn on or off app notifications and notification sounds <ul style="list-style-type: none"> • Edit Profile: To edit the phone number and country of the server user, from the user icon list, click Edit Profile. • Change Password: To change the password of the server user, from the user icon list, click Change Password. • Help: To view the PowerManage web help, from the user icon list, click Help. • Logout: To log out of the PowerManage web user interface, from the user icon list, click Logout.
		<p>The user icon displays the initial of the first name of the user that is logged on. The initials DS display for the default super admin user icon. For more information about users, see Users page.</p>




Figure 3: Navigation Pane

Table 3. Navigation pane pages and lists

Callout	Description	Function
1	Recent History	<p>Displays all the panel ID's and their primary user emails that were visited by the current operator in the current session.</p> <p>Note:</p> <ul style="list-style-type: none"> • If operator does not enter any panel, then it does not appear. • If no user is assigned to the panel, then 'Unassigned' appears. • Clicking on a panel takes the operator to this panel. • Clicking the small black triangle beside the panel lists all panels connected to this primary user. The operator can click any of these panels and go to the panels.
2	Last Visit	<p>Displays the last panel ID and its primary user email that was visited by the current operator in the current session.</p> <p>Note:</p> <ul style="list-style-type: none"> • If operator did not enter any panel, then it does not appear. • If no user is assigned to the panel the 'Unassigned' appears. • Clicking the panel ID or the user email takes the user to this panel.
3	Interactive users page	<p>Manage user access to the panel with the mobile application on the Interactive users page. With this tab, the operator can manage panels according to users rather than panel ID which is managed with Panels page (callout 4) For more information, see Interactive users page.</p>
4	Panels page	<p>Manage the panels that are enrolled on the server. You can enroll panels manually or automatically. To enroll a new panel, see Adding a panel to the server. For more information about Panels page, see Panels page.</p>
		<p>To examine a panel in the panel hub, on the Panels page, click the panel name. For more information about the panel hub, see Panel hub.</p>
		<p>The sub-menus Faulty Panels and Suspended Faults are examples of preset saved search filters that are related to the Panels page. Click X to delete the saved search filter. For more information, see section 6 on Table 26. Search interface elements</p>
5	My Jobs page	<p>Lists all tasks initiated by the current operator in their session.</p>
6	Remote inspection page	<p>Open the Remote inspection page to view, run, and schedule health tests for the panels that are enrolled in the server. For more information, see Remote inspections page.</p>
		<p>To run or view a remote inspection for an individual panel, open the panel in the panel hub and go to the REMOTE INSPECTIONS tab. For more information, see Remote inspections tab.</p>
7	Events page	<p>The Events page displays all of the events that are received from all enrolled panels. For more information, see Events page.</p>
8	Reports page	<p>View, create, stop, and remove reports on the Reports page. Reports are in CSV or PDF format. For more information about reports, see Reports page.</p>
		<p>If you create a report on the Reports page, the report runs on all panels that are enrolled on the server. To create a report for an individual panel, see Creating a new report on the Panels page.</p>
9	Firmware page	<p>Mass upgrade the firmware of a group of panels or devices on the Firmware page. For more information, see Firmware page.</p>

10	System list	To manage issues related to the server, select the required page from the System list. Manage server issues related to the following categories: groups, processes, users, roles, action log, central stations, basic configurations, installers, and dashboard. For more information, see Table 6 .
----	------------------------	--




Figure 4: Navigating the system list

Table 4. System list pages

Callout	Description	Function
1	Settings page	Use the settings page to set up server configuration parameters. For more information, see Settings page .
2	Groups page	Manage panel groups on the Groups page. A group is a collection of panels that share the same configuration settings. For more information, see Groups page .
3	Processes page	View a list of all the processes that run on the server on the Processes page. For more information, see Processes page .
4	Users page	Create, remove, suspend, or enable server users on the Users page. For more information, see Users page .
5	Roles page	Manage the role types that you can assign to users. For more information, see Roles page .
6	Action log page	View all of the actions made by the user that is logged on. The Actions log page logs actions in chronological order. A Success or Failure status does not mean that an action finishes with success or failure, it indicates if the action started with success or failure.
7	Central stations page	PowerManage can also function as a receiver that forwards events from security panels to automation servers or central stations. Manage the information panels communicate on the Central stations page. For more information, see Central stations page .
8	Basic configurations page	Manage basic configurations that you can push to multiple panels at once in the Basic Configurations page. For more information, see Basic configurations page .
9	Installers page	Manage installer access to the panel with the mobile application on the Installers page. For more information, see Installers page .
10	Dashboard page	View the overall statistical data from the server in a visual format on the Dashboard page. For more information, see Dashboard page .

Related topics[Navigating the MY PROCESSES pane](#)[Using the search filter](#)

Navigating the MY PROCESSES pane

The **MY PROCESSES** pane displays the most recent processes run by the user on the current computer. To view more information about a process, in the **MY PROCESSES** pane, click the process.

For more information about all processes on the server, see [Processes page](#). For more information about the processes of an individual panel, see [Processes tab](#).




Figure 5: Navigating the My Processes pane

Table 5. MY PROCESS pane interface elements

Callout	Description	Function
1	Process status color	The colored line under each process signifies the following statuses: <ul style="list-style-type: none">Gray: The process has not started.Yellow: The process is in progress.Green: The process finishes successfully.Red: The process fails.
2		Click to remove all the processes from the processes pane.
3		Click to remove a process from the processes pane.

Related topics

[Navigating the user interface](#)

[Using the search filter](#)

Using the search filter

Filter the search by one of the following methods:

- Type a search term in the **Search** bar and click **SEARCH**.
- Select one or more key-value pairs in the **Search** list.

Begin to type key-value pairs and click the desired option in the auto-complete list.




Figure 6: Navigating the search filter

Table 6. Search interface elements

Callout	Description	Function
1	Selected filters	When you select a Search list key-value pair, the key-value pair saves in the Search bar as a filter. Filter the search to return a match of one or more key-value pairs that you set in the Search list.
		Click a filter in the Search bar to remove it from the search.
2	Search bar	Enter a term or key-value pair in the Search bar to search the selected page.
		Click the Search bar or start to enter a key or value in the Search bar and a list of options appears. Select a key and pair from the auto-complete list and the key-value pair saves in the Search bar.
3	Cancel search	Click to cancel a search.
4	Search list button	Click to filter the search with one or more key-value pairs.
		Click the search bar to select a key and a related value, one at a time.
5	SEARCH	Click to search the selected page with a filter or search.
6	SAVE CURRENT SEARCH	Click to save your key-value pairs as a preset search. The saved search appears in the navigation pane in a drop-down list under the related page name.
		Faulty Panels and Suspended Faults are examples of preset saved searches that appear under the Panels page in the navigation pane. To delete a saved search on the navigation pane, click the X next to it.
7	Selected values	Click a search value to add it to the selected filters in the search bar. You can only select one value per key. The key-value pairs change depending on the page that is selected.
		Use the scroll bar to scroll horizontally through the search keys and values.

Related topics

[Navigating the user interface](#)

[Navigating the MY PROCESSES pane](#)

Logging on to the PowerManage system

Access the PowerManage system with an email address and password. A user's email address and password identify the user and are set when the user is added to the server. For more information on adding a user to the server, see [Adding a new user](#). To change a user's email address, see [Editing user information](#).

For more information about logging in as the Default Super Admin, see [Default super admin](#).


The image shows a login form for the PowerManage system. The form is titled "PowerManage" at the top. Below the title, there is a "LOGIN" section. It contains two input fields: "Email" with the value "admin@tycomonitor.com" and "Password" with masked characters "*****". There is a "FORGOT PASSWORD?" link below the password field and a "LOGIN" button to the right.

Figure 7: PowerManage logon

Related topics

[Resetting a forgotten password](#)

[Changing your logon password](#)

[Users page](#)

Changing your logon password

1. Click the user icon in the upper-right of any page.
2. From the **User** list, select **Change Password**.
3. Enter your current password in the **Current Password** field.
4. Enter your new password in the **New Password** and **Confirm Password** fields.
5. Click **SAVE**.

Note: To change the password of a server user with fewer permissions, navigate to the user on the **Users** page and click the edit user icon. For more information, see Edit user in [Table 43](#).

Related topics

[Resetting a forgotten password](#)

[Logging on to the PowerManage system](#)

Resetting a forgotten password

1. From the **LOGIN** dialog box, click **FORGOT PASSWORD** in the lower-left corner.
2. Enter your registered email address in the email field and click **REMINDE**.
3. Log on to the email account of the address you provide and retrieve your new password.

Note: If you cannot find the email with the password reset in your inbox, check your spam folder.

4. Log on with your email address and new password.

Related topics

[Changing your logon password](#)

[Logging on to the PowerManage system](#)

Configuring the server parameters by using the PowerManage web application

1. Open a web browser.

Note: The PowerManage server does not support Internet Explorer or Opera.

2. Enter the IP address or the DNS name of your PowerManage server. For example, enter: `https://<server URL name>`.
3. To log on, enter the default username and password:
 - **Username:** `admin@tycomonitor.com`
 - **Password:** `Admin123`

Important: Change the default admin password as soon as possible. For more information, see [Changing your logon password](#).

Configuring the server parameters by using the PowerManage Management Console

Note: Use the Management Console to configure the server in the initial stages of the panel installation. It is also mandatory to use the Management Console to configure the internet connection during the setup stages. The Management Console is also referred to as MMI.

1. To log on to the PowerManage server, use an SSH program such as PuTTY, or use the web browser URL: `<power-manage DNS name>:2200`.
2. Enter the default username, `mmi`.
3. Enter the default password, `visonic`.

Note: If you log on for the first time, you are prompted to enter a new password after this step.

Panels page

Navigating the Panels page

You can view a list of all of the panels that are enrolled on the server on the **Panels** page.




Figure 8: Navigating the panels page

Table 7. Panels page interface elements

Callout	Description	Function
1	Last panel viewed	Click to view the last panel viewed in the panel hub.
2	Panel filter	<p>Customized search filters that you create for the Panels page appear here. For more information, see Using the search filter.</p> <p>The preset Faulty Panels and Suspended Faults search filters appear by default. Click Faulty Panels to filter the panels page to only display panels with faults. Click Suspended Faults to filter the panels page to only display panels with suspended faults.</p>
3	Check box	Select the check box of one or more panels to enable SERVICE , FAULTS , CREATE REPORT , and RUN INSPECTION .
4	Panel name and account	<p>Displays the panel name and panel ID. By default, the panel name is the panel ID. To change this to a custom name, edit the panel information in the panel hub. For more information, see EDIT in Table 10. For more information on changing the panel name or account, see Editing basic panel and customer information.</p> <p>Note: For Neo panels, the panel ID is the integration identification number. To find this number, enter [851] [422] in the panel keypad.</p> <p>Select the panel name to open the panel in the panel hub. For more information about the panel hub, see Panel hub.</p>
5	SERVICE	<p>To perform an action on one or more selected panels, from the SERVICE list, select one of the following options:</p> <ul style="list-style-type: none"> Change Group Refresh State Refresh configuration Push Basic Configuration

		<ul style="list-style-type: none"> • Trigger Discovery • Remove <p>For more information on servicing panels, see Servicing panels.</p> <p>To enable SERVICE, select the check box of one or more panel rows.</p>
6	FAULTS	<p>To perform an action on one or more selected panels, from the FAULTS list, select one of the following options:</p> <ul style="list-style-type: none"> • Mark for service • Reassign • Resolve faults • Suspend faults • Resume faults <p>For more information on servicing panels, see Servicing panels.</p> <p>To enable FAULTS, select the check box of one or more panel rows.</p>
7	CUSTOMER column	Displays the customer's first name. Click the customer's name to view more customer information. For more information, Customer information .
8	Customer information	<p>Click the customer's name to view the following customer information:</p> <ul style="list-style-type: none"> • Customer name • Customer email address • Customer phone number • Customer address • Any comments posted on the INFO tab
9	CREATE REPORT	<p>Click to create a new report for one or more selected panels. For more information about creating a report, see Creating new reports and Creating a new report on the Panels page.</p> <p>To enable CREATE REPORT, select the check box of one or more panel rows.</p>
10	GROUP column	<p>The group that the panel connects to displays in the GROUP column. For more information about groups, see Groups page.</p> <p>Click the group name to open the group hub. For more information about the group hub, see Group hub.</p>
11	RUN INSPECTION	<p>Click to create a new inspection for one or more selected panels. For more information about creating an inspection, see Creating a remote inspection for a batch of panels and Scheduling a remote inspection for an individual panel.</p> <p>To enable RUN INSPECTION, select the check box of one or more panel rows.</p>
12	Connection status	<p>The G icon represents a GPRS or cellular connection and the B icon represents an Ethernet or broadband connection. The color of an icon represents the following information:</p> <ul style="list-style-type: none"> • If an icon is gray, no communication channel is present. • If an icon is green, the communication channel is present and the server receives keepalive messages from the panel. • If an icon is blue, there is an open connection between the panel and the server. • If an icon is red, the communication channel is present but the server does not receive keepalive messages from the panel. • If an icon is black, keepalive messages are disabled in the

		<p>panels group.</p> <p>Note:</p> <ul style="list-style-type: none"> You can only disable keepalive messages for Neo panel groups. The icon, Bg, indicates that the cellular connection is through an Ethernet board.
13	Panel model	The model of the panel.
14	EVENTS column	The EVENTS column contains a summary of alarm and alert events. The bell symbol indicates an alarm and the warning symbol indicates an alert. For more information on events, see Event severity in Table 30 .
		Click the bell symbol to view a list of alarms from the panel and click the warning symbol to view a list of alerts from the panel.
		If there are no events, or all events are resolved, a green check mark displays.
15	FAULTS column	The FAULTS column displays any faults that affect the panel.
		Hover over a fault icon to see a detailed description of the fault. Click a fault to view a list of all faults from the panel.
		If a panel is marked for service, a user icon appears to the left of the FAULTS column with the initial of the user that is assigned to service the panel. For more information about marking or reassigning a panel for service, see Marking a panel for service in the Panels hub and Reassigning one or more panels that are marked for service .
16	Search bar	In the search bar, search for a panel with the key-value pairs or by typing a search term. You can also type a search term to find a panel with private data, such as name, phone number, email address, and home address, that is available in the INFO tab of a panel in the panel hub.
17	User and installer apps	<p>Click to open the user and installer apps dialog box and perform one of the following actions:</p> <ul style="list-style-type: none"> To allow a user to access the application by using the mobile application, turn on User App. To disallow a user to access the application by using the mobile application, turn off User App. To allow an installer to access the application by using the mobile application, turn on Installer App. To disallow an installer to access the application by using the mobile application, turn off Installer App.
18	ADD PANEL	Click to add a new panel to the server. For more information on adding a panel to the server, see Adding panels to the server .
19	RI column	The RI column displays the status of the last remote inspection.
		Click the RI icon to open the panel on the REMOTE INSPECTIONS tab in the panel hub. For more information about REMOTE INSPECTIONS tab, see Remote inspections tab .

Related topics

[Servicing panels](#)

[Adding panels to the server](#)

[Adding a panel to the server](#)

[Assigning a panel to a different group](#)

[Creating a new report on the Panels page](#)

[Marking one or more panels for service on the Panels page](#)

[Pushing a basic configuration to one or more panels](#)

[Reassigning one or more panels that are marked for service](#)

[Refreshing a panel configuration](#)

[Resolving faults in one or more panels](#)

[Suspending faults in one or more panels](#)

Adding panels to the server

Add a panel to the server on the **Panels** page.

Note: By default, panels auto-enroll on the server. To disable auto-enroll, contact technical support.

To add a panel, click **ADD PANEL** on the **Panels** page. For more information, see ADD PANEL in [Navigating the Panels page](#).

The screenshot shows a dialog box titled "ADD NEO PANEL" with a close button (X) in the top right corner. The dialog is divided into two main sections: "Panel Info" on the left and "Customer Info" on the right, which is enclosed in a dashed border. Callout 1 points to the "Panel type" dropdown menu in the "Panel Info" section, which currently shows "Neo". Callout 2 points to the "Panel Id" text input field. Callout 3 points to the "Account" text input field. Callout 4 points to the "Group" dropdown menu. Callout 5 points to the "Sim Number" text input field. Callout 6 points to the "Customer Info" section, which contains fields for "Name", "Email", "Phone", "Address", "Remark", "Remark 2", and "Remark 3". At the bottom of the dialog are "DISMISS" and "SAVE" buttons.

Figure 9: ADD PANEL dialog box

In the **ADD PANEL** dialog box, enter the panel information. See the following definition list for descriptions of the dialog box fields:

Table 8. ADD PANEL dialog box elements

Callout	Description	Function
1	Panel type	From the Panel type list, select the panel type.
2	Panel Id	In the Panel ID field, enter the panel identification number. Note: For Neo panels, enter the integration identification number in panel installer menu: [851] [422] .
3	Account	To connect the panel to an automation or central station, enter the ID number of the automation or central station in the Account field.
4	Group	From the Group list, select the group that you want to associate the panel with.
5	SIM number	In the SIM number field, enter the number of the SIM card in the panel. The number is used to send a wake-up SMS to the panel. Note: The SIM number is equivalent to a phone number.
6	Customer Info	Enter the customer's information in the Name , Email , Phone , Address , and Remark fields. Note: Apart from the Email field, this information is stored and not used.

Adding a panel to the server

1. In the navigation pane, select **Panels**.
2. On the **Panels** page, click **ADD PANEL**.
3. Enter the required information in the **ADD PANEL** dialog box fields. For more information on the **ADD PANEL** dialog box fields, see [Adding panels to the server](#).
4. Click **SAVE**.

Related topics

[Servicing panels](#)

[Navigating the Panels page](#)

Servicing panels

You can service an individual panel in the panel hub, or multiple panels at once in the **Panels** page. When servicing a panel with the **SERVICE** or **FAULTS** lists, see the following definitions:

Table 9. Panel servicing options

Action	Description
Change Group	Move one or more panels from one group to another. For more information about groups, see Groups page .
Refresh State	Refresh the most up-to-date information for one or more panels, such as the faults and panel status.
Refresh Configuration	Refresh the configuration parameters of one or more panels.
Push Basic Configuration	Push a custom basic configuration to one or more panels. For more information about creating a basic configuration, see Creating a basic configuration from an existing panel configuration .
Trigger Discovery	Start a discovery process. During the discovery process, the server uploads configuration parameters from the panel to the server. You can also select a timeout to determine how long the discovery process runs.
Remove	Remove one or more panels from the server. Note: If the server is set to auto-enroll and the panel is still connected to the server, the panel enrolls again.
Mark for service	Mark one or more panels for service. If you mark a panel for service, the service icon and the user icon of the user that the task is assigned to appear in the FAULTS column on the Panels page. The user icon features the initials of the assigned server user.
Reassign	Assign the service task of one or more panels to a different server user.
Resolve faults	Remove the service icon and user icon from one or more panels that are marked for service.
Suspend faults	Suspend a fault on one or more panels until a specified date. The fault icons become gray in the FAULTS column on the Panels page.
Resume faults	Resume suspended faults on one or more panels.

Related topics

[Navigating the Panels page](#)

[Panel hub](#)

[Adding panels to the server](#)

[Adding a panel to the server](#)

[Assigning a panel to a different group](#)

[Creating a new report on the Panels page](#)

[Enabling automatic panel enrollment](#)

[Marking one or more panels for service on the Panels page](#)

[Pushing a basic configuration to one or more panels](#)

[Reassigning one or more panels that are marked for service](#)

[Refreshing a panel configuration](#)

[Resolving faults in one or more panels](#)

[Suspending faults in one or more panels](#)

Refreshing a panel configuration

1. In the navigation pane, select **Panels**.
2. Select the check box of one or more panels to refresh.
3. From the **SERVICE** list, select **Refresh configuration**.

A **Download configuration** process appears in the **MY PROCESSES** pane.

Related topics

[Servicing panels](#)

[Navigating the Panels page](#)

Pushing a basic configuration to one or more panels

1. In the navigation pane, click **Panels**.
2. Select the check box of one or more panels to configure.
3. From the **SERVICE** list, select **Push Basic Configuration**.
4. In the **PUSH BASIC CONFIG** dialog box, select a basic configuration.
5. Click **PUSH**.

Related topics

[Servicing panels](#)

[Navigating the Panels page](#)

Assigning a panel to a different group

1. From the navigation pane, select **Panels**.
2. Select the check box of one or more panels to reassign.
3. From the **SERVICE** list, select **Change group**.
4. In the **ASSIGN PANEL TO GROUP** dialog box, select a group from the **Group** list.
5. Click **SAVE**.

Related topics

[Servicing panels](#)

[Navigating the Panels page](#)

Reassigning one or more panels that are marked for service

1. In the navigation pane, click **Panels**.
2. Select the check box of one or more panels to reassign.
3. From the **FAULTS** list, select **Reassign**.
4. In the **REASSIGN PANEL FOR SERVICE** dialog box, from the **To** field, select a user.
5. Enter a comment in the **Comment** field.
6. Click **SAVE**.

Related topics

[Servicing panels](#)

[Navigating the Panels page](#)

Marking one or more panels for service on the Panels page

1. In the navigation pane, click **Panels**.
2. Select the check box of one or more panels to mark for service.
3. From the **FAULTS** list, select **Mark for service**.
4. In the **MARK PANEL FOR SERVICE** dialog box, from the **To** field, select a user.
5. Enter a comment in the **Comment** field.
6. Click **SAVE**.

Related topics

[Servicing panels](#)

[Navigating the Panels page](#)

Resolving faults in one or more panels

1. In the navigation pane, click **Panels**.
2. Select the check box of one or more panels.
3. From the **FAULTS** list, select **Resolve faults**.
4. In the **RESOLVE FAULTS** dialog box, select one or more faults to resolve.
Note: Only resolvable faults appear.
5. Click **SAVE**.

Related topics

[Servicing panels](#)

[Navigating the Panels page](#)

Suspending faults in one or more panels

1. In the navigation pane, click **Panels**.
2. Select the check box of one or more panels.
3. From the **FAULTS** list, select **Suspend faults**.
4. In the **SUSPEND FAULTS** dialog box, select one or more faults to resolve.
5. Enter a date in the **Suspend until** field manually or with the calendar.
6. Click **SAVE**.

Related topics

[Servicing panels](#)

[Navigating the Panels page](#)

Creating a new report on the Panels page

1. In the navigation pane, click **Panels**.
2. Select the check box of one or more panels.
3. Click **CREATE REPORT**.
4. Enter a report name in the **Report Name** field and configure the settings to define your report. For more information on report settings, see [Creating new reports](#).
5. Click **SAVE**.

The report now appears on the **Reports** page.

Related topics

Interactive users page

Navigating the Interactive users page

View and manage interactive users on the **Interactive users** page.

Users connecting to the server with the mobile application appear on the **Interactive users** page. For more information on accessing the server with the mobile application, see [Registering a user on the server with the mobile application](#).


Two factor authentication increases the security of the user mobile application, ConnectAlarm, with the following stages:

1. The user submits an email address and registration details to the mobile application.
2. The user receives a code by email and enters the code in the mobile application.

Click the **STATUS** toggle to toggle between **Active** and **Suspended** statuses.

A **Not verified** status indicates the user did not finish the registration process and cannot connect panels to the user mobile application.

Filter your search of the **Interactive users** page by selecting one or more filter values from the **Search** list. From the **Search** list, select a filter value from one or more of the following keys: **STATUS**, and **CREATED**. For more information, see [Using the search filter](#).



EMAIL	CREATED	PANELS	STATUS
<input type="checkbox"/> example@email.com	03/11 1:45 PM	1 panel	<input checked="" type="checkbox"/> Active
<input type="checkbox"/> example1@email.com	03/12 10:53 AM	No panels	<input type="checkbox"/> Not verified
<input type="checkbox"/> example2@email.com	03/12 2:50 PM	No panels	<input checked="" type="checkbox"/> Active
<input type="checkbox"/> example3@email.com	03/12 2:52 PM	No panels	<input checked="" type="checkbox"/> Active
<input type="checkbox"/> example4@email.com	03/14 1:01 PM	No panels	<input type="checkbox"/> Not verified
<input type="checkbox"/> example5@email.com	03/18 2:04 PM	No panels	<input checked="" type="checkbox"/> Active
<input type="checkbox"/> example6@email.com	03/18 4:16 PM	No panels	<input checked="" type="checkbox"/> Active
<input type="checkbox"/> example7@email.com	Tuesday 5:44 PM	1 panel	<input checked="" type="checkbox"/> Active
<input type="checkbox"/> example8@email.com	Tuesday 5:46 PM	1 panel	<input checked="" type="checkbox"/> Active
<input type="checkbox"/> example9@email.com	Tuesday 5:48 PM	1 panel	<input type="checkbox"/> Not verified

Figure 10: Navigating the Interactive Users page

Related topics

[Registering a user on the server with the mobile application](#)

Running an inspection on the Panels page

1. In the navigation pane, click **Panels**.
2. Select the check box of one or more panels.
3. Click **RUN INSPECTION**.
4. Click **BEGIN NOW**.

Related topics

[Servicing panels](#)

[Navigating the Panels page](#)

Panel hub

Navigating the Panel hub

View and configure detailed information for an individual panel in the panel hub. For more information on viewing a panel in the panel hub, see [Viewing a panel in the panel hub](#).

The panel data is categorized by the following tabs. For more information, see Panel hub tabs in [Table 10](#).

- **DEVICES:** Manage all devices that connect to the panel. For more information, see [Devices tab](#).
- **CONFIGURATION:** Configure an individual panel and its zones, outputs, communication, and user settings. For more information, see [Configuration tab](#).
- **KEYPAD:** Use a virtual keypad interface. For more information, see [Keypad tab](#).
- **STATE:** Arm and disarm panels and partitions. For more information, see [State tab](#).
- **EVENTS:** View events related to a panel. For more information, see [Events tab](#).
- **USERS:** View and manage (add / remove and enable / disable) mobile-app users for the user-app (Connect Alarm).
- **INSTALLERS:** view and manage (add / remove) mobile app installers for the installer-app (Alarm Install).
- **LOGS:** View a panel's log files. For more information, see [Logs tab](#).
- **REMOTE INSPECTIONS:** Manage the remote inspections for a panel. For more information, see [Remote inspections tab](#).
- **REPORTS:** View all reports that have occurred or are scheduled for a panel. For more information, see [Reports tab](#).
- **PROCESSES:** View a list of all finished processes for a panel. For more information, see [Processes tab](#).
- **FIRMWARE:** Upgrade an individual panel's software and its connected devices. For more information, see [Firmware tab](#).
- **INFO:** View and edit general information about the panel and the customer, or leave comments about a panel. For more information, see [Info tab](#).

Note: Neo and Powerseries pro (PSP) panels require activation the first time you open the panel in the panel hub. If the message **This panel has not been activated yet and cannot be correctly managed from PowerManager** appears below the panel hub tabs, click **ACTIVATE**. In the **ACTIVATE PANEL** dialog box, enter the panel's installer code in the **Installer Code** field and click **ACTIVATE**. Another method to activate Neo and Powerseries pro (PSP) panels is to connect and log on to the panel using the AlarmInstall mobile application while in **Remote mode**. For more information, refer to *Accessing an alarm panel using Remote mode* in *Alarm Install App User Guide*.








Table 10. Panel hub interface elements

Figure 11: Panel hub

Callout	Description	Function
1	Last viewed panel	Click to view the last viewed panel in the panel hub.
		Displays panel ID and primary user of the panel. 'Unassigned' is displayed when primary user is not defined.
2	Online status	The bulb color signifies the status of the connection between the panel and the server. Hover over the bulb to see a text description of the connection status.
		   
3	Panel name	Displays the panel name and account number of the selected panel.
4	Status stream	<p>A stream of various statuses. The status stream may not be up-to-date if the online status bulb is not green.</p> <p>Note: A progress bar displays instead of the status stream if a discovery process is in progress.</p>
5	Panel hub tabs	Click a tab title to view the tab in the panel hub.

6	FAULTS	<p>To perform an action on the panel, from the FAULTS list, select one of the following options:</p> <ul style="list-style-type: none"> • Mark for service: Select to mark a panel for service. • Reassign: Select to assign the service task to a different server user. • Resolve faults: Select to remove the service icon and user icon from a panel that is marked for service. The fault is now resolved • Suspend faults: Select to suspend a fault until a specified date. The fault icons become gray in the FAULTS column. • Resume faults: Select to resume suspended faults.
7	ACTIONS	<p>To perform an action on the panel, from the ACTIONS list, select one of the following options:</p> <ul style="list-style-type: none"> • User App: Turn on to allow the user access to the panel using the user mobile application. Turn off to disallow the user access to the panel using the user mobile application. • Installer App: Turn on to allow the installer access to the panel using the installer mobile application. Turn off to disallow the installer access to the panel using the installer mobile application. • Trigger Discovery: Start a discovery process. During the discovery process, the server uploads configuration parameters from the panel to the server. • Edit: Click to edit the panel information. You can edit the panel account number, group, client type, and SIM number. • Remove: Click to remove the panel from the server. • Read Diagnostic: Reads the power statistics of the panel. To view the results when the process finishes, select the control panel in the DEVICES tab and then select the DIAGNOSTICS tab in the pane to the right. <p>Note: This option is available for Neo and PSP panels only.</p>
8	REFRESH	Click to receive a reading of the latest status change in the panel.
9	REMARK	Add and remove comments about the selected panel.

Related topics

[Marking a panel for service in the panels hub](#)

[Reassigning a panel for service in the panels hub](#)

[Resolving faults in a panel in the panels hub](#)

[Resuming faults in a panel in the panels hub](#)

[Suspending faults in a panels in the panels hub](#)

[Viewing a panel in the panel hub](#)

Viewing a panel in the panel hub

1. In the navigation pane, click **Panels**.
2. On the **Panels** page, navigate to the panel to view and click the panel name in the **PANEL** column.

Related topics

[Navigating the Panel hub](#)

Marking a panel for service in the panels hub

1. To open a panel in the panel hub, on the **Panels** page, click the panel name in the **PANEL** column.
2. From the **SERVICE** list, select **Mark for service**.
3. In the **MARK PANEL FOR SERVICE** dialog box, select a user from the **To** list.
4. Enter a comment in the **Comment** field.
5. Click **SAVE**.

Related topics

[Navigating the Panel hub](#)

Reassigning a panel for service in the panels hub

1. To open a panel in the panel hub, on the **Panels** page, click the panel name in the **PANEL** column.
2. From the **SERVICE** list, select **Reassign**.
3. In the **REASSIGN PANEL FOR SERVICE** dialog box, select a user from the **To** list.
4. Enter a comment in the **Comment** field.
5. Click **SAVE**.

Resolving faults in a panel in the panels hub

1. To open a panel in the panel hub, on the **Panels** page, click the panel name in the **PANEL** column.
2. From the **SERVICE** list, select **Resolve faults**.
3. In the **RESOLVE FAULTS** dialog box, click one or more faults to resolve.
Note: Only resolvable faults appear.
4. Click **SAVE**.

Related topics

[Navigating the Panel hub](#)

Suspending faults in a panel in the panels hub

1. To open a panel in the panel hub, on the **Panels** page, click the panel name in the **PANEL** column.
2. From the **SERVICE** list, select **Suspend Faults**.
3. In the **SUSPEND FAULTS** dialog box, click one or more faults to resolve, or select the **All** check box to select all of the faults.
4. Enter a date in the **Suspend until** field manually or with the calendar.
5. Click **SAVE**.

Related topics

[Navigating the Panel hub](#)

Resuming faults in a panel in the panels hub

1. To open a panel in the panel hub, on the **Panels** page, click the panel name in the **PANEL** column.
2. From the **SERVICE** list, select **Resume faults**.
3. In the **RESUME FAULTS** dialog box, click one or more faults to resume.
4. Click **SAVE**.

Related topics

[Navigating the Panel hub](#)

Devices tab

Navigating the Devices tab

Manage all devices that connect to a panel on the **DEVICES** tab.




Figure 12: Navigating the devices tab

Table 11. DEVICES tab interface elements

Callout	Description	Function
1	Troubles check box	To only display devices with troubles, select the Show devices with troubles check box.
2	REFRESH RSSI	<p>To refresh the Received Signal Strength Indication (RSSI) for the panel and its connected devices, click REFRESH RSSI.</p> <p>There are two types of radio frequencies: GPRS connects the panel to the server with a cellular modem and PowerG connects wireless devices to the panel. For more information on the GPRS RSSI of the panel, see Panel RSSI. For more information on the RSSI of a device, see Device RSSI.</p>
3	ADD DEVICE	Click to pre-enroll a new wireless device on the panel with the device enrollment ID and zone number.
4	WALK TEST	Click to perform a walk test on all eligible devices. A walk test discovers if wireless stationary devices are operational and reporting event information to the panel. See Performing a walktest on all eligible devices for more information.
5	Panel RSSI	<p>Displays the Received Signal Strength Indication of the panel's cellular connection.</p> <p>Note: The ? icon indicates that no RSSI measurement exists.</p>
6	Examination pane	The examination pane appears when you select a device on the DEVICES tab.
7	Examination pane tabs	<p>Depending on a device's features, the examination pane displays interactive tabs for the device.</p> <p>GENERAL: View general information about the device and perform general tasks on the GENERAL tab. On the GENERAL tab, you can view RSSI information, rename or remove a device, bypass or soak a device, and mark a device as rarely triggered.</p>

		<p>CONFIGURATION: On the CONFIGURATION tab, you can view and edit device configuration settings, such as the location, Rf-id number, enrollment method, zone type, chime and subtype. To ensure the information is up-to-date, click REFRESH. If no configuration is available, click DOWNLOAD NOW.</p>
		<p>VIDEO ON DEMAND: Appears if the device has video capturing capabilities. To view the video footage of video on demand device, click the VIDEO ON DEMAND tab. For more information, see Using the video on demand tab.</p>
		<p>PARENT: Appears if an auxiliary device is wired to a parent device. To view the parent device, click the PARENT tab. For more information, see Using the PARENT and CHILDREN tabs.</p>
		<p>CHILDREN: Appears if a parent device connects to an auxiliary wired device. To view the child device or devices, click the CHILDREN tab. For more information, see Using the PARENT and CHILDREN tabs.</p>
		<p>METEO: Appears if a device has smart sensing features. To view the temperature and light data of a smart detector, click the METEO tab. To find the smart sensing icon, see Smart sensing. For more information on the METEO tab, see Temperature and light readings on the METEO tab.</p>
		<p>FIRMWARE: Displays the relevant firmware upgrades that are available.</p>
		<p>CONNECTION STATUS: Displays the status of the IP and cellular communication channels.</p>
		<p>DIAGNOSTIC:</p> <p>Note: The DIAGNOSTIC tab feature is available for Neo and PSP panels only.</p> <p>Displays the power statistics of the panel. To refresh this information, open the panel in the Panel hub, click ACTIONS, then click Read Diagnostic. For more information, see ACTIONS in Table 10.</p>
		<p>TEMPERATURE/LIGHT STATISTIC: View all the previous temperature and light measurements of a device. This feature is only available for smart devices that can sense temperature and light. To enable temperature and light recording, see Enabling or disabling temperature and light statistics for a group of panels with smart devices.</p>
8	Bypass	To disable a device from triggering an alarm, select the Bypass check box. The device is not bypassed after the next arm or disarm state change.
9	Soak	To put a device in a soak state in order to monitor for false alarms, select the Soak check box. A device that is in a soak state does not create an alarm but a soak event.
10	Rarely triggered	<p>Device inactivity causes a remote inspection test to fail. If a device is not expected to trigger often, select the Rarely Triggered check box.</p> <p>Note: For more information on remote inspections, see Remote inspections tab.</p>
11	REMOVE	Click to remove a device from the panel
12	RENAME	<p>Click to rename a device</p> <p>Note: For PowerMaster panels the name saves on the server. For Neo and PSP panels the name saves as a label in the panel.</p>
13	Smart sensing	The smart sensing icon indicates that the device has smart temperature and light sensing features.

		If a device has the smart sensing icon, you view temperature and light readings on the METEO tab. For more information, see Temperature and light readings on the METEO tab .
14	Camera	The camera icon indicates that the device has video capabilities and you can view the device's video footage in the examination pane.
15	Partition	Displays the partition that the device is in. All indicates that the device is connected to all partitions.
16	Trouble icons	Displays all of the troubles that affect the device. Hover over an icon to see a description of the trouble.
17	Device type	Displays the device type. Examples of device types are contact, LCD keypad, and motion outdoor camera.
18	Device number	The device number refers to the zone number for a sensor and the index number for infrastructural devices, such as a keypad, siren, or repeater.
19	Device zone type	Displays the device's zone type. Examples of zone types are perimeter, home delay, interior follow, or fire.
20	Location	Displays the location of the device. Note: For PowerMaster panels, the location of zoned devices displays. For Neo/PSP panels, the label of the device displays.
21	Device RSSI	Displays the Received Signal Strength Indication of wireless devices or panels that have a cellular connection. Note: The ? icon indicates that no RSSI measurement exists.

Related topics

[Panel hub](#)

[Adding a wireless device to a panel](#)

[Bypassing, soak testing, and marking a device as rarely triggered](#)

[Editing the configuration of a device](#)

[Performing a walk test on all eligible devices](#)

[Putting a device in a soak test state](#)

[Refreshing the Received Signal Strength Indicator of a panel](#)

[Renaming or removing a device](#)

[Temperature and light readings on the METEO tab](#)

[Using the VIDEO ON DEMAND tab](#)

[Viewing device video footage](#)

[Viewing all devices with troubles in a panel](#)

[Viewing device smart temperature and light readings](#)

[Using the PARENT and CHILDREN tabs.](#)

Adding a wireless device to a panel

1. To open a panel in the panel hub, on the **Panels** page, click the panel name in the **PANEL** column.
2. Click **ADD DEVICE**.
3. Enter the enrollment identification number in the **Enrollment ID** field.

Note: The device ID is on the device's label, written in the following format: **ID: XXX-XXXX**. The first three digits of the identification number indicate the device type and the remaining four digits are unique to the device. For more information, see.

4. Enter the desired zone number or the device number.

5. Click **ADD**.

The device is now pre-enrolled. To complete the enrollment process, refer to the device manual.

Related topics

[Devices tab](#)

[Panel hub](#)

Refreshing the Received Signal Strength Indicator of a panel

1. To open a panel in the panel hub, on the **Panels** page, click the panel name in the **PANEL** column.
2. Click **REFRESH RSSI**.

Related topics

[Devices tab](#)

[Panel hub](#)

Viewing all devices with troubles in a panel

1. To open a panel in the panel hub, on the **Panels** page, click the panel name in the **PANEL** column.
2. Select the **Show devices with troubles** check box.

Related topics

[Devices tab](#)

[Panel hub](#)

Performing a walktest on all eligible devices

1. To open a panel in the panel hub, on the **Panels** page, click the panel name in the **PANEL** column.
2. To view the devices that are eligible for a walk test, click **WALKTEST**.

Note: To return to the **DEVICES** tab, click **DIAGNOSTICS**.

3. Click **START WALKTEST**.

Note: When you click **START WALKTEST**, the walktest begins and this button changes to **STOP WALKTEST**. To stop a walktest click **STOP WALKTEST**.

Note: The ? icon beside each device indicates the device has not yet passed the walktest. When the device triggers, the ? icon disappears to indicate that the device passes the test.

Important:

- Neo panel walktests ends if you click **STOP WALKTEST** or the test times out.
- PowerMaster panel walktests ends if all sensors are activated or the test times out.

Related topics

[Devices tab](#)

[Panel hub](#)

Bypassing, soak testing, and marking a device as rarely triggered

1. To open a panel in the panel hub, on the **Panels** page, click the panel name in the **PANEL** column.
2. On the **DEVICES** tab, select the device to bypass, soak test, or mark as rarely triggered.
3. On the **GENERAL** tab in the examination pane, select one of the following check boxes to perform the action:
 - Bypass
 - Soak
 - Rarely Triggered

Related topics

[Devices tab](#)

[Panel hub](#)

Renaming or removing a device

1. To open a panel in the panel hub, on the **Panels** page, click the panel name in the **PANEL** column.
2. On the **DEVICES** tab, click the device to rename or remove.
3. From the **GENERAL** tab in the examination pane, select one of the following options:
 - Click **RENAME** and enter a new device name in the **Name** field.
 - Click **REMOVE**.
4. To confirm, click **RENAME** or **REMOVE**.

Related topics

[Devices tab](#)

[Panel hub](#)

Editing the configuration of a device

1. To open a panel in the panel hub, on the **Panels** page, click the panel name in the **PANEL** column.
2. On the **DEVICES** tab, select a device to configure.
3. To view the device configuration settings in the examination pane, click the **CONFIGURATION** tab. To ensure the configuration is up-to-date, click **REFRESH**. If there is no configuration information, click **DOWNLOAD NOW** to download the most recent configuration data from the device.
4. Edit the required settings. To undo a change, click the undo arrow to the left of the field.
5. To upload the configuration changes to the panel, click **UPLOAD**. **UPLOAD** appears above the configuration when you edit at least one field.

Related topics

[Devices tab](#)

[Panel hub](#)

Using the VIDEO ON DEMAND tab

Note: The following panel setups have video on demand capabilities:

- All PowerMaster panels
- PSP panels with software 1.0, 1.1, and 1.2 that have a FIBRO connection
- PSP panels with software version 1.3 and later that have an ITv2 connection

To view device video on demand in the **VIDEO ON DEMAND** tab, on the **DEVICES** tab, select a device with the camera icon. For more information, see camera in [Navigating the Devices tab](#).

The installer can define during which panel states you can request video on demand, if the video has audio, and many other settings. For more information on changing the video on demand settings for all devices with video, see **CONFIGURATION** tab. For more information on changing the video on demand settings for an individual device with video, see the **CONFIGURATION** tab of the device on the **DEVICES** tab.




Figure 13: Navigating the VIDEO ON DEMAND tab

Table 12. VIDEO ON DEMAND tab interface elements

Callout	Description	Function
1	Device type	Displays the name of the device, remaining battery life, and PIR CAM details like zone type, zone name, zone number, sensor type and icons for sensor troubles and alarms.
2	Play button	Click to play the video and enlarge the screen.
3	VIDEO	Click to open the VIDEO ON DEMAND tab.

	ON DEMAND	
4	Forward skip arrow	Click to skip forward one frame.
5	Actions Menu	Click to display DOWNLOAD and REQUEST NEW VIDEO tabs.
		DOWNLOAD : Click to download the video locally.
		REQUEST NEW VIDEO : Click to record new video footage.
6	All Videos	Video on Demand clips can be viewed here. The maximum number of stored videos can be defined under menu: System -> Groups -> <select panel group, for example 'Main Group'> -> GENERAL tab -> VOD HISTORY LOG SIZE here you can view the max number of stored VOD files or press the EDIT GROUP button to change it
7	Frames and time	Displays the number of frames and the total duration of the video.
8	Location and time	Displays the time the event occurs and the location of the device.
9	Back skip arrow	Click to skip backwards one frame.

Related topics

[Devices tab](#)

[Panel hub](#)

Viewing device video footage

For more information about the **VIDEO ON DEMAND** tab, see [Using the video on demand tab](#).

1. To open a panel in the panel hub, on the **Panels** page, click the panel name in the **PANEL** column.
2. On the **DEVICES** tab, select a device that contains the video footage to view. A camera icon indicates that a device has video capabilities. For more information, see camera in [Navigating the Devices tab](#).
3. On the **VIDEO ON DEMAND** tab in the examination pane, click the play button in the center of the image to play the last recorded video.

Note: To view the footage frame by frame, click the left and right arrows on the video.

Related topics

[Devices tab](#)

[Panel hub](#)

Temperature and light readings on the METEO tab

View temperature and light readings from smart detectors on the **METEO** tab.

To find the **METEO** tab, in the **DEVICES** tab, select a smart detector and in the examination pane, click **METEO**. You can only open devices with the smart sensing icon in the **METEO** tab. For more information, see smart sensing in [Navigating the Devices tab](#).




Figure 14: Navigating the METEO tab

Table 13. METEO tab interface elements

Callout	Description	Function
1	Brightness graph	View the brightness readings over time. The x-axis represents the selected time period and the y-axis represents the brightness in lumens.
2	Temperature graph	View the temperature readings over time. The x-axis represents the selected time period and the y-axis represents the temperature in degrees Celsius.
3	METEO tab	Click to open the METEO tab.
4	SHOW	Click to view a more detailed graph.
5	Detailed graph	A more detailed version of the graph. Change the y-axis with a preset time period or manually change it to a custom time period. For more information, see Statistical period and Custom statistical period.
6	Custom statistical period	Click to enter custom time period dates that change the x-axis of the graph.
7	Graph line	Each point on the graph has multiple readings. The gray lines represent the minimum and maximum readings and the blue line is the average reading.
8	Statistical period	To change the x-axis of the graph with a preset time, click LAST DAY , LAST WEEK , LAST MONTH , or ALL .

Related topics

[Devices tab](#)

[Panel hub](#)

Viewing device smart temperature or light readings

1. To open a panel in the panel hub, on the **Panels** page, click the panel name in the **PANEL** column.
2. On the devices tab, select a device that contains the smart temperature or light readings to view. A light bulb icon indicates that a device has smart temperature or light readings. For more information, see Smart sensing in [Navigating the Devices tab](#).
3. On the **METEO** tab in the examination pane, click **SHOW** to view either the **Temperature** or **Brightness** graph in detail.
Note: If the METEO tab does not display, you must enable it. For more information, see Enabling METEO data for a group.
4. Select the time period to view in the examination pane by using one of the following methods:
 - To view preset time periods in the examination pane, click **LAST DAY**, **LAST WEEK**, **LAST MONTH**, or **ALL**.
 - To manually enter a time period, click the date field.

Note: The blue line indicates the average light or temperature value and the gray lines indicate the maximum and minimum values.

Related topics

[Devices tab](#)

[Panel hub](#)

Enabling METEO data for a group

1. In the navigation pane, from the System list, select **Groups**.
2. Select the group you want.
3. Click **EDIT GROUP**.
4. Enable **Temperature/light statistic**.

Using the PARENT and CHILDREN tabs

If a device has other devices connected to it, the connected device appears in the examination pane on the **PARENT** and **CHILDREN** tabs on the **DEVICES** tab in the panel hub. The **PARENT** tab appears in the examination pane if an auxiliary device is wired to a wireless parent device. Similarly, the **CHILDREN** tab appears if a wireless parent device connects to one or more auxiliary wired devices.




Figure 15: Using the PARENT tab

Table 14. PARENT tab interface elements

Callout	Description	Function
1	Child device	Click to open in the examination pane.
2	Parent device	The parent device of the selected device appears in the examination pane. Click to open the parent device in the examination pane.
3	PARENT tab	Appears if an auxiliary device is wired to a wireless parent device. To view the parent device, in the examination pane, click the PARENT tab.




Figure 16: Using the CHILDREN tab

Table 15. CHILDREN tab interface elements

Callout	Description	Function
1	Parent device	Click to open in the examination pane.
2	Child devices	Any child devices of the selected parent device appear in the examination pane on the CHILDREN tab.
		Click a child device to open it in the examination pane.
3	CHILDREN tab	Appears if a wireless parent device connects to one or more auxiliary wired devices. To view the child device or devices, in the examination pane, click the CHILDREN tab.

Related topics

[Devices tab](#)

[Panel hub](#)

[Editing the configuration of a device](#)

[Temperature and light readings on the METEO tab](#)

[Using the VIDEO ON DEMAND tab](#)

Info tab

Navigating the Info tab

View and edit general information about the panel and the customer on the **INFO** tab.

Leave comments about the panel on the **INFO** tab. If a panel fault is reassigned to a different user, the comment appears on the **INFO** tab. Users can reply to these comments.




Figure 17: Navigating the INFO tab

Table 16. INFO tab interface elements

Callout	Description	Function
1	PANEL INFO	The PANEL INFO section displays basic panel information such as PANEL NAME , PANEL ID and version information.
		To change the panel information, click EDIT to open the EDIT PANEL dialog box.
2	CUSTOMER INFO	The CUSTOMER INFO section displays basic panel information such as the customer name and address.
		To change this information, click EDIT to open the EDIT PANEL CUSTOMER INFO dialog box.
3	Data use policy	Personal customer data in the CUSTOMER INFO section is used for security purposes only.
4	SERVICE	To perform an action on one or more selected panels, from the SERVICE list, select one of the following options: <ul style="list-style-type: none"> • Mark for service • Reassign • Resolve faults • Suspend faults • Resume faults For more information on servicing panels, see Servicing panels .

5	Reassigned fault comment	If you reassign a fault, the information logs here with the initials of the person who reassigns the fault and any message the user leaves. Note: To reassign a fault, from the SERVICE list, click Reassign .
6	Options	Click to open the options dialog box.
7	REMOVE	To remove a reassigned fault comment, hover over the comment until three vertical dots appear. Click the dots and then click Remove .
8	Add note	To leave a comment, enter your comment in the Add note field and click the post button.
9	Comment	Comments that users leave appear in blue on the right hand side. To remove a comment, hover over the comment until three vertical dots appear. Click the dots and then click Remove .

Related topics

[Editing basic panel and customer information](#)

[Panel hub](#)

Editing basic panel and customer information

To edit basic panel information, or customer information related to a panel, complete the following procedure:

Note: Examples of basic panel information include the following: panel name, panel group, panel account number, and SIM number. Examples of panel customer information include the following: customer name, email address, home address, and phone number.

1. To open a panel in the panel hub, on the **Panels** page, click the panel name in the **PANEL** column.
2. Click the **INFO** tab.
3. Perform one of the following options:
 - To edit customer information, click **EDIT** in the **CUSTOMER INFO** section.
 - To edit panel information, click **EDIT** in the **PANEL INFO** section. Alternatively, click **EDIT** on the panel hub. For more information, see [Table 10](#).
4. Make the required changes.
5. Click **SAVE**.

Related topics

[Info tab](#)

State tab

Arm and disarm panels and partitions on the **STATE** tab.

Note: The Neo panel's **STAY** arm feature and Visonic panel's **HOME** arm feature have the same function but different names. Visonic panels do not have the **NIGHT** arm feature.







Figure 18 Navigating the STATE tab

Table 17. STATE tab interface elements

Callout	Description	Function
1	States	 Indicates a ready or armed state.
		 Displays when you change to a different panel menu or during an exit delay period. Examples of panels menus are the user menu, installer menu, and periodic test menu.
		 Indicates a not ready state. You cannot arm the panel until the panel is in a ready state. To return a panel to a ready state, ensure that all sensors are physically closed. Doors and windows are examples of zones that can physically close. If the issue is not physical, select the Show devices with troubles check box to see all of the devices with troubles in the examination pane and select the BYPASS check box to bypass devices with troubles.
2	Partition	Displays the name of the partition. To change the arm or disarm state for a partition, click AWAY , NIGHT , STAY , or DISARM . Note: The All row always appears first in the list. Use the All row to change the state of all partitions in the panel at once.
3	Arming options	The STAY/HOME and AWAY buttons have arming sub-options. To view the sub-options list, click the drop-down arrow. You can select NO ENTRY and NO EXIT from the STAY list, and NO ENTRY from the AWAY list. For the system to alarm when someone

		enters the perimeter, select NO ENTRY . For the system to alarm when someone exits the perimeter, select NO EXIT .
4	Arm state	The active state is blue.
5	Selected partition	Click the row of a partition to view it in the examination pane. Note: Partitions appear on the STATE tab if they are enabled in the panel. To enable panel partitions, enable and configure Partition set on the CONFIGURATION tab.
6	Troubles check box	Select to view all of the devices with troubles in the partition.
7	Device partition	Displays the name of the selected partition that features in the examination pane.
8	Trouble icons	Displays the types of troubles that affect the device. Hover over an icon to see a description of the trouble.
9	Associated partitions	A list of all of the partitions that associate with the device.
10	BYPASS	Select to bypass a device. If a panel is in a not ready state, bypass any troubled devices to return it to a ready state. The system bypasses the device until the next arm or disarm state change. For more information about states, see States.

Related topics

[Devices tab](#)

[Bypassing, soak testing, and marking a device as rarely triggered](#)

[Viewing all devices with troubles in a panel](#)

[Panel hub](#)

Configuration tab

Navigating the Configuration tab

Configure an individual panel and its zones, outputs, communication, and user settings on the **CONFIGURATION** tab. You can also save a panel configuration as a basic configuration that you can push to multiple panels.

To view a configuration on the **Configuration** tab, select a configuration from the current and previous panel configurations list. For more information, see [Current and previous panel configurations list](#).

You can only edit a configuration if it is the current configuration. For information on changing the configuration settings, see [Editing the configuration settings of an individual panel](#).

You can only download a panel configuration if the panel is connected to the server. The blue bulb indicates if the panel is connected. For more information, see Online status in [Table 10](#)

For information on pushing a basic configuration to one or more panels, see [Pushing a basic configuration to one or more panels](#).




Figure 19: Navigating the Configuration tab

Table 18. CONFIGURATION tab interface elements

Callout	Description	Function
1	Configuration date	Each configuration download is distinguished by the date of download.
2	Hidden characters	Secure information such as pass codes are hidden.
3	REFRESH	Refresh the page with the latest data from the panel.
4	SAVE AS BACKUP	Save configuration as a backup configuration.
5	MAKE BASIC	Click to make the configuration a basic configuration that you can push to other panels. Find the basic configurations on the Basic configurations page in the System drop-down list. For more information, see Basic configurations page . For more information about making a basic configuration, see Creating a basic configuration from an existing panel configuration .

6	Compare with backup	Compare current configuration with the backup configuration.
7	Show only changed	Click to show only the configuration settings that you changed. You can only edit a configuration if it is the current configuration. For more information, see Current and previous panel configurations list .
8	Quick search	Filter the configuration to return only values that contain the search term.
9	TABLE OF CONTENTS	Use the table of contents to navigate the configuration quickly. The table of contents is categorized and expandable.

Related topics

[Panel hub](#)

[Devices tab](#)

[Creating a basic configuration from an existing panel configuration](#)

[Current and previous panel configurations list](#)

[Editing the configuration settings of an individual panel](#)

[Synchronizing the configuration of an individual panel](#)

Current and previous panel configurations list

View and edit up to eight panel configurations for an individual panel in the configurations list. The configurations are ordered by the date of download. Select a configuration to view it in the **CONFIGURATION** tab. For more information, see [Configuration tab](#).

If a panel is newly registered on the server, click **DOWNLOAD NOW** to download the panel configuration to the server.




Figure 20: Navigating the panel configurations list

Table 19. Configuration list interface elements

Callout	Description	Function
1	Current configuration	You can edit the current configuration only. Click to view or edit.
2	Previous configurations	View seven previous configurations in the PREVIOUS list.
		If you download a new configuration, it overwrites the oldest configuration in the PREVIOUS list. To ensure a configuration is not overwritten, click the bookmark icon.
3	REFRESH	Click to refresh the configurations list.
4	Compare configuration	Click to compare the configuration with the current configuration.
5	Bookmark	To ensure a configuration from the PREVIOUS list is not overwritten by new configurations, click the bookmark icon. You can only save seven previous configurations at a time from the PREVIOUS list.

Related topics

[Configuration tab](#)

[Creating a basic configuration from an existing panel configuration](#)

[Editing the configuration settings of an individual panel](#)

[Synchronizing the configuration of an individual panel](#)

[Devices tab](#)

Creating a basic configuration from an existing panel configuration

1. To open a panel in the panel hub, on the **Panels** page, click the panel name in the **PANEL** column.
2. From the **CONFIGURATION** tab, click **REFRESH** to synchronize the panel and the server.
3. **Important:** Click **REFRESH** in the **CONFIGURATION** tab, not **REFRESH** above the panel hub tabs. From the **CURRENT** list, select the current panel configuration.
4. Click **MAKE BASIC**.
5. Select the check boxes of the settings to include in the basic configuration.
6. Click **CREATE**.
7. Enter a unique name in the **Basic configuration name** field.
8. Click **SAVE**.

Related topics

[Configuration tab](#)

[Creating a basic configuration from an existing panel configuration](#)

[Current and previous panel configurations list](#)

[Editing the configuration settings of an individual panel](#)

[Synchronizing the configuration of an individual panel](#)

[Devices tab](#)

Synchronizing the configuration of an individual panel

1. To open a panel in the panel hub, on the **Panels** page, click the panel name in the **PANEL** column.
2. From the **CONFIGURATION** tab, click **REFRESH**.

Related topics

[Configuration tab](#)

[Creating a basic configuration from an existing panel configuration](#)

[Current and previous panel configurations list](#)

[Editing the configuration settings of an individual panel](#)

[Devices tab](#)

Editing the configuration settings of an individual panel

1. To open a panel in the panel hub, on the **Panels** page, click the panel name in the **PANEL** column.
2. To synchronize the panel and the server, from the **CONFIGURATION** tab, click **REFRESH**. **Note:** If there is no refresh option, select **DOWNLOAD NOW**.
3. From the **CURRENT** list, select the current panel configuration.
4. Make the required changes and select the **Show only changed** check box to review your changes.
5. Click **UPLOAD**.

Related topics

[Configuration tab](#)

[Creating a basic configuration from an existing panel configuration](#)

[Current and previous panel configurations list](#)

[Synchronizing the configuration of an individual panel](#)

[Devices tab](#)

Locations tab

Provide custom location names to zones for ease of reference.

Note: The **LOCATIONS** tab only appears in the panel hub for PowerMaster panels.




Figure 21: Locations tab

Table 20. LOCATIONS tab interface options

Callout	Description	Function
1	Show only editable locations	To view only locations that you can rename, select the Show only editable locations check box.
2	SAVE LOCATIONS	<div>To rename a location, type a new name in at least one field and click SAVE LOCATIONS.</div> <div>Enter a maximum of 15 characters in any field. Type only the following characters only in the location fields: A-Z, a-z, 0-9, !, @, #, %, ^, &, _, +, =, -, ' , " , : , /</div>

Related topics

[Devices tab](#)

[Panel hub](#)

Processes tab

View a list of all processes for the selected panel on the **PROCESSES** tab. Each row represents a single process. Each process displays with a start time, description, current status, process initiator name, and duration.

Click **X** to cancel a process.

To view a list of all recent processes for all of the panels that are enrolled in the server, in the navigation pane, from the **System** list, select **Processes**. For more information about the **Processes** page, see [Processes page](#).

Related topics

[Devices tab](#)

[Processes page](#)

[Panel hub](#)

Reports tab

View reports that have occurred or are scheduled to occur for an individual panel on the **REPORTS** tab. The tab displays this information on a calendar.




Figure 22: Navigating the reports tab

Table 21. **REPORTS** tab interface elements

Callout	Description	Function
1	Today	Click TODAY to return to the current month.
2	Month and year selector	The calendar displays one month or one year at a time. To change the month or year, click the arrows to the left of the month name. To change from the month view to the year view, click the button between the arrow selectors.
3	Select month	Click a month to open the calendar month in the viewer.
4	Current date or month	A blue circle indicates the current day or month.
5	Report	All reports appear in the calendar and each report is a different color.
		Select a report to display the file download options. Click CSV or PDF to download the report in the chosen format. PDF is a more readable file type than CSV.
6	CREATE REPORT	Click to create a new report. For more information, see Creating new reports .

Related topics

[Reports page](#)

[Creating a new report on the Panels page](#)

[Creating a new report on the Reports page](#)

[Devices tab](#)

[Panel hub](#)

Logs tab

Navigating the Logs tab

View log files on the **LOGS** tab. Log files record all events that occur in the panel.



Figure 23 Navigating the LOGS tab

Table 22. LOGS tab interface elements

Callout	Description	Function
1	Event number	Each event in the panel has a number that identifies the event type.
2	Event time	Displays the time that the server receives the event notification from the panel.
3	Event description	A textual description of the event.
4	Date	Events are grouped by the day they occur.
5	Event source ID	<p>Displays the ID of the source of the event.</p> <ul style="list-style-type: none"> The source ID for a sensor is its zone number. The source ID for an arm or disarm state change is the user number of the user who changed the arm state. The source ID for an action that the panel performs is the panel name. <p>Note: The source ID is followed by the number of the partition that the event occurs in.</p>
6	REFRESH	Click to download the most up-to-date log file on the LOGS tab.
7	DOWNLOAD CSV	Download a CSV file of the events log.
8	Standard and legacy logs	Click STANDARD LOG or LEGACY LOG to display the log list on the LOGS tab.
		<p>Users can view and erase the standard log.</p> <p>Security operators and systems use the legacy log. The legacy log appears for</p>
		PowerMaster panels only.

Related topics

[Downloading a panel log file in the Panels hub](#)

[Devices tab](#)

[Panel hub](#)

Downloading a panel log file in the panels hub

1. To open a panel in the panels hub, click the panel name in the **PANEL** column of the **Panels** page.
2. From the **LOGS** tab, click **DOWNLOAD CSV**. The file downloads in the browser.

Related topics

[Logs tab](#)

[Devices tab](#)

[Panel hub](#)

Remote inspections tab

Navigating the Remote inspections tab

Manage the remote inspections for a single panel on the **REMOTE INSPECTIONS** tab in the panel hub.

For more information on remote inspections, see [Remote inspections page](#).

Figure: Navigating the REMOTE INSPECTIONS tab






Figure 24: Navigating the remote inspections tab

Table 23. REMOTE INSPECTIONS tab interface elements

Callout	Description	Function
1	TODAY	Click to return to today's date.
2	Year and month filter	Use the arrows to navigate the remote inspections by year or month on the calendar interface. When you are in the monthly view, click the button between the arrows to return to the annual view.
3	Month	Select the month to open it in the viewer. The current month is highlighted.
4	Inspection	All scheduled remote inspections appear in the calendar. The reports colors indicate the following test statuses: <ul style="list-style-type: none"> Red: the test failed Green: the test succeeded
5	Send email	Click the email icon to send the results of the remote inspection to a predefined email address. <p>Note:</p> <ul style="list-style-type: none"> Define the email address when you add a panel on the Panels page. For more information, see Adding a panel to the server. Change the email address on the INFO tab. For more information, see Editing basic panel and customer information.
6	Viewing status	<div>   </div> <p>Click to mark the remote inspection as viewed.</p> <p>The remote inspection is viewed. Only mark a remote inspection as viewed if your investigation is complete.</p>
7	START INSPECTION	Click to initiate the selected remote inspection

8	SCHEDULE INSPECTION	Click to schedule the selected remote inspection to occur at a specific date and rate of recurrence. For more information, see Scheduling a remote inspection for an individual panel .
9	Examination pane	To examine the results of a remote inspection in the examination pane, click the remote inspections row. Select a section title to expand the test results. For more information on each test, see Remote inspection tests .

Related topics

[Remote inspection tests](#)

[Remote inspection page](#)

[Devices tab](#)

[Panel hub](#)

Scheduling a remote inspection for an individual panel

Note: To schedule a remote inspection for a batch of panels, see [Scheduling one or more remote inspections for a batch of panels](#).

1. To open a panel in the panel hub, on the **Panels** page, click the panel name in the **PANEL** column.
2. On the **REMOTE INSPECTIONS** tab, click **SCHEDULE INSPECTION**.
3. In the dialog box, select **Enabled**.
4. Enter the required date in the **Next Inspection** field.
5. In the **Choose repetition** field, select how often you want the test to occur. You can select **Once**, **1 Month**, **3 Months**, **6 Months**, or **9 Months**.
6. Click **SAVE**.

Related topics

[Remote inspections tab](#)

[Scheduling one or more remote inspections for a batch of panels](#)

[Remote inspection tests](#)

[Remote inspection page](#)

[Devices tab](#)

[Panel hub](#)

[Users](#)

[Installers](#)

Users Tab

Lists all the users registered on the mobile app. Mobile app users are defined as interactive users. Each user shows its **ROLE**, **LABEL** (name) **EMAIL**, when he was registered and his status. Checking the **Show unassigned users** box shows all the users in the panel that are not set as interactive users or users of the mobile app.

Pressing **+ ASSIGN USER** pops up a menu to enter the new-user email and the user number in the panel.




Figure 25: Navigating the user tab

Table 24 Users tab interface elements

Callout	Description	Function
1	Show unassigned users	Select the Show unassigned users check-box to display all the free panel users that can be assigned.
2	ASSIGN USER	Allows the administrator to assign a new user to the panel or to select an existing user from the drop-down menu. If a new email is entered, it will initiate a two-factor authentication (2FA) request.
3	Assigned users	Lists the assigned users and displays their role, label, email address, registration date, and status.
4	- icon	Removes the users of the panel that are not assigned as interactive users. The user remains on the server.
5	Unassigned	Lists users of the panel that are not assigned as interactive users.

Installers Tab

Displays all the installers that are assigned to the panel.

Assigning Installers




Figure 26: Navigating the installers tab

Table 25 Installer tab interface elements

Callout	Description	Function
1	Assign Installer	Click to assign installer to the panel.
2	Drop down menu	Displays registered installers. The operator can choose a registered installer from the list or enter a new email to register a new installer which initiates a 2FA process.
3	Save	Saves installer.
4	- Icon	Removes the user from the panel. The user remains on the server.



Events tab

View events related to a single panel on the **EVENTS** tab.



Figure 27: Navigating the events tab

Table 26. EVENTS tab interface elements

Callout	Description	Function
1	Event time	The time the event occurs.
2	Video content	The camera icon indicates that the event has video footage that you can view on the EVENT VIDEO tab.
3	Event description	A description of the alarm type. For more information, see Event severity in Table 30 .
4	Selected event	Select an event row to view information about the related device in the examination pane.
5	LOAD OLDER	Click to load older events. By default, only 10 events display on the EVENTS tab.
6	Device number and partition	Displays the device number and its partition.
7	Viewing status	<div>  Click the icon to mark the event as viewed. </div> <div>  The event is viewed. Only mark an event as viewed if your investigation is complete. </div>
8	EVENT VIDEO tab	The EVENT VIDEO tab appears if the selected device has a camera. Select the EVENT VIDEO tab to view the video footage related to the event.
9	Video footage	If an event has video, view the video footage here. <ul style="list-style-type: none"> Click play to view video footage. Click the arrows to view the footage frame by frame. Click DOWNLOAD to download the video file locally. For more information about viewing event video footage, see Viewing event video footage in the events tab.

10	LIVE VIDEO tab	Click the LIVE VIDEO tab to view live video footage from the source device. The live video stream lasts five seconds. Note: The LIVE VIDEO tab appears for Visonic panels only. You can enable or disable live video on demand capabilities during specific states only, such as an armed state. Define the video demand settings in the Video on demand field on the panel CONFIGURATION tab.
11	Device information	General information about the source of the event, such as a device.

Related topics

[Events page](#)

[Viewing event video footage in the events tab](#)

[Devices tab](#)

[Panel hub](#)

Firmware tab

Navigating the Firmware tab

Upgrade an individual panel's software and its connected devices on the **FIRMWARE** tab.

For Visonic panels, you can only upgrade panels and the power link. For Neo panels, you can upgrade the panel, the communicator, and any wired devices and modules. For more information about upgrading panels, devices, and modules, see [Firmware page](#).




Figure 28: Navigating the firmware tab

Table 27. **FIRMWARE** tab interface elements

Callout	Description	Function
1	APPLIANCE	Displays the appliance.
2	CURRENT VERSION	Displays the current software version of the appliance.
3	Do not upgrade	By default, no package is selected from the APPLY PACKAGE list.
4	APPLY PACKAGE	Find packages that are available for upgrade in the APPLY PACKAGE column. Note: T.3 tech support loads upgrade packages to the repository server.
5	APPLY PACKAGE drop-down	Select an upgrade package from the APPLY PACKAGE list.
6	UPGRADE	Click upgrade to upgrade an appliance to the selected package. For more information, see Upgrading the firmware related to an individual panel in the Panels hub .

Related topics

[Firmware page](#)

[Upgrading the firmware related to an individual panel in the Panels hub](#)

[Devices tab](#)

[Panel hub](#)

Upgrading the firmware of an individual panel in the panel hub

1. To open a panel in the panel hub, on the **Panels** page, select the panel name in the **PANEL** column.
2. On the **FIRMWARE** tab, select the device to upgrade.
3. From the **APPLY PACKAGE** list, select an upgrade package.
4. Click UPGRADE

Related topics

[Firmware tab](#)

[Firmware page](#)

[Devices tab](#)

[Panel hub](#)

Keypad tab

Use a virtual keypad interface on the **KEYPAD** tab. To open a virtual keypad on the **KEYPAD** tab, click **CONNECT NOW** to connect to the physical keypad.

Important: Click **DISCONNECT** after you use the virtual keypad to disconnect from the physical keypad. If you do not disconnect, a communication backlog occurs and no other virtual keypad can connect. For more information, see Disconnect in [Table 28](#).

Note: You can use the virtual and physical keypads simultaneously with Visonic panels. If you activate a Neo or PSP virtual keypad, the physical keypad deactivates.




Figure 29: Navigating the Keypad tab

Table 28. KEYPAD tab interface elements

Callout	Description	Function
1	Sound toggle	Turn on Sound enabled to enable the sound of keypad notifications.
2	Virtual keypad	The virtual keypad mirrors the keypad buttons and the live LED and LCD display of the physical keypad. The LED display features the power status, trouble status, WAN, and WiFi connectivity icons.
3	Log	The log file records all messages between the keypad and the panel.
4	FILTER	To show only a specific category of message, from the FILTER list, select any of the following options: <ul style="list-style-type: none">• Key: Display messages related to key presses only• Leds: Display messages related to LED status only• Text: Display messages related to LED text only
5	CLEAN	Click to erase the log
6	DOWNLOAD	Click to download the log locally
7	DISCONNECT	Click when you finish using the virtual keypad. Some physical keypads cannot function when the virtual keypad is connected.

Related topics

[Devices tab](#)

[Panel hub](#)

Remote Inspection page

Navigating the Remote Inspection page

A remote inspection is a series of nine tests that check a panel remotely for any faults that affect the system and its functionality. If at least one of the nine tests fail, the inspection fails. For more information about each inspection test, see [Remote inspection tests](#).

Tests can be performed once or periodically. Finished remote inspections appear at the top of the page and uninitiated tests appear at the bottom of the page.

Filter your search of the **Remote Inspection** page by selecting one or more filter values from the **Search** list. From the **Search** list, select a filter value from one or more of the following keys: **NAME**, **ACCOUNT**, **PANEL ID**, **GROUP**, **LAST RRI**, **NEXT RRI**, **EMAIL SENT**, and **REVIEWED**. For more information, see [Using the search filter](#).




Figure 30: Navigating the Remote Inspections page

Table 29. Remote inspection page interface elements

Callout	Description	Function
1	Check box	Select one or more check boxes to perform an action.
		Select a check box to enable MARK AS VIEWED , SCHEDULE , and RUN .
2	Failed test	Red text indicates that the test is complete and that there was at least one failure.
3	Successful test	Green text indicates that the test is complete and that no failure is found.
4	Selected test	Click a completed test to view it in the examination pane.
5	MARK AS VIEWED	Click to mark one or more remote inspections as viewed. MARK AS VIEWED appears when you select a check box.
6	SCHEDULE	Click to schedule one or more reports. SCHEDULE appears when you select a check box.

7	RUN	Click to run one or more reports immediately. RUN appears when you select a check box.
8	Email icon	Email the results of the completed remote inspection to a user. This has the same function as SEND EMAIL . Note: For PowerMaster panels, the email address is defined in the private panel report. For Neo and PSP panels, the email address is defined on the INFO tab. For more information on the INFO tab, see Info tab .
9	Mark as viewed icon	Click to mark the completed remote inspection as viewed. This has the same function as MARK AS VIEWED .
		If a remote inspection is viewed, hover over the icon to see who viewed the report and when.
10	Schedule icon	Click the schedule icon to schedule a remote inspection or stop a scheduled remote inspection. This has the same function as SCHEDULE .
11	Run icon	Click to run a report immediately. This has the same function as RUN .
12	Progress tracker	Displays the completion percentage of a report that is in progress.
13	Result color	When you view a report in the examination pane, the report title color indicates success or failure. <ul style="list-style-type: none"> • If the report title is green, the test is successful • If the report title is red, the test is unsuccessful. • If the report title is gray, the test did not complete due to lack of information. Note: To see a description of each test, see Remote inspection tests .
14	MARK REVIEWED	Click to mark a completed remote inspection as reviewed. This has the same function as MARK AS VIEWED . Note: If the report is already reviewed, this text is gray.
15	SEND EMAIL	Click to email the results of a completed remote inspection to a user that is defined in the private report in the panel. This has the same function as the email icon.
16	SETTINGS	Click to configure the general remote inspection settings. For more information, see Remote inspection values .
17	RUN	Click to run a report again immediately. This has the same function as Run icon and RUN .
18	UPLOAD SCHEDULE	Click to create a new remote inspection schedule. For more information, see Creating a remote inspection for a batch of panels .
19	Examination pane	Click a report to review the results in the examination pane. Note: To see a description of each test, see Remote inspection tests .
20	Next report	Click the arrow to review the next report in the test results window. Note: Click the arrow on the opposite side of the test results window to review the previous report.

Related topics

[Remote inspection tests](#)

[Remote inspection values](#)

[Creating a remote inspection for a batch of panels](#)

[Canceling a remote inspection](#)

[Running a remote inspection manually](#)

[Scheduling one or more remote inspections for a batch of panels](#)

Remote inspection tests

When you view a completed remote inspection in the examination pane, see to the following definitions:

Note: For more information about the examination pane, see Examination pane in [Table 29](#).

Active faults

The **Active Faults** test is an inspection that checks the panel for faults that currently affect the operation of the panel.

Check clock

The **Check Clock** test is an inspection that checks if the time difference between the panel clock and the server clock is greater than the value set in [Remote inspection values](#).

GPRS

The **GPRS** test is an inspection that checks for a GPRS heartbeat. The GPRS test passes in one of the following cases:

- The GPRS module does not exist. The test title displays in the color gray.
- The GPRS module exists but the keepalive messages are disabled. To disable or enable keepalive messages, see the **GPRS Keep Alive Enabled** toggle in [Group parameters](#).
- The GPRS module exists and keepalive messages arrive on time.

Reported faults

The **Reported Faults** test is an inspection that checks the panel log file for faults. The test fails if a fault is found.

To define the number of recent events that the test inspects for faults, see **Check for reported faults in last** in [Remote inspection values](#).

Total system usage

The **Total System Usage** test is an inspection that checks the panel for any arm or disarm logs.

- If there is at least one arm or disarm log, the test passes.
- Define how many reports from the panel that the test inspects in [Remote inspection values](#).

Bypassed/In-test zones

The **Bypassed/In-test Zones** test is an inspection that checks the panel for any log of a bypassed zone. If the test finds that a zone is bypassed, the test fails.

Frequently used zones

The **Frequently used zones** test is an inspection that checks if zones have been activated in the time defined in the **Check frequently used zones not used over** value in [Remote inspection values](#). If the time of inactivity is greater than the defined time, the test fails.

Note: The test bypasses zones that are defined as rarely triggered. To mark a zone as rarely triggered, see [Bypassing, soak testing, and marking a device as rarely triggered](#).

Broadband

The **Broadband** test is an inspection that checks for the presence of a broadband heartbeat.

- If the panel is not connected by broadband or there is no broadband module, the test title displays in the color gray.
- If there is a heartbeat, the test passes. If there is no heartbeat, the test fails.

Failed soak test zones

The **Failed Soak test Zones** test is an inspection that checks for soak test zones that cause an alarm. If there are no sensors in soak test mode or no alarms from sensors in soak test mode, the test passes.

Note: To put a device in a soak test state, see [Putting a device in a soak test state](#).

Remote inspection values

To change the remote inspection settings, on the **Remote Inspections** page, click **SETTINGS** and set your testing preferences. The definition list below defines each setting:

Check for reported faults in last

Set the number of recent events that the test inspects for faults in the panel log file.

- The test fails if a fault is found.
- Select either 10, 20, or 30 events to inspect.

Total system states in last

Set the number of reports that the test inspects for arm or disarm logs.

- The test fails if a system state change is not found in the panel log file.
- Select either 40, 60, or 120 reports to inspect.

Check frequently used zones not used over

Set the period of time the test inspects frequently used zones for an activation log. By default, all zones are defined as frequently used.

If a zone is rarely used, mark it as rarely triggered. To mark a device as rarely triggered on the **DEVICES** tab, see [Bypassing, soak testing, and marking a device as rarely triggered](#).

Note: A zone is a sensor.

Treat adjusted date/time as failure if adjustment is over

Set the maximum allowed time difference between the panel and server clocks. If the time difference is greater than the value, the test fails.




Figure 31: Remote Inspection Values dialog box

Related topics

[Navigating the Remote Inspection page](#)

Creating a remote inspection for a batch of panels

Note: To create a remote inspection for a single panel, see [Scheduling a remote inspection for an individual panel](#).

1. Open a new spreadsheet using your chosen application.
2. In the first row, type the panel name in column A, type the inspection date in column B, and type the number of months between each repetition in column C. For more information, see [Figure 31: Spreadsheet example](#).

Note:

- Enter the date in the following format: YYYY-MM-DD.
 - The recognized inspection repetition values for column C are: 0, 1, 3, 6, 9. To perform the test once only, enter a value of 0.
3. **Optional:** To add an additional panel, type the relevant information in the row below the first entry and follow the same column format. You can add multiple panels.
 4. To save the file in a comma delimited format, save the spreadsheet as a CSV file.

5. From the navigation pane in the PowerManage web application, click **Remote Inspection**.
6. Click **UPLOAD SCHEDULE**.
7. Click **CHOOSE FILE** and select the CSV file.

The remote inspection now appears on the **Reports** page.

	A	B	C
1	A00000	2019-01-25	3
2	A00001	2018-01-25	

Figure 32: Spreadsheet example

Related topics

[Navigating the Remote Inspection page](#)

[Scheduling a remote inspection for an individual panel](#)

Scheduling one or more remote inspections for a batch of panels

Note: To schedule a remote inspection for a single panel, see [Scheduling a remote inspection for an individual panel](#).

1. In the navigation pane, click **Remote Inspection**.
2. Select the check box of the remote inspection to schedule.
3. Click **SCHEDULE** to open a dialog box.
4. In the **Next Inspection** field, enter a date manually or select a date in the calendar.
5. From the **Choose repetition** list, select how often you want the remote inspection to occur. You can select **Once**, **1 month**, **3 months**, **6 months**, or **9 months**.
6. Click **SAVE**.

Related topics

[Navigating the Remote Inspection page](#)

[Scheduling a remote inspection for an individual panel](#)

Canceling a remote inspection

1. In the navigation pane, click **Remote Inspection**.
2. Select the check box of the remote inspection you want to cancel.
Note: You can only cancel a report that is scheduled to run.
3. Click **CANCEL**.
4. In the dialog box, click **CANCEL**.

Related topics

[Navigating the Remote Inspection page](#)

Running a remote inspection manually

1. In the navigation pane, click **Remote Inspection**.
2. Select the check box of one or more remote inspections to run manually.
3. Click **RUN**.
4. Click **BEGIN NOW**.

Related topics

[Navigating the Remote Inspection page](#)

Events page

Navigating the Events page

View a list of all panel events on the **Events** page.

Filter the **Users** page to return a match of specified criteria that you set in the search bar. Filter your search with one, or a combination of the following criteria: **SEVERITY**, **PANEL ID**, **PANEL NAME**, **ACCOUNT**, **HAS VIDEO**, **DATE** and **TYPE**. For more information about using the search filter, see [Using the search filter](#).









Figure 33: Navigating the Events page

Table 30. Events page interface elements

Callout	Description	Function
1	Events since last login	Displays the number of unresolved events since the user last logged on. To enable the notification, from the user icon list, select Settings and turn on Enable alarm supervision . For more information on the user icon, see User icon in Table 2 .
2	Check box	Select the check box of one or more events to enable MARK AS VIEWED .
3	MARK AS VIEWED	Click MARK AS VIEWED to mark multiple events as viewed. This button has the same function as the Viewed icon, but it can be performed on more than one event. Important: Only mark an event as viewed if your investigation is complete.
4	Panel name	Click the panel name to open it in the panel hub on the DEVICES tab. For more information, see Panel hub .
5	Event severity	<div>  </div> <p>The offline notification icon appears if the PowerManage server does not receive a keepalive message from the panel.</p> <p>Note: Define the delay between the panel's last keepalive message and the offline notification in the Groups page. For more information, see Group parameters.</p>

		 <p>The online notification icon appears if the PowerManage server receives regular keep alive messages from a panel that was offline.</p>
		 <p>The trouble icon appears next to the event in the SEVERITY column if there is a trouble event, such as a low battery, AC fail, gas or flood alert.</p>
		 <p>The alarm icon appears if there is an event caused by a breach of security or safety. Panic alarms, burglar alarms and fire alarms are examples of alarms.</p>
		 <p>The information event icon appears when a panel signals information such as a device bypass, an auto test, or any other information messages.</p>
6	View in examine mode	Click the event row to open an event in examine mode. For more information on examining events, see Examining events on the Events page .
7	Appointment	<p>You can find the source of the event in the APPOINTMENT column. The source can be one of the following examples:</p> <ul style="list-style-type: none"> • Panel: Low battery, tamper, or other causes. • Device: The panic button on a key fob, a sensor triggering a burglar alarm. • Server: Online and offline status reports.
8	Stream new events	<p>Turn on the Stream new events toggle to update the Events page every time a new event occurs.</p> <p>Note: By default, the Stream new events toggle is turned on.</p>
9	Raw event number icon	Hover over the icon to view the raw event number that was sent to the server.
10	Viewed or unviewed icon	<p>The eye symbol indicates unviewed reports. If you click the eye icon, a check mark replaces it to indicate the report is viewed.</p> <p>Note: Only mark an event as viewed if your investigation is complete.</p>

Related topics

[Examining event video on the Events page](#)

[Examining events on the Events page](#)

[Viewing events in the Events page](#)

[Viewing an event in the Events page](#)

Examining event video on the Events page

1. In the navigation pane, select **Events**.
2. Select the event with video to examine. To filter the **Events** page to only display events with video footage, from the **Search** list, select **has video**. From the **Has Video** list, select **Yes**.
3. Play the video in the examination pane to view the recorded footage.
4. To view live footage, click **LIVE VIDEO**.
5. **Optional:** To download the footage, click **DOWNLOAD**.

Related topics

[Navigating the Events page](#)

[Examining events on the Events page](#)

Examining events on the Events page

On the **Events** page, select the line of an event to view it in examine mode. The event is highlighted and appears in context with other events from the panel that you can examine.




Figure 34: Examining events on the Events page

Table 31. Events page examination interface elements

Callout	Description	Function
1	Exit	Click the arrow to return to the Events page.
2	Selected event	The selected event is highlighted.
3	LOAD NEWER	Click LOAD NEWER to load up to ten more recent events. The LOAD NEWER button only appears if more recent events exist.
4	LOAD OLDER	Click LOAD OLDER to load up to ten more older events.
5	Viewed event	A check mark indicates that a user marked the event as viewed.
6	Unviewed event	The unviewed icon indicates that a report is not viewed. If you select the icon, a check mark replaces it to indicate that the report is viewed. Only mark an event as viewed if your investigation is complete.
7	Examination pane	Click an event row to see more information in the examination pane about the source device that detects the event.
		If the event has video footage, you can play the recorded footage in the examination pane. For more information, see Using the video on demand tab .

Related topics

[Navigating the Events page](#)

[Examining event video on the Events page](#)

[*Viewing events in the Events page*](#)

[*Viewing an event in the Events page*](#)

[*Using the video on demand tab*](#)

Viewing an event or multiple events on the Events page

1. From the navigation pane, select **Events**.
2. Navigate to the events you want to mark as viewed and select the check box at the start of each line.
Note: You can select the eye symbol to quickly mark a single event as viewed. See Viewed or unviewed icon in [Table 30](#).
3. Click **MARK AS VIEWED**.

Reports page

Navigating the Reports page

View, create, stop and remove reports on the **Reports** page.

Filter your search of the **Reports** page by selecting one or more filter values from the **Search** list. From the **Search** list, select a filter value from one or more of the following keys: **IS ACTIVE**, **CREATED**, **LAST REPORT**, and **NEXT REPORT**. For more information, see [Using the search filter](#).




Figure 35: Navigating the Reports page

Table 32. Reports page interface elements

Callout	Description	Function
1	Check box	Select the check box of one or more reports to enable use of STOP and REMOVE .
2	STOP	Click to stop a report that is currently running. If you stop a report, it will not run on scheduled dates in the future. STOP appears when you select a check box.
3	REMOVE	Click to remove a report from the list of reports and cancel any recurrences that are scheduled in the future. REMOVE appears when you select a check box.
4	PDF	Click to download the report locally as a PDF file. The .pdf format is more readable than a .csv file and contains more panel information.
5	CSV	Click to download the report locally as a CSV file.
6	ADD REPORT	Click to create a new report for all panels that are enrolled on the server. For more information, see Creating a new report for all panels on the server . Note: To create a new report for one or more panels, see Creating a new report on the Panels page .
7	Viewed/unviewed icon	The eye icon indicates unviewed reports. If you click the icon, a check mark replaces it to identify the report as viewed. Only mark an event as viewed if you conclude the event investigation.

Related topics

[Creating a new report for all panels on the server](#)

[Creating new reports](#)

[Stopping or removing a report from the Reports page](#)

Creating new reports

To create a new report for all of the panels that are enrolled in the server, see the definitions below and follow the procedure in [Creating a new report on the Reports page](#).

To create a new report for one or more panels, see the definitions below and follow the procedure in [Creating a new report on the Panels page](#).




Figure 36: Create a Report for all Panels dialog box

Report Name

Name the report as descriptively as possible.

Note: The report name is mandatory.

Report options:

Report type

- **One time:** The report runs once only.
- **Daily:** Set your report to run daily, or in a regular sequence of days. For example, you can set the report to run every day, every two days, every three days, or at any regular interval up to every 30 days. You can also configure the report to run every weekday only.
- **Weekly:** Set the report to run on a weekly basis. For example, you can set the report to run every week, every two weeks, every three weeks, or at any week based interval up to every 52 weeks. You can set the day of the week you want the report to run.
- **Monthly:** Set your report to run on a monthly basis. For example, you can set the report to run every month, every two months, every three months, or at any month based interval up to every 12 months. You can then select one of two options to set the day of the month that the report runs:
 1. Set the report to run on every first, second, third, fourth, or fifth day of the month.
 2. Set the report to run on one specified day of the week, based on its ordinal occurrence in a month. For example, you can set the report to run on the first Monday of every month, the second Friday of every month, or the fourth Wednesday of every month. The highest ordinal occurrence you can set is the fourth occurrence of a day in the month.

Range of recurrence

Set the report to recur constantly, to end after a specified number of recurrences, or to end on a specified date.

Note: This option is not available if you set **Report Type** to **One time**.

Schedule start

Set when the recurring report starts. The default setting is **Start Right Now**.

If you clear the **Start Right Now** check box, a date and time field appear. Click the date field to select a start date in the calendar interface and click the time field to select a start time.

Note: If you click **X** in the time field, a default time of **12:00 AM** is set.

Content options

You can read reports on the **Reports** page. Alternatively, you can send a report to an email address or an FTP server site.

On the **Reports** page you can set the format of the report to a CSV file. The option to set the format of the report to a more readable PDF file is available only when you create a report on the **Panels** page. For more information, see [Creating a new report on the Panels page](#).

Related topics

[Navigating the Reports page](#)

[Creating a new report on the Panels page](#)

Creating a new report for all panels in the server

1. In the navigation pane, click **Reports**.
2. Click **ADD REPORT**.
3. Enter a report name in the **Report Name** field and configure the settings to define your report.

Note: See [Creating new reports](#) for more information on report settings.

4. Click **SAVE**.

The report now appears on the **Reports** page.

Related topics

[Navigating the Reports page](#)

Stopping or removing a report from the Reports page

Note: If you remove a report, it is deleted from the page and you cannot reuse it.

1. In the navigation pane, click **Reports**.
2. Select the check box of the report to stop or remove.

Note: You can select multiple reports to stop or remove at the same time, but you can only perform one function at a time.

3. Perform one of the following actions:
 - Click **STOP**
 - Click **REMOVE**

4. Click **OK**.

Related topics

[Navigating the Reports page](#)

Firmware page

Navigating the Firmware page

You can mass upgrade the firmware of a group of control panels, Ethernet Powerlinks, wired keypads, PGH outputs, and communication boards on the **Firmware** page. A device group only appears on the **Firmware** page if the server contains an upgrade package related to the device.

After you select a device for upgrade, filter your search by selecting one or more filter values from the **Search** list. From the **Search** list, select a filter value from one or more of the following keys: **NAME**, **PANEL ID**, **ACCOUNT**, **GROUP**, **MODEL**, **CONTROL PANEL**, **WIRED KEYPAD**, **ZONE EXPANDER**, **OUTPUT EXPANDER**, **POWER SUPPLY**, **POWER SUPPLY WITH OUTPUTS**, **PGH**, **COMMUNICATOR**, **AUDIO VERIFICATION**.

For more information, see [Using the search filter](#).

In order for firmware packages to appear on the page, technical support must complete the following tasks:

- Download the upgrade packages to the repository server
- Connect the upgrade packages to the PowerManage server




Figure 37: Navigating the Firmware page and the CHOOSE DEVICE FOR MASS UPGRADE list

Table 33. Firmware page interface elements

Callout	Description	Function
1	Upgrade status	Click Upgrade Status to view the upgrade status of firmware upgrades.
		You can stop a software upgrade on the Processes page if it has a START status. For more information, see Stopping a process . To stop a process for an individual panel, see Processes tab .
2	Quick search	Enter a search term to search the devices that are available for upgrade.
3	Firmware groups	The firmware packages that are available for mass upgrade.




Figure 38: Selecting a group to upgrade on the Firmware page

Table 34. Firmware page interface elements

Callout	Description	Function
1	Check box	Select the check box of one or more devices to enable UPGRADE .
2	Return	Click to return to Firmware page.
3	UPGRADE	Click UPGRADE to apply the upgrade package to the selected groups. To upgrade the firmware of an individual panel, see Firmware tab .
		The firmware upgrade times out after a week if the process does not finish. If the panel is offline, in an armed state, or experiencing troubles, the upgrade process pauses in a START state. Note: Power-link upgrades are an exception. Power-link upgrades time out after one hour.
4	Device list	Only devices that are relevant to the upgrade package that you select appear in the device list.
		As well as selecting the upgrade package by device model, PowerMaster panels and GSM modem upgrade packages also require the current version number. The 4G/LTE cellular modem requires two separate upgrades. The first upgrade is 'GSM Modem' and second is 'OTA Modem'.

Related topics

[Firmware tab](#)

[Mass upgrading the firmware of a device](#)

Mass upgrading the firmware of a device

1. In the navigation pane, click **Firmware**.
2. From the **CHOOSE DEVICE FOR MASS UPGRADE** list, click the device type that you want to upgrade. For more information, see Firmware groups in [Table 33](#).
3. From the **UPGRADE CONTROL PANEL TO VERSION** list, select the software version you want to upgrade the device to.
4. Select the check box of one or more panels to upgrade.
5. Click **UPGRADE**.
6. Click **OK**.

Related topics

[Firmware page](#)

[Upgrading the firmware related to an individual panel in the Panels hub](#)

System drop-down menu

To manage issues related to the server, select from the **System** drop-down menu.

Manage server issues related to the following categories:

- [Settings](#)
- [Groups](#)
- [Processes](#)
- [Users](#)
- [Roles](#)
- [Action log](#)
- [Central stations](#)
- [Basic configurations](#)
- [Installers](#)
- [Dashboard](#)

Settings page

Navigating the Settings page

Use the settings page to set up server configuration parameters.




Figure 39: Navigating the Settings page

Table 35. Navigating the Settings page

Callout	Description	Function
1	GENERAL	Use the GENERAL tab to: <ul style="list-style-type: none">• Enable or disable the auto-enrollment of panels to the server. To enable the auto-enrollment of panels by cellular connection, see Editing the cellular connection settings. To enable the auto-enrollment of panels by broadband connection, see Enabling or disabling the auto-enrollment of panels to the server by broadband

		<p>connection.</p> <ul style="list-style-type: none"> • Select a message broker for SMS wake up. For more information, see Adding a message broker to the system and Editing the user notifications settings. • Enable or disable wakeup SMS generation when the user starts a discovery process. For more information, see Editing the cellular connection settings. • Set a mask to enable only specific panels and prohibit authorized panels to connect to the server. For more information, see Masking the system ID. • Enable or disable the automatic deletion of the server IP address from a panel when you remove it from the server. For more information, see Enabling or disabling the automatic deletion of the server IP address from a panel when you remove it from the server.
2	RECEIVER	<p>Use the RECEIVER tab to:</p> <ul style="list-style-type: none"> • Enable or disable online and offline event the generation. For more information, see Enabling or disabling the generation of system online and offline events for one and two-channel panels. • Enable or disable email and SMS notifications for online and offline events. For more information, see Enabling or disabling email and SMS notifications for panel online and offline events.
3	RESOLVE	<p>Use the RESOLVE tab to:</p> <ul style="list-style-type: none"> • Enable or disable remote inspection success or failure event generation. For more information, see Enabling or disabling the generation of remote inspection success and failure events. • Enable or disable email notifications for successful remote inspections. For more information, see Enabling or disabling remote inspection success email notifications to the customer.
4	INTERACTIVE	<p>Use the INTERACTIVE tab to:</p> <ul style="list-style-type: none"> • Enable or disable the user app or the installer app as a default for new panels that are enrolled in the server. For more information, see Editing the interactive session settings. • For PSP panels that connect to the server with an IP channel, enable or disable a connection to the DLS service. The server prompts the panel to connect to the DSL application. This is also known as firewall friendly protocol transfer. For more information, see Editing the interactive session settings. • Enable or disable user permission to grant the installer access to the user's panel with the user application. For more information, see Editing the interactive session settings. • Limit the number of active user sessions per server and per panel. For more information, see Editing the user notifications settings. • Enable or disable email notifications for emails with video attachments and emails without video attachments. For more information, see Editing the inter-active session settings. • Enable user app notifications with a pop-up dialog box. For more information, see Editing the user notifications settings.
5	MESSAGE BROKERS	<p>Use the MESSAGE BROKERS tab to:</p> <ul style="list-style-type: none"> • Add a message broker to the system so the PowerManage server sends SMS messages to panels. For more information, see Adding a message broker to the system. • Remove a message broker. For more information, see Removing a message broker from the server. • Edit message broker information. For more information, see Editing message broker information.

General tab

Editing the cellular connection settings

1. In the navigation pane, click **System**, then click **Settings**.
2. On the **GENERAL** tab, in the **CELLULAR CONNECTED** section, click **EDIT**.
3. In the **EDIT CELLULAR CONNECTED SETTINGS** dialog box, perform one or more of the following actions:
 - To select a message broker for SMS wakeups, from the drop-down list, select a message broker from the **MESSAGE BROKERS** tab. For more information about adding a message broker to the system, see [Adding a message broker to the system](#).
 - To set the number of times the server sends a wakeup SMS if the first wake up fails, enter the number in the **Number of retries** field.
 - To set the time interval between each SMS wakeup retry, enter a time in seconds in the **Retries Interval [seconds]** field.
 - To enable the auto-enrollment of panels to the sever, select the **Enable Auto-Enroll** check box. To disable the auto-enrollment of panels to the sever, clear the **Enable Auto-Enroll** check box.
 - To enable wakeup SMS generation when the user starts a discovery process, select the **WakeUp panel on user initiated discovery** check box. To disable wakeup SMS generation when the user starts a discovery process, clear the **WakeUp panel on user initiated discovery** check box.
4. Click **SAVE**.

Enabling or disabling the auto-enrollment of panels to the server by broadband connection

1. In the navigation pane, click **System**, then click **Settings**.
2. On the **GENERAL** tab, in the **BROADBAND CONNECTED** section, click **EDIT**.
3. In the **EDIT BROADBAND CONNECTED SETTING** dialog box, perform one or more of the following actions:
 - To enable the auto-enrollment of panels to the sever, select the **Enable Auto-Enroll** check box.
 - To disable the auto-enrollment of panels to the sever, clear the **Enable Auto-Enroll** check box.
4. Click **SAVE**.

Masking the system ID

1. In the navigation pane, click **System**, then click **Settings**.
2. On the **GENERAL** tab, in the **COMMON CONNECTED** section, click **EDIT**.
3. In the **EDIT COMMON CONNECTED SETTINGS** dialog box, enter a system ID mask in the **System ID's Mask** field.
4. Click **SAVE**.

Enabling or disabling the automatic deletion of the server IP address from a panel when you remove it from the server

1. In the navigation pane, click **System**, then click **Settings**.
2. From the **GENERAL** tab, in the **COMMON CONNECTED** section, click **EDIT**.
3. In the **EDIT COMMON CONNECTED SETTINGS** dialog box, perform one of the following actions:
 - To enable the automatic deletion of the server IP address from a panel when you remove it from the server, select the **Remove Panel by Resetting the Receiver IP** check box.
 - To disable the automatic deletion of the server IP address from a panel when you remove it from the server, clear the **Remove Panel by Resetting the Receiver IP** check box.
4. Click **SAVE**.

Receiver tab

Enabling or disabling email and SMS notifications for online and offline panel events

1. In the navigation pane, click **System**, then click **Settings**.
2. On the **RECEIVER** tab, in the **SUPERVISION** section, click **EDIT**.
3. **Optional:** In the **EDIT SUPERVISION SETTINGS** dialog box, to enable or disable email notifications, perform one or more of the following actions:
 - To enable email notifications, select the **Send Notification Email on Online/Offline Event** check box.
 - To disable email notifications, clear the **Send Notification Email on Online/Offline Event** check box.
4. **Optional:** In the **EDIT SUPERVISION SETTINGS** dialog box, to enable SMS notifications, perform one or more of the following actions:
 - To enable email notifications, select the **Send Notification SMS on Online/Offline Event** check box.
 - To disable email notifications, clear the **Send Notification SMS on Online/Offline Event** check box.
5. Click **SAVE**.

Enabling or disabling the generation of system online and offline events for one and two-channel panels

1. In the navigation pane, click **System**, then click **Settings**.
2. On the **RECEIVER** tab, in the **SUPERVISION** section, click **EDIT**.
3. **Optional:** In the **EDIT SUPERVISION SETTINGS** dialog box, to enable or disable system online and offline event generation for one-channel panels, perform one or more of the following actions:
 - To enable the generation of system online and offline events, select the **Generate `SYSTEM OFFLINE/ONLINE` Events for One-Channel Panels** check box.
 - To disable the generation of system online and offline events, clear the **Generate `SYSTEM OFFLINE/ONLINE` Events for One-Channel Panels** check box.
4. **Optional:** In the **EDIT SUPERVISION SETTINGS** dialog box, to enable or disable the generation of system online and off- line events for two-channel panels, perform one or more of the following actions:
 - To enable the generation of system online and offline events, select the **Generate `SYSTEM OFFLINE/ONLINE` Events for Two-Channel Panels** check box.
 - To disable the generation of system online and offline events, clear the **Generate `SYSTEM OFFLINE/ONLINE` Events for Two-Channel Panels** check box.
5. Click **SAVE**.

Resolve tab

Enabling or disabling remote inspection success email notifications to the customer

1. In the navigation pane, click **System**, then click **Settings**.
2. On the **RESOLVE** tab, click **EDIT**.
3. Perform one of the following options:
 - To enable email notifications, select the **Send Email to the Customer of Succeed RI** check box.
 - To disable email notifications, clear the **Send Email to the Customer of Succeed RI** check box.
4. Click **SAVE**.

Enabling or disabling the generation of remote inspection success and failure events

1. In the navigation pane, click **System**, then click **Settings**.
2. On the **RESOLVE** tab, in the **REMOTE INSPECTION** section, click **EDIT**.
3. In the **EDIT REMOTE INSPECTION SETTINGS** dialog box, perform one or more of the following actions:
 - To enable remote inspection success and failure event generation, select the **Generate 'Succeed/Failed RI' Event** check box.
 - To disable the generation of remote inspection success and failure event generation, clear the **Generate 'Succeed/Failed RI' Event** check box.
4. Click **SAVE**.

Interactive tab

Editing the user notifications settings

1. In the navigation pane, click **System**, then click **Settings**.
2. On the **INTERACTIVE** tab, in the **USER NOTIFICATIONS** section, click **EDIT**.
3. In the **EDIT USER NOTIFICATIONS SETTINGS** dialog box, perform one or more of the following actions:
 - To select a message broker for user notifications, from the **Message Broker** drop-down list, select a message broker. For more information about adding a message broker to the system, see [Adding a message broker to the system](#).
 - To enable email notifications with video attachments, select the **Enable Emails with Attached Video** check box. To disable email notifications with video attachments, clear the **Enable Emails with Attached Video** check box.
 - To enable email notifications without video attachments, select the **Enable Emails without Attached Video** check box. To disable email notifications without video attachments, clear the **Enable Emails without Attached Video** check box.
4. Click **SAVE**.

Editing the interactive session settings

1. In the navigation pane, click **System**, then click **Settings**.
2. On the **INTERACTIVE** tab, in the **INTERACTIVE SESSION** section, click **EDIT**.
3. In the **EDIT INTERACTIVE SESSION SETTINGS** dialog box, perform one or more of the following actions:
 - Enter the type of application in the **Application Type** field.
 - To limit the number of connections to a server at a time, enter the maximum number in the **Limit of Concurrent Interactive Connections per Server** field.
 - To limit the number of connections to a panel at a time, enter the maximum number in the **Limit of Concurrent Interactive Connections per Panel** field.
 - To enable the user app as a default for new panels that are enrolled in the server, select the **Enable User App for New Incoming Panels** check box. To disable the user app as a default for new panels that are enrolled in the server, clear the **Enable User App for New Incoming Panels** check box.
 - To enable the installer app as a default for new panels that are enrolled in the server, select the **Enable Installer App for New Incoming Panels** check box. To disable the installer app as a default for new panels that are enrolled in the server, clear the **Enable Installer App for New Incoming Panels** check box.
 - To enable DLS service, select the **Enable DLS service** check box. To disable DLS service, clear the **Enable DLS service** check box.
 - To enable the ability for the user to grant the installer access to the user's panel with the user application, select the **Approve Installer Access by User** check box. To disable the ability for the user to grant the installer access to the user's panel with the user application, clear the **Approve Installer Access by User** check box.
4. Click **SAVE**.

Editing the advertisement settings

1. In the navigation pane, click **System**, then click **Settings**.
2. On the **INTERACTIVE** tab, in the **ADVERTISEMENT** section, click **EDIT**.
3. In the **EDIT ADVERTISEMENT SETTINGS** dialog box, in the URL field, enter the URL address.
4. Click **SAVE**.

Message brokers tab

Add a message broker to the system to enable the PowerManage server to send SMS messages to the following:

- Panels to wake up one or more panels
- The homeowner's phone to send event notifications to the user

To send an SMS, you can use the following options:

- A modem that is connected serially (deprecated) to the server
- A third-party message broker

The message broker tab displays the following:

- Third party message brokers: Most message broker companies provide a similar API. You can find five leading companies' APIs on the **MESSAGE BROKER** tab. You can use and modify any of these APIs to match the message broker company that you choose.
- Modems that connect to the server

To define a message broker for SMS wakeup, see [Editing the cellular connection settings](#).

To edit the user notification settings, see [Editing the user notifications settings](#).

To add a message broker to the system, see [Adding a message broker to the system](#).

To edit message broker information, see [Editing message broker information](#).




Figure 40: Navigating the Message Broker tab

Table 36. MESSAGE BROKER tab interface elements

Callout	Description	Function
1	NAME	Displays the name of the message broker company.
2	DESCRIPTION	Describes the message broker.
3	ADD MESSAGE BROKER	Click ADD MESSAGE BROKER to create a message broker. For more information, see Adding a message broker to the system .
4	X button	Click to remove a message broker from the server.

Adding a message broker to the system

1. In the navigation pane, click **System**, then click **Settings**.
2. On the **MESSAGE BROKERS** tab, click **ADD MESSAGE BROKER**.
3. Enter the required information in the **ADD MESSAGE BROKER SETTINGS** dialog box.
4. Click **SAVE**.

Add message broker settings

Figure 41: Add Message Broker Settings in dialog box

Table 37. ADD MESSAGE BROKER SETTINGS interface elements

Name	Description
Name	The name that identifies the message broker on the MESSAGE BROKER tab.
Type	If the modem is connected to the server, from the Type drop-down, select Serial Port . To use a third party message broker, connect via HTTPS Ethernet (TCP/IP). From the Type drop-down list, select HTTP Gateway .
Description	Describes the message broker on the MESSAGE BROKER tab.
Sender (\${ORIGINATOR})	Your message broker's phone number. To the user, this number displays as the SMS sender.
Login (\${USER})	The user logon that the message broker provides.
Password (\${PASSWORD})	The password that the message broker provides.
Host (\${HOST})	The message broker's URL.
Port (\${PORT})	The port to use to connect to the message broker.
Template of GET/POST request to send sms	The HTTP message that sends to the message broker. For more information about Template of GET/POST request to send sms , see Creating a GET or POST request template .
Use TLS	To enable TLS encryption, select the Use TLS check box.

Creating a GET or POST request template

The contents of the **Template of GET/POST request to send sms** field are sent as a HTTP/HTTPS message to the message broker site to send an SMS.

Important:

- The type, format, and parameters of a GET or POST message vary and depend on your message broker and your country. The guidelines below are general and you will need to contact your message broker to successfully complete the task. To see a GET/POST request example, see [GET or POST request example](#).
- The request fails if you do not press the ENTER key on the keyboard after `HTTP/1.1` in the request method statement and at the end of each request header. For more information about the request method statement, see Step 1. For more information on request headers, see Step 2.
- The request fails if the request contains any unnecessary blanks.

1. On the first line, enter the request method statement. The request method statement generally begins with the request method, for example, GET or POST, and ends with `HTTP/1.1`. Enter the URI and the required key-value pairs between the request method and `HTTP/1.1`.

Note: It is necessary to substitute the values with local environment variables as required. For more information, see [Substituting values in your GET or POST request template](#).

2. On a new line, enter a request header, for example, `Host:`. Enter any additional request headers and ensure each request header is on a new line. Other examples of request headers include: `User-Agent:` and `Connection:`.

Note: Use local environment variables as required. For more information, see [Substituting values in your GET or POST request template](#).

Substituting values in your GET or POST request template

To convert an API query string value, replace it with its relevant local environment variable.

Important: The type, format, and parameters of a GET or POST message vary and depend on your message broker. These guidelines are general and you will need to contact your message broker to successfully complete the task. To see a GET/POST request example, see [GET or POST request example](#).

Note: In GET or POST request example, the local environment variables are enclosed in curly braces and preceded by a dollar sign: `${ }`.

In the example in GET or POST request example, the following conversions take place:

- `username=demot` converts to `username=${USER}`
- `&password=demo` converts to `&password=${PASSWORD}`
- `&msg=1234` converts to `&msg=${TEXT}`

Use the environment variables in the **ADD MESSAGE BROKER SETTINGS** dialog box. For more information, see [Add message broker settings](#).

- **\${ORIGINATOR}**: Your message broker's phone number. To the user, this number displays as the SMS sender.
- **\${USER}**: The logon that the message broker provides.
- **\${PASSWORD}**: The password that the message broker provides.
- **\${HOST}**: The message broker's URL
- **\${PORT}**: The port you use to connect to the message broker

As well as the environment variables in the **ADD MESSAGE BROKER SETTINGS** dialog box, PowerManage automatically creates the following variables that you can also use:

- **\${CONTENT_LENGTH}**: Information about the size of POST request body
- **\${ID}**: An auto-increment variable
- **\${UUID}**: An auto-generated variable that is usually used as a message ID
- **\${DESTINATION}**: SMS recipient number
- **\${TEXT}**: Message text

GET or POST request example

Important: The type, format, and parameters of a GET or POST request vary and depend on your message broker. These guidelines are general and you will need to contact your message broker to successfully complete the task. To see a GET/POST request example, see [GET or POST request example](#).

Example information provided

In the following general example, the message broker site is `http://www.vianett.com` and the message broker API URL is `https://www.vianett.com/en/developers/api-documentation/http-get-post-api`.

The API description contains the following example variables:

```
https://smsc.vianett.no/v3/send?
```

```
username=demot
```

```
&password=demo
```

```
&msgid=1234
```

```
&tel=4711111111
```

```
&msg=Hello+World
```

```
&pricegroup=300
```

```
&campaignid=12345
```

GET/POST template request

```
GET /v3/send?username=${USER}&password=${PASSWORD}&msgid=${UUID}&tel=${DESTINATION}  
&msg=${TEXT}&campaignid=378404HTTP/1.1
```

```
Host:${HOST}
```

```
Port:${PORT}
```

```
User-Agent:firefox
```

```
Connection:close
```

Editing message broker information

1. In the navigation pane, click **System**, then click **Settings**.
2. On the **MESSAGE BROKERS** tab, click the message broker to edit.
3. Edit the required information in the **ADD MESSAGE BROKER SETTINGS** dialog box.
4. Click **SAVE**.

Removing a message broker from the server

1. In the navigation pane, click **System**, then click **Settings**.
2. On the **MESSAGE BROKERS** tab, navigate to the message broker to remove and select **X**.
3. Click **OK**.

Groups page

Navigating the Groups page

Manage panel groups on the **Groups** page. A group is a collection of panels that share the same configuration settings.

Note: Any panel that connects by auto enroll automatically joins **Main Group**.




Figure 42: Navigating the Groups page

Table 38. Groups page interface elements

Callout	Name	Description
1	Check box	Select the check box of one or more groups to enable REMOVE .
2	REMOVE	Click to remove one or more selected panels from the server. Select a check box to enable REMOVE . Note: You cannot remove Main Group .
3	Group hub	Click the row of the group to open it in the group hub. In the group hub, you can view general group and central station information in the GENERAL and CS COMMUNICATING tabs. For more information on the group hub, see Group hub .
4	ADD GROUP	Click to add a new panel to the server. For more information about adding a group to the server, see Adding groups to the Groups page and Adding a group to the Groups page .
5	Connected users	Click the connected users icon to display a list of all of the server users that have privileges to view the panels of the group.

Related topics

[Adding a new group](#)

[Group parameters](#)

[Configuring the central station communication settings for a group](#)

[Group hub](#)

[CS communicating tab in the group hub](#)

[Group central station communication settings](#)

Group parameters

If you add a new group to the server or edit an existing group, configure the parameters in the **ADD GROUP** or **EDIT GROUP** dialog boxes.

To make a new group in the server, see [Adding a group to the groups page](#).

To edit a group configuration, see **EDIT** in [Table 41](#).

ADD GROUP [X]

Name

Description

PowerMaster/PowerMax

Power Master upgrade method
GPRS

Cellular

☒ Supervision enabled

Supervision Period: 120 Offline Timer: 240

Broadband

☒ Encryption enabled

Supervision Period: 5 Offline Timer: 60

PowerSeries NEO/Pro, Quazar <5.3

☒ Cellular Supervision enabled

Supervision Period: 135 Cellular Offline Timer: 405

☒ Broadband Supervision enabled

Broadband Offline Timer: 405

PowerSeries NEO, Quazar 5.3 and higher

Cellular

☒ Supervision enabled

Supervision Period: 135 Offline Timer: 405

Broadband

☒ Supervision enabled

Supervision Period: 135 Offline Timer: 405

General

Interactive

☒ Local wake up

Server Messaging Language

Video On Demand History Size

Other

☐ Panel's time synchronization

☐ Allow upgrade over GPRS for DSC panel

☐ Temperature/light statistic

DISMISS **SAVE**

Figure 43: Group parameters in dialog box

Table 39. Group parameters interface elements

Callout	Description	Function
1	Name	Each group name must be unique and can only contain the characters: A-Z, a-z, and 0-9. Spaces are also accepted.
2	Description	Enter an optional description of the group in the Description field.

3	PowerMaster upgrade method	From the PowerMaster upgrade method list, select either GPRS or Broadband as a connection type for upgrades.
4	PowerMaster panel cellular supervision settings	<ul style="list-style-type: none"> • Supervision enabled: To disable the GPRS supervision and reduce GPRS communication, turn off Supervision enabled. Turn on Supervision enabled to enable the supervision. • Supervision Period: To determine how often the panel sends a supervision message, enter a value in the Supervision Period field. • Offline Timer: If no supervision message reaches the server, the panel's online status is set to GPRS Offline on the Panels page and a message is sent to the central station or automation. To delay the offline message by a specified time, enter a value that is greater than the Supervision Period value in the Offline Timer field.
5	PowerMaster panel broadband supervision settings	<p>Encryption enabled: Turn on Encryption enabled to encrypt messages that are sent from the panel with SSL encryption. To disable encryption, turn off Encryption enabled.</p> <p>Old power-link boards cannot encrypt messages. With newer power-link boards, you cannot disable encryption if the security level is set to medium or high in the administration console.</p> <ul style="list-style-type: none"> • Supervision Period: To define how often the panel sends supervision messages, enter a value in the Supervision Period field. The smallest value you can enter in the field is 5 seconds. • Offline Timer: If no supervision message reaches the server by Ethernet, the panel's online status is set to BBA Offline on the Panels page and a message is sent to the central station or automation. To delay this message by a specified time, enter a value that is greater than the Supervision Period value in the Offline Timer field. <p>Note: You cannot disable broadband supervision messages for PowerMaster panels.</p>
6	Neo/Pro and Quazar panel cellular supervision settings	<p>Edit the cellular connection settings for NEO/Pro and Quazar panels earlier than version 5.3 and NEO and Quazar panels later than version 5.3.</p> <ul style="list-style-type: none"> • Cellular Supervision enabled: To disable the GPRS supervision and reduce GPRS communication, turn off Cellular Supervision enabled. To enable the supervision, turn on Cellular Supervision enabled. <p>Note: If you turn on Cellular Supervision enabled, ensure that the correct receiver channel directs to a PowerManage server that can support a GPRS heartbeat.</p> <ul style="list-style-type: none"> • Supervision Period: To determine how often the panel sends a supervision message, enter a value in the Supervision Period field. • Cellular Offline Timer: If no supervision message reaches the server, the panel's online status is set to GPRS Offline on the Panels page and a message sends to the central station or automation. To delay this message by a specified time, enter a value that is greater than the Supervision Period value in the Cellular Offline Timer field.
7	Neo/Pro and	Edit the broadband connection settings for NEO/Pro and Quazar.

	Quazar panel broadband supervision settings	<p>panels earlier than version 5.3 and NEO and Quazar panels later than version 5.3.</p> <ul style="list-style-type: none"> • Supervision enabled: Turn on Supervision enabled to disable the Ethernet heartbeat. <p>Note: If you enable the broadband supervision, ensure that the correct receiver channel directs to a PowerManage server that can support an Ethernet heartbeat.</p> • Supervision Period: To determine how often the panel sends a supervision message, enter a value in the Supervision Period field. • Broadband Offline Timer: For panel with version 5.3 or earlier, if no supervision message reaches the server by Ethernet, the panel's online status is set to BBA Offline in the Panels page and a message is sent to the central station or automation. To delay this message by a specified time, enter a value that is greater than the Supervision Period value in the Broadband Offline Timer field. • Offline Timer: For panel with version 5.3 or later, if no supervision message reaches the server by Ethernet, the panel's online status is set to BBA Offline in the Panels page and a message is sent to the central station or automation. To delay this message by a specified time, enter a value that is greater than the Supervision Period value in the Broadband Offline Timer field.
8	Panel time synchronization	To periodically synchronize the panel clock with the server clock, select the Panel's Time Synchronization check box.
9	Allow upgrade over GPRS for DSC panel	Select the Allow upgrade over GPRS for DSC panel check box to enable firmware upgrades by cellular GPRS communication for NEO and PSP panels.
10	Temperature/light statistic	Enable to record temperature and light measurements with smart devices. To view temperature and light graphs, in the panel hub, go to the DEVICES tab and click the smart device to open it in the examination pane. Note: If you enable Temperature/light statistic, the bandwidth between the panel and the server increases.
11	SAVE	Click to save the group configuration.
12	Video on demand history size	Click to display maximum number of VOD films saved.
13	Server messaging Language	From the Server Messaging Language list, select a server messaging language.
14	Local wake up	Unlike Ethernet, GPRS does not provide an open session between the server and the panel. To send a wake-up SMS to the panel every time an open connection is required between the server and the panel, select the Local wake-up check box.

Related topics

[Adding a new group](#)

[Group hub](#)

[Configuring the central station communication settings for a group CS communicating tab in the group hub](#)

[Group central station communication settings](#)

Adding a new group

1. In the navigation pane, click System, then click Groups.
2. Click ADD GROUP.
3. Enter the information required in the ADD GROUP dialog box. For more information about the ADD GROUP dialog box settings, see [Adding groups to the Groups page](#).
4. Click SAVE.

The new group now appears on the **Groups** page.

To complete the setup, configure the central station communication settings. For more information, see [Configuring the central station communication settings for a group](#).

Related topics

[Adding groups to the Groups page](#)

[Configuring the central station communication settings for a group](#)

[Groups page](#)

Group hub

View and edit general group settings and central station communication settings in the group hub. To open a group in the group hub, on the group page, click the group row.




Figure 44: Navigating the Group hub

Table 40. Group hub interface elements

Callout	Description	Function
1	Group name	The name of the group you open in the group hub.
2	Group GENERAL tab	Displays general group information and parameters. For a description of the group information and parameter fields, see Groups page parameters . To edit the group information and parameters, see Edit group.
3	Group CS COMMUNICATING tab	Click to manage the communication between the panel and the central station or automation. For more information, see CS communicating tab in the Groups hub .
4	EDIT GROUP	Click to edit the group page parameters. For more information, see Group page parameters .

CS communicating tab in the group hub

Define which event types are communicated to one or more central stations or automations on the **CS COMMUNICATING** tab.




Figure 45: CS communicating in the group hub

Table 41. CS communicating tab interface elements

Callout	Description	Function
1	Central station	A central station or automation that is connected to the group. The central stations that appear here are added and defined on the Central stations page. For more information, see Central stations page .
2	EDIT	To determine the event types that the panel group communicates to the central station, click EDIT to open the Event types dialog box.
3	Event types dialog box	Determine the event types that the group of panels communicates to the central station. <ul style="list-style-type: none">• The name of the central station is the title of the dialog box.• To open the Event types dialog box, click EDIT.
4	All check box	Select or clear all of the event type check boxes with the All check box.
5	Event type check boxes	Select a check box to enable the communication of that event type to the central station. By default, all of the check boxes are cleared. For more information about each event type check box, see Group central station communication settings .

Related topics

[Groups page](#)

[Configuring the central station communication settings for a group](#)


[Group hub](#)

[CS communicating tab in the group hub](#)

[Group central station communication settings](#)

Group central station communication settings

Select a check box to enable or disable the communication of various event types to one or more central stations.



FIRST CS (VIS NAP V2/VISIONIC)

☐ All

☐ Alert ☐ Online

☐ Alarm ☐ Offline

☐ Restore ☐ Notice

☐ Security open/close ☐ RRI

☐ Camera being viewed ☐ Open/Close

☐ Camera trouble ☐ Temperature

☐ HD on/off ☐ Illuminance

☐ HD trouble

DISMISS SAVE

Figure 46: CS communicating tab in the group hub

The following list defines the information each event type communicates to the central station when you select the relevant check box on the **CS COMMUNICATING** tab:

Alarm

If there is a security or safety breach, an alarm notification is sent to the central station. Examples of security and safety breaches are burglary, fire, emergency, and panic alarms.

Alert

If there is an event that requires attention, an alert notification is sent to the central station. Examples of alert events are low battery, AC failure, gas, and flood events.

Restore

If a detector reading returns to its original state, a restore alert is sent to the central station.

Security open/close

If the state of the panel changes, the central station is updated. Examples of panel states are away, home, and disarm.

Note: You can configure the panel to send detector open and close notifications even when the panel is in a disarm state.

Camera being viewed

If a PIR CAM requests video on demand, a notification is sent to the central station.

Camera trouble

Currently not supported.

Home devices (HD) on/off

If a PGM turns on or off, a notification is sent to the central station.

Home devices (HD) trouble

Currently not supported.

Online

When the panel goes online, a notification is sent to the central station.

Offline

When the panel goes offline, a notification is sent to the central station.

Notice

If there is an info message, such as a device bypass or panel auto test, a notification is sent to the central station.

Routine remote inspection (RRI)

After a routine remote inspection, a success or failure notification is sent to the central station.

[Open/close](#)

If the state of a detector changes, a notification is sent to the central station.

[Illumination](#)

If there is an alert related to light, a notification is sent to the central station.

[Temperature](#)

If there is a temperature alert, a notification is sent to the central station.

Related topics

[Groups page](#)

[Configuring the central station communication settings for a group](#)

[Group hub](#)

[CS communicating tab in the group hub](#)

Configuring the central station communication settings for a group

1. In the navigation pane, click **System**, then click **Groups**.
2. On the **Groups** page, click the group to configure.
3. Click the **CS COMMUNICATING** tab.
4. Navigate to the central station to configure and click **EDIT**.
5. Select the check boxes of the alert types to communicate to the central station. For more information, see [Configuring central station communication settings for groups](#).
6. Click **SAVE**.

Related topics

[Configuring the central station communication settings for a group](#)

[Groups page](#)

[Adding groups to the Groups page](#)

Processes page

Navigating the Processes page

View a list of all processes on the **Processes** page. To view the processes for an individual panel, see [Processes tab](#). Each row represents a single process and each row displays the following:

- Process start time
- Panel ID
- Process description
- Current status
- Process creator name
- Duration

This information is contained in the column titles: **STARTED**, **PANEL**, **PROCESS**, **STATUS**, **USER**, and **DURATION**.

Filter your search of the **Processes** page by selecting one or more filter values from the **Search** list. From the **Search** list, select a filter value from one or more of the following keys: **PANEL ID**, **PANEL NAME**, **TYPE**, **USER**, **STATUS**, **STARTED AT**. For more information, see [Using the search filter](#).




Figure 47: Navigating the Processes page

Table 42. Processes page interface elements

Callout	Description	Function
1	Check box	Select the check box of one or more processes to enable use of STOP .
2	STOP	Click to stop one or more selected processes that are running.
3	PROCESS	A description of the process.
4	STATUS	A description of the of the process status. A progress bar indicates the process is running and the warning icon indicates the process stopped. The text after the warning icon indicates the reason the process stopped.
5	USER	Displays the name of the user that initiates the process. Note: If a process requires a subsequent task to complete the current process, the user name for subsequent process task is SYSTEM .
6	DURATION	Displays the total or current run time of the process. For more information, see Process duration column .

7	Cancel process	Click to stop a process that runs. Note: This has the same function as STOP except that you can only stop one process at a time.
---	----------------	---

Related topics

[Process duration column](#)

[Stopping a process](#)

[Processes tab](#)

Processes page duration column

when a process runs, the **DURATION** column displays the run time of the process. If a process is complete, the **DURATION** column displays the total run time of the process.

If the process does not finish, it times out after one hour. In this case, the process terminates and a time-out error displays in the **STATUS** column. The following examples are exceptions to this rule:

- A software upgrade cannot start if the panel is in an armed state.
- A software upgrade process times out after one week.
- A walk test for Neo panels times out after 15 minutes.
- A walk test for a PowerMaster panel times out after 500 seconds, or 8 minutes and 20 seconds.
- A remote inspection for Neo panels times out after 10 minutes.
- A video on demand process for a PIR CAM times out 10 minutes after it receives the final image.
- The estimated time-out period for a remote inspection is the number of devices, multiplied by 50 seconds.

Related topics

[Navigating the Processes page](#)

Stopping a process

Note: To stop a single process while it is in operation, Click **X**. **X** does not appear if you cannot stop the process.

To stop multiple processes at one time, complete the following steps:

1. In the navigation pane, click **System**, then click **Processes**.
2. Select the check box of one or more processes to cancel.
3. Click **OK**.

Related topics

[Navigating the Processes page](#)

[Process duration column](#)

Users page

Navigating the Users page

Add, suspend, remove, enable and edit server users on the **Users** page.

Important: You can manage all server users on the **Users** page, except the Default Super Admin. For more information on the Default Super Admin, see [Default super admin](#).

Each row in the list represents an individual user and displays the following information:

- User name and email address.
- User phone number.
- Latest log in time. If there is no date and time information in the **LAST LOGIN** column, the user has never logged in to the server.
- Role of the user. For more information about roles, see [Roles page](#).
- Title of the administrator who created the user account.

This information is contained in the column titles: **NAME**, **PHONE**, **LAST LOGIN**, **ROLE**, and **CREATED BY**.

Filter your search of the **Users** page by selecting one or more filter values from the **Search** list. From the **Search** list, select a filter value from one or more of the following keys: **NAME**, **PHONE**, **ROLE NAME**, **ROLE CREATOR NAME**, and **LAST LOGIN**. For more information, see [Using the search filter](#).







Figure 48: Navigating the Users page

Table 43. Users page interface elements

Callout	Name	Description
1	Check box	Select the check box of one or more events to enable REMOVE , SUSPEND , and ENABLE .
2	User status	 The user is enabled.  The user is suspended.  The user is logged in to the server.
3	REMOVE	Click to remove a user from the server.
4	SUSPEND	Click to suspend a user. A suspended user cannot log on to the server.
5	ENABLE	Click to enable a user. Enabled users can log on to the server.
6	ADD USER	Click to add a new user to the server.
7	Edit user	Click to edit user information.

Related topics

[Adding a new user](#)

[Adding or editing users](#)

[Default super admin](#)

[Editing user information](#)

[Removing, suspending and enabling users](#)

Default super admin

There is always at least one Default Super Admin for a PowerManage server. The Default Super Admin is a permanent role with full privileges.

The default username and default password are as follows:

- Username: admin@tycomonitor.com
- Password: Admin123

Important: Change the Default Super Admin password as soon as possible. For more information on changing a password, see [Changing your login password](#).

Related topics

[*Adding or editing users*](#)

[*Navigating the Users page*](#)

[*Adding a new user*](#)

[*Editing user information*](#)

[*Removing, suspending and enabling users*](#)

Removing, suspending and enabling users

1. In the navigation pane, click **System**, then click **Users**.
2. Select the check box of the user to remove, suspend, or enable.

Note: You can select multiple users to remove, suspend or enable at the same time, but you can only use one of the functions at a time.

3. Perform one of the following actions:

- Click **REMOVE**.
- Click **SUSPEND**
- Click **ENABLE**.

4. Click **OK**.

Related topics

[Navigating the Users page](#)

Adding or editing users

Add a new user or edit the information of an existing user on the **Users** page.

When you add a new user or edit the information of an existing user, you can set the following information:

- Full name
- Email address
- Phone number Country
- Belongs to role
- Password

The user logs on to the system with the email address and password you define.

The **Belongs to role** list displays all roles available on the **Roles** page. For more information, see [Roles page](#).

Related topics

[Navigating the Users page](#)

[Adding a new user](#)

[Editing user information](#)

[Default super admin](#)

Adding a new user

1. In the navigation pane, click **System**, then click **Users**.
2. Click **ADD USER**.
3. Type the information required in the **Full name**, **Email Address**, **Phone**, **Country**, **Belongs to role**, and **Password** fields.
4. Click **SAVE**.

The new user now appears in the users list.

Related topics

[Adding or editing users](#)

[Navigating the Users page](#)

Editing user information

1. In the navigation pane, click **System**, click **Users**.
2. Navigate to the user that to edit and click the edit user button.
3. Edit the information you want to change in the **Full name**, **Email Address**, **Phone**, **Country**, **Belongs to Role**, and **Password** fields.
4. Click **SAVE**.

Related topics

[Adding a new user](#)

[Adding or editing users](#)

[Default super admin](#)

[Navigating the Users page](#)

Roles page

Navigating the Roles page

Assign roles to server users on the **Roles** page.

Each server user has one role type. The role type defines the following:

- The pages the user can access
- The functions the user can perform
- The groups the user can manage

Note: For more information about groups, see [Groups page](#). For more information about users, see [Users page](#).

Each row on the **Roles** page represents a role and displays the following information:

- The role name. Administrator, Operator, and Event interface user are examples of role names. For more information, see [Role types](#).
- The role name of the user that created the role
- The username of the role creator
- The groups available to the role

This information is contained in the column titles: **NAME**, **PARENT ROLE**, **CREATED BY**, and **GROUPS**.

Filter your search of the **Roles** page by selecting one or more filter values from the **Search** list. From the **Search** list, select a filter value from one or more of the following keys: **NAME**, **PARENT ROLE**, and **CREATOR**. For more information, see [Using the search filter](#).




Figure 49: Navigating the roles page

Table 44. Roles page interface elements

Callout	Description	Function
1	Check box	Select the check box of one or more roles to enable REMOVE .
2	REMOVE	Click to remove a user from the server. Do not remove all of the roles. If you remove all of the roles, you cannot create additional roles for new users. If a role is assigned to a user, you cannot delete the role on the Roles page. See Users page for more information.
3	ADD ROLE	Click to create a new role.

4	Edit role	Click to edit a role. Note: You cannot edit the Administrator role; all the permissions are enabled by default.
---	-----------	---

Related topics

[Role types](#)

[Editing a role](#)

[Adding a new role](#)

Role types

There are three predefined role types in the server: Administrator, Operator, and Event interface user.

You can change or remove these roles but do not remove all of the roles. If you remove all of the roles, you cannot create additional roles for new users.

Administrator

The administrator role can access all of the menus and pages. Managers use the administrator role.

Operator

The operator role can access all of the menus except the **System** list. Users that control panels but do not have any server configuration permissions use the operator role.

Event interface user

By default, the event interface user role does not have any permissions. The role is used by the automation software to retrieve alarm video scripts from the PowerManage server.

Related topics

[Navigating the Roles page](#)

[Adding a new role](#)

[Editing a role](#)

Adding a new role

1. In the navigation pane, from the **System** list, select **Roles**.
2. On the **Roles** page, click **ADD ROLE**.
3. Enter a role name in the **Name** field.
4. From the **Parent Role** list, select a parent role.
5. From the **Unit Groups** list, select one or more groups that the role manages.

Note: A group defines the panel types that the role manages. For more information about groups, see [Groups page](#).

6. Click **SAVE**.

Related topics

[Navigating the Roles page](#)

[Editing a role](#)

[Role types](#)

Editing a role

1. In the navigation pane, from the **System** list, select **Roles**.
2. Navigate to the role to edit and click the edit role button. For more information, see Edit role in [Table 44](#)
3. Edit the role with one or more of the following actions:
 - Edit the information required in the **Name**, and **Unit groups** fields.
 - To delete a unit group, click **X**.
4. To add a unit group, click the **Unit groups** field and select one or more unit groups from the **Unit Groups** list. Click **SAVE**.

Related topics

[Navigating the Roles page](#)

[Role types](#)

[Adding a new role](#)

Central stations page

Navigating the Central stations page

Use the **Central stations** page to manage the central station applications that connect to the PowerManage server. On the **Groups** page, connect groups to one or more of the central stations defined on this page. For more information about groups, see [Groups page](#).

Each row on the **Central stations** page represents a role and displays the following information:

- The Central station name
- The protocol used
- The communication parameters of the central station

This information is contained in the column titles: **NAME**, **PROTOCOL**, and **COMMUNICATION**.

Filter your search of the **Central stations** page by selecting one or more filter values from the **Search** list. From the **Search** list, select a filter value from one or more of the following keys: **NAME**, **PROTOCOL**, **HOST**, **PORT**, and **DEVICE**. For more information, see [Using the search filter](#).

Note:

- The **Central stations** page is an automation application.
- Self-monitoring users do not need to use this page.




Figure 50: Navigating the Central Stations page

Table 45: Central stations page interface elements

Callout		Description	Function
1		Check box	Select the check box of one or more central station applications to enable REMOVE .
2		STATUS	Displays the connection status of the central station.
3		ADD CENTRAL STATION	Click to add a new central station. For more information about adding a central station, see Adding a central station and Adding or editing central stations .
4		Edit central station	Click to edit a central station configuration. For more information about editing a central station, see Editing a central station configuration and Adding or editing central stations .

Related topics[Adding a central station](#)[Adding or editing central stations](#)[Editing a central station configuration](#)[Removing a central station](#)

Adding or editing central stations

Configure the central station settings when you add a new central station or edit an existing central station configuration.

For more information about adding a new central station, see [Adding a central station](#).

For more information about editing a central station configuration, see [Editing a central station configuration](#).

CREATE CENTRAL STATION

Name

Protocol

☒ Heart beat

Heart beat
25

Retry time
10

Retry count
4

Connection Type
TCP/IP

Host

Port

Security
None

DISMISS SAVE

Figure 51: Central station settings dialog box

The following list defines the central station settings:

- **Name:** Enter a name that is local and identifiable to the server.
 - **Note:** When adding a central station, the **Name** field is mandatory. When editing a central station, the **Name** field is read-only.
- **Protocol:** Select a protocol that is suitable for the central station or automation. For example, MasterMind or Patriot servers use NMLR2 protocols, and BOLD's Manitou server uses FEP protocol.
- **Heart beat:** Define how often the server checks the status of the connection. The heart beat is measured in seconds.
- **Retry time:** Define how often the server automatically tries to send a message to the central station in case of a failure.
- **Retry count:** Define how many times the server automatically tries to send a message to the central station in case of a failure.
- **Connection type:** From the Connection Type list, select one of the following options:
 - Transmission Control Protocol/Internet Protocol (TCP/IP). If you select TCP/IP, continue to enter the required information in the Host and Port fields.
 - Serial connection type. If you select Serial, enter a serial port in the Serial Port field.
- **Security:** If you select a **TCP/IP** connection, from the **Security** list, select one of the following options: **TLS 1**, or **None**.

Adding a central station

1. In the navigation pane, click **System**, then click **Central Stations**.
2. Click **ADD CENTRAL STATION**.
3. Enter the information required in the **Name**, **Protocol**, **Heart beat**, **Retry time**, **Retry count**, and **Connection Type** fields. For more information, see [Adding or editing central stations](#).
4. Click **SAVE**.

Related topics

[Navigating the Central stations page](#)

[Adding or editing central stations](#)

[Editing a central station configuration](#)

[Removing a central station](#)

Editing a central station configuration

1. In the navigation pane, click **System**, then click **Central Stations**.
2. Click the edit button of the central station to edit.
3. Enter the information that is required in the **Name**, **Protocol**, **Heart beat**, **Retry time**, **Retry count**, and **Connection Type** fields. See [Adding or editing central stations](#) for more information.
4. Click **SAVE**.

Related topics

[Navigating the Central stations page](#)

[Adding or editing central stations](#)

[Adding a central station](#)

[Removing a central station](#)

Removing a central station

1. In the navigation pane, click **System**, then click **Central Stations**.
2. Select the check box of one or more central stations to remove.
3. Click **REMOVE**.
4. To confirm the function, click **OK**.

Related topics

[Navigating the Central stations page](#)

[Adding or editing central stations](#)

[Adding a central station](#)

[Editing a central station configuration](#)

Basic configurations page

Navigating the Basic configurations page

Manage created panel configurations on the **Basic Configurations** page. A basic configuration is a copy of one or more configuration parameters from an existing panel that you can use for multiple panels. To create a basic configuration from an existing panel configuration, see [Creating a basic configuration from an existing panel configuration](#).

To push a basic configuration to one or more panels, see [Pushing a basic configuration to one or more panels](#).

Each row on the page represents a basic configuration. A row displays the configuration name, panel model, creation date, and update time. This information is contained in the column titles: **NAME**, **PANEL MODEL**, **CREATED**, and **UPDATED**.

Filter your search of the **Basic Configurations** page by selecting one or more filter values from the **Search** list. From the **Search** list, select a filter value from one or more of the following keys: **NAME**, **VENDOR**, and **CREATED**. For more information, see [Using the search filter](#).




Figure 52: Navigating the basic configurations page

Table 46. Basic configurations page interface elements

Callout	Name	Description
1	Check box	Select the check box of one or more basic configurations to enable REMOVE .
2	REMOVE	Click to remove one or more basic configurations.
3	Basic configuration	A basic configuration. Click the basic configuration row to view a list of panels that are eligible for the configuration. To push the basic configuration to one or more panels, see Pushing a basic configuration on the Basic Configuration page .
4	Edit configuration	Click to edit the basic configuration. For more information about basic configuration parameters, see Basic configuration parameters .

Related topics

[Basic configurations page](#)

[Basic configuration parameters](#)

[Editing a basic configuration](#)

[Pushing a basic configuration on the Basic configuration page](#)

[Removing a basic configuration](#)

Basic configuration parameters

To configure the parameters of a basic configuration, on the **Basic Configuration** page, click the edit configuration button. For more information, see Edit configuration in [Table 46](#).




Figure 53: Navigating the basic configurations parameters

Table 47. Basic configuration editing interface elements

Callout	Description	Function
1	Selected parameters	When you push a basic configuration to one or more panels on the Panels page, only the selected fields are pushed to the panel configuration. You can select or clear other parameter check boxes to include or exclude the parameters from the basic configuration.
2	Undo	Click the undo arrow to undo a selection or change.
3	Enable/disable	Click to enable or disable functions.
4	Table of contents	Expand the table of contents to navigate the configuration parameters quickly.
5	Show only changed	Select the Show only changed check box to only view the parameters you edit.
6	Quick search	Enter a search term in the Quick search field to search the configuration parameters. You can search parameter names and the possible values of the parameters.
7	SAVE	Click to update the basic configuration. If you make any change, SAVE is enabled.

Related topics

[Basic configurations page](#)

[Editing a basic configuration](#)

[Pushing a basic configuration on the Basic configuration page](#)

[Removing a basic configuration](#)

Editing a basic configuration

1. In the navigation pane, from the **System** list, select **Basic Configurations**.
2. Click the edit button of the basic configuration that to edit.
3. Make the required changes. For more information about basic configuration parameters, see [Basic configuration parameters](#).
4. Select the **Show only changed** check box to review the changes made.
Note: Use the **Quick search** bar and expand the **TABLE OF CONTENTS** to navigate the basic configurations.
5. Click **SAVE**.

Related topics

[Basic configurations page](#)

[Basic configuration parameters](#)

[Pushing a basic configuration on the Basic configuration page](#)

[Removing a basic configuration](#)

Removing a basic configuration

1. In the navigation pane, from the **System** list, select **Basic Configurations**.
2. Select the check box of the basic configuration to remove.
3. Click **REMOVE**.

Related topics

[Basic configurations page](#)

[Basic configuration parameters](#)

[Editing a basic configuration](#)

[Pushing a basic configuration on the Basic configuration page](#)

Installers page

Navigating the Installers page

Accept or reject installers that are registered in the server on the **Installers** page. Use the search bar to filter the **Installers** page by status.

To connect remotely to a panel by using the installer mobile application, AlarmInstall, installers need to register on the server and receive an accepted status:

- **Registration:** Installers register the first time they use the mobile application.
- **Accepted status:** Either the user or the administrator then accepts or rejects access to the panel.
 - a. Turn on **Approve Installer Access by User** to grant the installer an **Accepted** status automatically. The user then approves the connection via the user mobile application, ConnectAlarm. This option is common for panels that are not monitored.
 - b. Turn off **Approve Installer Access by User** to grant the installer a **Pending** status automatically. A server operator then accepts the installer and the installer can access the panel remotely by using the installer mobile application. This option is common for panels that are monitored

For more information about the differences between monitored and self-monitored servers, see [Installer status](#).




Figure 54: Navigating the Installers page

Table 48. Installers page interface elements

Callout	Description	Function
1	Check box	Select the check box of one or more basic configurations to enable use of ACCEPT and REJECT .
2	LAST LOGIN	Displays the last time the installer logged to their account.
3	PANELS	Displays the number of panels the installer is connected to.
4	STATUS	The current acceptance status of the user. To change status press ACCEPT or REJECT
5	+ADD INSTALLER	Click +ADD INSTALLER to add new installers by initiating the 2FA process.




Figure 55: Editing the installers page.

Table 49. Editing the installers page.

Callout	Description	Function
1	RESET PASSWORD	Click to reset installer password. This sends an email to the installer with a reset code.
		Displays a list of panels connected to the installer.
2	-	Click - to remove panel.
3	ADD PANEL	Click ADD PANEL to add a panel to the installer.

Related topics

[Accepting or rejecting installers](#)

Accepting or rejecting installers

To accept or reject multiple installers, complete the following steps:

Note: To accept or reject one installer at a time, select the check box in the status column to toggle between an accept or reject status. For more information, see Status toggle in [Accepting or rejecting installers](#).

1. In the navigation pane, click **System**, then click **Installers**.
2. Select the check box of one or more installers to accept or reject.
3. Perform one of the following actions:
 - Click **ACCEPT**.
 - Click **REJECT**.
4. Click **OK**.

Related topics

[Navigating the Installers page](#)

Registering a user on the server with the mobile application

1. To register to the server, the user opens the user mobile application for the first time and enters the following details:

- Server URL
- Name
- Email address

Note: If successful, the user appears on the **Interactive users** page with a **Not verified** status and receives a 2FA email with a verification code.

2. The user enters the code in the mobile application when prompted.

Note: If successful, the user's status changes from **Not verified** to **Active** after a short time-out period.

3. The user can now add one or more panels to the account via the mobile application.

Note: The **PANELS** column displays the number of panels connected to an account.

Related topics

[Interactive users page](#)

Dashboard page

The **Dashboard** page displays the overall statistical data from the server in a visual format.




Figure 56: Navigating the dashboards page

To see a description of the four types of graphs on the **Dashboard** page, see the following definition list:

EVENTS RATE

The **EVENTS RATE** graph displays visual data of events in three categories: **Alarms**, **Alerts**, and **Other**.

- The Y-axis measures the number of events.
- The X-axis measures time by calendar date.
- Each point on the graph represents 10 minutes.

FAULTY PANELS

The **FAULTY PANELS** graph displays visual data of the percentage of the total panels that are **Faulty**.

- The Y-axis measures from 0% to 100%. All of the panels comprise 100% and the position of the blue and red lines represents a percentage of the total number of panels.
- The blue line represents faulty panels. A faulty panel is a panel with at least one fault. For more information about the faults column, see **FAULTS** column in [Table 7](#).
- The X-axis measures time by calendar date.
- Hover over a particular part of either line to see the percentage. This percentage is a decimal of 1. For example, 0.7 represents 70%.

ALL PROCESSES

The **All processes** pie chart displays visual data of the percentage of processes that fail and succeed.

CONNECTED PANELS

The **CONNECTED PANELS** graph displays visual data of the number of panels that are connected to the server over time.

Note: If a panel is connected, there is a live connection between the panel and the server. The term **Connected** does not mean **Online**. For more information about the connection status, see Connection status in [Table 7](#).

Related topics

[Panels page](#)

[Processes page](#)

[Events page](#)

PowerManage 4.8 updates

See the following list of PowerManage 4.8 updates.

PIR camera zone association

You can associate a PIR (passive infrared) camera with up to eight sensors. If any of the sensors trigger, the PIR camera records video footage for a short period of time.

In the PowerManage web application, the footage associates with the alarm event that the sensor triggers and not the PIR camera. In the following example, the sensor in zone 1 is connected to the PIR camera in zone 248. For more information, see Camera Zone Assign in [Table 50](#) and Zone in [Table 51](#). When the sensor in zone 1 triggers an alarm, the PIR camera in zone 248 records a short video clip.

To associate a PIR Camera with one or more sensors, see [Associating a PIR camera with a sensor](#).




Figure 57: PIR camera zone association

Table 50. PIR camera zone association

Callout	Description	Function
1	UPLOAD button	Click UPLOAD to upload the configuration you make in Camera Zone Assign to the server.
2	PIR camera	Click a PIR camera device to open the device in the examination pane.
3	CONFIGURATION tab	Click CONFIGURATION to edit the device configuration.
4	Camera Zone Assign	Enter the zone numbers of the sensors that you want to trigger the PIR camera.




Figure 58: PIR camera zone association event

Table 51. Zone association event

Callout	Description	Function
1	Camera icon	Indicates that video footage is available from an associated PIR camera.
2	Zone	Indicates the zone number of the sensor.

Associating a PIR camera with a sensor

Note: You can associate a PIR camera with sensors with a PSP 1.30 panel only.

1. To open a panel in the panel hub, on the **Panels** page, in the PANEL column, click the panel name.
2. On the DEVICES tab, click a PIR camera device.
3. In the examination pane, click **CONFIGURATION**. If the configuration parameters are not up to date, click **REFRESH**.
4. Scroll down to **Camera X Zone Assign**. The X stands for the PIR camera device zone number.
5. In a **Zone Cam Trig** field, enter the zone number of the sensor that you want to trigger the PIR camera to record video footage.
6. **Optional:** Repeat Step 5 to associate the PIR camera with up to seven additional trigger sensor devices.
7. To save the configuration in the panel, in the notification panel below the Devices tabs, click **UPLOAD**.

Using video on demand with ITv2 integration

The user or operator can record a short video clip after an alarm with video on demand through the ITv2 protocol integration.

In Neo and PSP panels, video on demand is available only if the FIBRO receiver channel is configured to the PowerManage server. For PSP panels version 1.3 and later, you can use video on demand with the ITv2 integration channel.

PIR camera images during a system test

In a system test, Neo panels version 1.35 and later, and PSP panels version 1.30 and later, upload two images from each PIR camera sensor. You can view the video footage in the PowerManage GUI.

If both the FIBRO receiver and the ITv2 integration channels direct to the PowerManage server, one system test event appears in the PowerManage web application with the PIR camera video footage.

If the ITv2 integration channel only directs to the PowerManage server, two system test events appear in the PowerManage web application. The first system test event, like in previous versions, does not have video. The second system test event contains video footage from the PIR cameras.

Upgrading 4G/LTE modems

You can upgrade 4G/LTE cellular modems for PowerMaster panels. The 4G/LTE modem comprises two parts that you can upgrade separately, the GSM modem and the OTA (Over The Air) modem.

Before you can upgrade either the GSM modem or the OTA modem, technical support must upload the upgrade package to the repository and attach it to the PowerManage server. The packages appear in the global FIRMWARE page and the local FIRMWARE tab.

Note: To upgrade the GSM modem, choose the upgrade package that matches both your current version and the version that you want to upgrade to. To upgrade the OTA modem, choose only the upgrade package that matches the version that you want to upgrade to.

To mass upgrade the GSM modem or the OTA modem for multiple panels, see in [Mass upgrading the firmware of a device](#).

To upgrade the GSM modem or the OTA modem for a single panel, see in [Upgrading the firmware of an individual panel in the panel hub](#).

You can see the 4G/LTE cellular modem on the DEVICES tab in the panel hub. The software version and RSSI also display. For more information see GSM modem and OTA modem in [GSM modem and OTA modem on the devices tab](#).




Figure 59: Global firmware page

Table 52. Global firmware page

Callout	Description
1	Firmware page
2	GSM Modem and OTA modem




Figure 60: Local firmware page

Table 53. Local firmware page

Callout	Description	Function
1	Upgrade packages	Select an upgrade package in the APPLY PACKAGE list.
2	FIRMWARE tab	FIRMWARE tab on the panels page.
3	Upgrade package dropdown list	Click to select an upgrade package from a dropdown list.




Figure 61: GSM modem and OTA modem on the devices tab

Table 54. GSM modem and OTA modem on the devices tab

Callout	Description
1	GSM modem
2	OTA modem

Interactive user management

The Interactive Users page includes additional interactive user management features, to select interactive users see, [Table 55](#) To view all features of interactive user management, see [Table 56](#).




Figure 62: Interactive users page updates

Table 55. Interactive Users page updates

Callout	Description	Function
1	Interactive Users page	For more information, see Navigating the Interactive users page .
2	ADD USER	Click to add a new user with an email address. The new user receives a 2FA verification email to enter in the mobile user app.




Figure 63: Interactive user management

Table 56. Interactive user management

Callout	Description	Function
1	CONNECTED PANELS	Displays the panels the user is connected to. <ul style="list-style-type: none"> PANEL: Displays the name of the panel. GROUP: Displays the panel group. USER: Displays the type of user permissions the user has for the panel
2	SUSPEND	Click to suspend the user.
3	RESET PASSWORD	Click to reset the user's password.
4	REMOVE PANEL BUTTON	Click to remove a panel from the interactive user account.
5	ADD PANEL	Click to add a new panel to the interactive user account.

Panel search by customer information

You can search for a panel on the Panels page using the following information that is on the INFO tab:

- Customer name
- Customer email address
- Customer phone number
- Customer address
- Any comments posted on the INFO tab

For example, you can search for the panel in the following figure that contains the comment, `short remark`. For more information, see Panel in [Table 58](#) and Comment in [Table 57](#). If you type `short remark` in the search bar on the Panels page, the search results display the panels that contain the comment in the INFO tab of the panel. For more information, see CUSTOMER INFO in [Table 57](#).




Figure 64: Customer information in the INFO tab

Table 57. Customer information on the INFO tab

Callout	Description	Function
1	CUSTOMER INFO	Information about the customer that users can edit on the INFO tab.
2	Comment	A comment entered by a user. Click EDIT to leave a comment.




Figure 65: Searching for panels with customer information

Table 58. Searching for panels with customer information

Callout	Description	Function
1	Comment	Type a comment to search the Panels page for any panel with the same comment left in the panel's INFO tab.
2	Panel	Panels that contain the search term in the panel's INFO tab appear in the search results.

Authorization settings for interactive users




Figure 66: Authorization settings

Table 59. Authorization settings

Callout	Description	Function
1	Settings page	For more information, see Settings page .
2	INTERACTIVE tab	For more information, see Interactive tab .
3	AUTHORIZATION SETTINGS	<ul style="list-style-type: none"> FIRST FACTOR EXPIRATION PERIOD [SECONDS]: The time that a user can stay logged on to the app when the AlarmInstall and ConnectAlarm apps are minimized and running in the background. EMAIL CODE LENGTH: The length of the verification email code that the server sends to the user during the 2FA sign up process. ACCOUNT LOGIN LOCK TIMEOUT [SECONDS]: The length of time that the user's account is blocked from a panel if the user enters incorrect 2FA login information for more times than the limit. PANEL LOGIN ATTEMPTS LIMIT: The number of 2FA login retries before the user's account is blocked SECOND FACTOR EXPIRATION PERIOD [SECONDS]: The length of time that the AlarmInstall and ConnectAlarm app stay connected to a panel if the app is minimized and running in the background. EMAIL CODE EXPIRATION PERIOD [SECONDS]: The length of time that the 2FA email verification code is valid. ACCOUNT LOGIN ATTEMPTS LIMIT: The number of 2FA logon retries before the user's account is blocked. PANEL LOGIN LOCK TIMEOUT [SECONDS]: The length of time that access to a panel is blocked if the user enters incorrect 2FA log on information for more times than the limit. PERMANENT USER LIFETIME [DAYS]: The number of days a user has a permanent user status after successfully logging on to a panel. Permanent users can log on to the panel, even if the panel is locked.

Panel connection channel status

To view the channel connection statuses of a panel, see ITv2 integration channels and FIBRO receiver channels in [Table 60](#). In the following figure, the Neo panel has four ITv2 integration connection channels. The first channel is connected to the server and the remaining three channels are not configured.

The Neo panel also has four FIBRO receiver connection channels. The first channel is connected to the server and is online. The remaining three channels are not configured.




Figure 67: Panel communication channel status on the Devices tab

Table 60. Panel communication channel status on the DEVICES tab

Callout	Description	Function
1	Selected panel	Click a panel to open the panel in the examination pane and view the connection channels on CONNECTION STATUS tab.
2	ITv2 channels	There are four ITv2 integration connection channels.
3	FIBRO channels	There are four FIBRO receiver connection channels.

Viewing panel connection channels

1. To open a panel in the panel hub, on the Panels page, in the PANEL column, click the panel name.
2. On the DEVICES tab, click the panel you want. On the CONNECTION STATUS tab, the panel channel connection statuses display in the examination pane.

For more information on panel channel connection statuses, see [Viewing panel connection channels](#).

Reading the diagnostics of a panel

Read the diagnostics of a panel to view the panel power data.

Note: System diagnostics are available for Neo and PSP panels only.

1. To open a panel in the panel hub, on the Panels page, in the PANEL column, click the panel name.
2. From the ACTIONS list, click **Read Diagnostic**. A **Read diagnostic info** process starts in the MY PROCESSES pane. For more information about the MY PROCESSES pane, see [Navigating the MY PROCESSES pane](#).
3. When the process ends successfully, on the DEVICES tab, click the panel.
4. In the examination pane, to open the DIAGNOSTIC tab, click **DIAGNOSTIC**.

To ensure the data is up to date, repeat this procedure to refresh the diagnostic reading.




Figure 68: Starting a read diagnostic process

Table 61. Starting a Read diagnostic process

Callout	Description	Function
1	Read diagnostic info process	When you click Read Diagnostic , a Read diagnostic info process starts in the MY PROCESSES pane.
2	Read Diagnostic	Click to start a Read diagnostic info process.




Figure 69: Panel diagnostic results

Table 62. Panel diagnostic results

Callout	Description	Function
1	Read diagnostic info process	When you click Read Diagnostic, a Read diagnostic info process starts in the MY PROCESSES pane.
2	Selected panel	Click a panel to open it in the examination pane.
3	DIANOSTIC tab	Click DIAGNOSTIC to view the panel's diagnostic information on the DIAGNOSTIC tab.

Enabling or disabling temperature and light statistics for a group of panels with smart devices

Note: Temperature and light statistics are disabled by default for groups. Processing this data increases communication and requires higher bandwidth.

- 1. In the navigation pane, click **System**, then click **Groups**.
- 2. Click the group you want.
- 3. Click **EDIT GROUP**.
- 4. Enable **Temperature/light statistic**.
- 5. Click **SAVE**.

To view the temperature or light statistics of a device, see [Viewing device smart temperature or light readings](#).




Figure 70: Temperature and light statistic results

Table 63. Temperature and light statistic status

Callout	Description
1	Groups page
2	TEMPERATURE/STATISTIC status




Figure 71: Temperature and lights on the METEO tab

Table 64. Temperature and light graph on the METEO tab

Callout	Description
1	DEVICES tab
2	Selected smart device
3	Smart device icon
4	METEO tab

Viewing GSM signal statistics

1. To open a panel in the panel hub, on the Panels page, in the PANEL column, click the name of the panel that you want.
 2. On the DEVICES tab, click the GSM Modem.
 3. To view the GSM statistics, in the examination pane, click **GSM RSSI**.
- Note:** In PowerManage 4.8, GSM modem and OTA modem appear in the DEVICES tab, separate from the panel.
4. **Optional:** To open the GSM RSSI statistics dialog box, click **SHOW**. In the dialog box, you can view GSM RSSI statistical graphs representing interactive time periods.




Figure 72: Viewing GSM signal statistics

Table 65. Viewing GSM signal statistics

Callout	Description	Function
1	GSM modem	A cellular communication modem.
2	OTA modem	An 'Over the Air' software package in the 4G/LTE cellular modem. The OTA modem exists only in PowerMaster panels.
3	GSM RSSI tab	Click GSM RSSI to view the connection strength of the cellular modem over time.
4	SHOW	Click to view a larger graph that is interactive.

Integration session access keys for type 2 ITv2 panels

Neo and PSP panels use an integration session channel. To encrypt the integration session channels, you require an integration session key for each of the four channels.

To access the four keys, in your Neo or PSP panel menu, enter the following:

```
[*][8]<installer code>[851][423]/[450]/[477]/[504]
```

Note: In previous versions of PowerManage, the integration session access key was the same for all panels. From PowerManage version 4.8, the integration session access key is unique to a panel and you cannot use the key for any other panel.

Customer information on the Panels page

On the Panels page, the CUSTOMER column displays the first name of the customer that is associated with that panel. For more information, see CUSTOMER column in the following figure. Click the customer name to view more customer information from the INFO tab. For more information, see Customer information in [Table 66](#).




Figure 73: Customer column on the panels page

Table 66. CUSTOMER column on the Panels page

Callout	Description	Function
1	Panels page	Click to view the connected panels.
2	CUSTOMER column	Displays the customer's first name.
3	Customer information	Click the customer's name to view the following customer information: <ul style="list-style-type: none">Customer nameCustomer email addressCustomer phone numberCustomer addressAny comments posted on the INFO tab




Figure 74:Info tab in the customer column

Table 67. INFO tab information in the CUSTOMER column

Callout	Description	Function
1	Customer information	Appears if you click the customer name. This information populates the INFO tab.

Configuring the removal of events, processes, and reports from the server in rotation

Set the rotation time period to remove events, processes, or reports from the server.

1. In the navigation pane, click **System**, then click **Settings**.
2. On the RESOLVE tab, in the ROTATION pane, click **EDIT**.
3. **Optional:** In the Events Age [DAYS] field, enter the number of days you want events to stay on the server before the system removes them.
4. **Optional:** In the Process Age [DAYS] field, enter the number of days you want processes to stay on the server before the system removes them.
5. **Optional:** In the Report Age [DAYS] field, enter the number of days you want reports to stay on the server before the system removes them.

Figure: Rotation of events processes and reports on the RESOLVE tab




Figure 75: Rotation of events processes and reports on the resolve tab

Table 68. Rotation of events processes and reports on the RESOLVE tab

Callout	Description
1	Settings page
2	RESOLVE tab
3	ROTATION pane

Server CUSTOMER INFO tab in the system settings

You can add or edit the following server administrator customer information in the CUSTOMER INFO tab in the system settings:

- Customer name
- Address
- Web admin email address

Note: The email address in WEB ADMIN EMAIL is also the default super admin logon email address. The default email address is admin@tycomonitor.com.

- Personal email address
- Point of contact name
- Phone number




Figure 76: Customer info tab in the system settings

Table 69. Customer info tab in the system settings

Callout	Description
1	Settings page
2	WEB ADMIN EMAIL
3	CUSTOMER INFO tab

PowerManage 4.10 updates

LTE modems upgrade for V18 panels

You can upgrade the 4G/LTE GSM modem of the following PowerMaster panels: PM360, PM360R and PM30, PM10, PM33E.

For more information, see [Upgrading 4G/LTE modems](#)

Server version 4.8 upgrades panels version 19 and 20, and server version 4.10 includes panels version 18.

Dual path push notifications

A custom event description is defined on the dual path as a description for each event number for each communicator. This custom event description displays in the user app ConnectAlarm as an event or push notification.

Installers management

Installers are managed in the Sytem page in the main menu.




Figure76: Installer management in the main menu

Table 70. Installer management in the main menu

Callout	Description
1	Installers
2	RESET PASSWORD
3	+ADD PANEL or -

1. Click **Installers** and select an installer from the pop-up menu on the right.
2. Click **RESET PASSWORD** to invalidate the installer's current password. The installer receives a 2FA verification email.
3. Add or remove panels from the installer and click on a panel to navigate to the **INSTALLERS** tab.

INSTALLER tab in panel pane

The operator can also add or remove installers that are connected to the panel in **INSTALLERS** tab




Figure77: Installer management from installers tab

Table 71. Installer management from the installers tab

Callout	Description	Function
1	INSTALLER	The Operator can add or remove installers connected to the panel by clicking this tab.
2	+ASSIGN INSTALLER	Click ASSIGN INSTALLER to add a new installer.
3	-	Click the minus button to remove an installer.

Incremental upgrade

An incremental upgrade uses small software packages, where one package contains one tool and is accessed through the internet from a remote software repository. You can incrementally upgrade the PowerManage server so only the relevant part of the server is upgraded, and the remaining server is unaltered.

For incremental upgrades please contact [Tyco's technical support](#).




Figure78: Incremental upgrades

Note: This mechanism is more powerful than the patch's mechanism. The incremental upgrade replaces the existing patch.

VOD history

In previous versions only the last video on demand (VOD) was saved. The server can now store multiple VOD clips on the GUI.




Figure79: VOD History clips on the GUI




Figure 80:Setting the number of VOD history clips

Table 72. Setting the number of VOD history clips

Callout	Description
1	Groups
2	GENERAL
3	VOD HISTORY LOG SIZE

Setting the number of VOD history clips:

1. In the main menu, in the System tab click Groups and select the relevant group.
2. Click GENERAL in the top panel.
3. Click VOD HISTORY LOG SIZE to set the number of relevant clips.

Offline handler tuning for DSC panels

Offline handler tuning corrects the logic for Neo/PSP panels offline in geo-redundancy (master secondary) topology.

If a panel is offline in the master server but online in the secondary server (secondary server received supervision message), then master server does not send a communication trouble message to the CS.

Note: The same communication channel (BBA or GPRS) needs to be connected to both master and secondary servers for the offline logic to work correctly.

CAUTION

Note: Be advised no warning message is displayed before the operation.

If the **REMOVE PANEL BY RESETTING THE RECEIVER IP** option is enabled, then the panel does not enroll back to the server.

The installer can remove the panel from the server by using the app AlarmInstall.




Figure81: Remove panel by resetting the receiver IP

Process creator real name

Hovering the cursor over a user displays the user name and email of the operator that created the process




Figure82: Process creator user name

Log forwarding

Tyco's technical support can configure the server by using the MMI editor to send the server's log for debug purposes.




Figure 83: Log forwarding

GSM/PowerG RSSI, temperature, and light statistic in reports




Figure 84: Meteo options in reports

Including temperature, humidity, brightness or GSM RSSI graphs in PDF reports:

1. Click and select a panel.
2. In the **Reports** tab, click **CREATE REPORT** in the upper-right of the screen.
3. In **Meteo Options**, select the relevant statistics box.
4. Click **SAVE**.




Figure 85: Brightness statistics in reports




Figure 86: GSM RSSI statistics in reports




Figure 87: Temperature statistics in reports

Three separate private remark fields in panel info tab

In the **INFO** tab of a panel there are three remarks instead of one.




Figure 88: Customer remarks

Stream new events – ON

By default, **Stream new events** is turned ON which causes new events to show up in the GUI.




Figure 89: Stream new events on default

Customizable sounds

Sounds are played when an event arrives to the server and can be customized according to category.




Figure 90: Customizable sounds

Configuring sounds:

1. Click user-icon in the upper-right corner of the screen, then click **Settings**. Click the speaker icon.
2. The following four categories of sounds appear:
 - alarm
 - alert security
 - open/close (arm/disarm)
 - and other

Note: These categories are the same as in group forwarding.

3. Click the small triangle on the left or hover the cursor over the sound text to play the audio.

Device ID filtering

DEVICE ID search option is added in the 'Panels' pane.




Figure 91: Device ID filtering

AC Fail false warning fix

AC-failure, low-battery, line-failure, and other options are shown in the **Panels** pane and in **DEVICES** tab after selecting a panel. This only occurs when trouble is active and not in memory. Trouble may remain in memory until the panel is disarmed and armed again, or if the trouble no longer exists).




Figure 92: AC failure in panels pane




Figure 93: AC failure in devices tab

Recent history and Last visit widgets




Figure 94: Recent history and last visit widgets

Table 73. Recent history and last visit widgets

Callout	Description	Function
1	LAST VISIT	Displays the panel name and any interactive user of the panel that has been viewed in current session by the operator. Note: Only shown if a panel has been viewed.
2	Recent History	Lists all the panels and master users that the operator has viewed during the current session.
3	▶	Click one of the panels from the list to display all the master user’s registered panels. The operator can click and view panels here. If the panel does not have a master user, it displays Unassigned .

Interactive Users

The **Interactive Users** tab is located in the main menu.




Figure 95: Interactive users

Secondary node group synchronization

Groups created on the master node are synchronized with the secondary node:

- New groups created on master node are synchronized with secondary node with its attributes.
- Panels added or removed from a group on master node are also synchronized with secondary node.