


SFX/TWINAX-272-LSZH-BLU

Twinaxial 272 2 Core 20AWG Overall Braided Screen 600V Blue LSZH (9272)



Cable Construction	
Cable Construction	2 Cores
Conductor	Tinned Copper
Conductor Diameter (mm)	0.32 ±0.008 x 7(0.52mm ²)
Stranded Diameter (mm)	0.81
Insulation	
Insulation	Solid PE
Insulation Thickness (mm)	0.51
Insulation Diameter (mm)	2.00 ±0.10
Insulation Colours	Clear, Blue
Filler	1.2mm PE Strip x 2
Mylar Spiral	≥115%
Braiding Shield	Tinned Copper
Braiding Construction	0.12 ±0.008 x 16 x 9
Braiding Coverage	93% ±5%
Jacket	
Jacket	LSZH
Jacket Thickness (mm)	0.85
Overall Diameter (mm)	6.20 ±0.20
Jacket Colour	Blue RAL 5015
Sheath Printing	Twinaxial 272 2x20AWG Overall Braided Screen LSZH (PO) (m)
Reaction to Fire	Eca
Electrical Characteristics	
Max Conductor DC resistance @ 20°C	<33.10Ω/km
Rated Temperature	70°C
Rated Voltage	600V
Insulation Resistance @20°C	>200MΩ/km
Standards	CE2014/30/EU, RoHS2 2011/65/EU, LVD 2014/35/EU
Application	Control, instrumentation, RF application and computer systems.