



Qing Cables

Malmesbury Road,
Kingsditch Industrial Estate,
Cheltenham, Glos, GL51 9PL. UK




T: 01242 224141

F: 01242 224134

www.qingcables.com

enquire@qingcables.co.uk

This specification and images
© Qing Cables Ltd



URM70

75 Ohm CCTV Coaxial

Physical Characteristics

Conductor:	Stranded Pure Copper
Size:	7/0.19mm
Dielectric:	Solid PE [Ø3.25mm]
Screening:	Copper Clad Aluminium Wire Braid
Outer Sheath:	See Below
Sheath Colours	See Below
Weight	See Below

Other versions available:

Sheath	Information	Sheath Colour (s)	Overall Diameter	Weight KG/KM
PVC		Black/White	Ø5.80	40
LSF	Low Smoke & Fume	Black	Ø5.80	40
LSZH	Low Smoke Zero Halogen	Black/White	Ø5.80	40
PE/PP	Direct Burial [Heavier Duty External / Duct]	Black	Ø8.00	60

Electrical Characteristics

Conductor DC Resistance	93.8 [Ω/km]
Rated Temperature	80°C
Rated Voltage	300V
Insulation Resistance	>500 [MΩ/km]
Nominal Capacitance	<67pF/M [±10%]
Velocity Ratio	66.7%
Nominal Impedance	75Ω

Attenuation

@20°C (dB/100M)

5MHz	8.5	800MHz	35.8
100MHz	13.8	860MHz	37.2
200MHz	16.5	1000MHz	39.5
450MHz	26.0		

QUALITY
CONNECTIVITY

LSZH Sheath meets:
IEC60332-1 [Flame Propagation]
IEC60754 [Halogen Free]
IEC61034 [Smoke Emissions]

Our full product range includes:

COAXIALS: RG / URM Digital / Satellite (incl Sky+) [CAI Approved] CCTV RF / Microwave
TELECOM: CW1308LSF CW1308LSZH CW1308B CW1128 CW1128/1198 CW1128/1252 Dropwire Jumper Wire CW1311 3002 Coax Flat Cordage
STRUCTURED WIRING: CAT5e UTP & FTP CAT6 UTP & FTP CAT6A U-UTP & U-FTP CAT7A S-FTP [PVC LSZH External UV PE SWA Versions]
DATA: Single Pair Shielded/Unshielded Overall Shielded Core Overall Shielded Pairs Foil & Braid Shield Individual Shielded Pairs Twinax [Belden Equivalents]
DEF STANDARD: 7/0.2 Unscreened / Screened 16/0.2 Unscreened / Screened
CCTV / SECURITY: RG/URM Coaxial Video/Door Entry Composites B54737 Alarm Flex Mains Flex PH30/PH120 Fire Performance Cable
FIBRE OPTICS: Singlemode/Multimode Loose Tube/Tight Buffer Internal/External LSZH Corrugated Armour/SWA
SPEAKER FLEX: "QCSound" Pro Grade OFC Cores LSZH Sheaths External Grade
CONNECTED HOME: QCMC5 [2x HDTV Coax] + [2x CAT6] + [1x CAT5e]
CONTROL BUS CABLES: KNX/EIB Bus Cables DataBus® DiviceNet™ PROFIBUS Lutron Grafik Eye® CRESSNET® SIMMTRONIC - EBUS / MBUS / OBUS Echelon LonWorks® Mode Lighting
MAINS FLEX: H03VV-F H03VVH2-F H05VV-F H05Z1Z1-F BS6500/BS7919 Arctic Grade H07RN-F
SOLAR: TUV Approved PV Cable.

All our products are RoHS2 [2015/863] and REACH Compliant unless stated otherwise.

Every care is taken to ensure all information contained in this publication is correct.

No legal responsibility can be accepted for any inaccuracy.

The company reserves the right to alter or modify the information without notice.

Any images are for illustration purposes only.

Registered in England & Wales No. 2181405 Directors: M.L.G.Taylor, L.J.Taylor, K.M.Wylde

Statement of Conformance

It is hereby certified that any goods supplied that reference those above, conform to this specification unless otherwise noted