

**1682****IKALL VIP AUDIO ONLY SPEAKER**

Audio unit for ViP system. Complete with terminal block and digital audio management system with Echo-cancelling, watertight loudspeaker and electret microphone, loudspeaker volume adjustable from the front. For fitting in modules: part. 33400, 33401, 33402. Dimensions: 102x55x38 mm.



**1682**

## IKALL VIP AUDIO ONLY SPEAKER

### GENERAL DATA

Type	Audio and video unit
Height (mm)	102
Width (mm)	55
Depth (mm)	43
Product color	White
Product weight (g)	200
Type of finishing materials	ABS

### COMPATIBLE SYSTEMS

Vip system	Yes
------------	-----

### AUDIO FEATURES

Microphone	9.7 (ø), omnidirectional
Loudspeaker	50mm (Ø), 8 Ohm, 0.2W

### ELECTRICAL CHARACTERISTICS

Supply voltage	33VDC
----------------	-------

### HARDWARE FEATURES

Clamps	TX- TX+RX- RX+V- V+RTE GND SE COM NC NO
Removable terminals	Yes
Number of inputs (n°)	1
Number of outputs (n°)	2
Type of outputs	Relay (C-NO-NC, 10A@12÷24 VAC/VDC), SE: unlock pulse of 4A, holding current of 200mA for 12VAC / DC locks (maximum impedance 18 Ohm)
Communication ports	Ethernet

### SETTINGS

Loudspeaker volume	Yes
--------------------	-----



**1682**

## IKALL VIP AUDIO ONLY SPEAKER

### NETWORK AND COMMUNICATION PROTOCOLS

Type of LAN network	Ethernet 10 Mbit/s
---------------------	--------------------

### PROGRAMMING MODE

ViP Manager software	Yes
----------------------	-----

### ENVIRONMENTAL AND COMPLIANCE FEATURES

Operating temperature (°C)	-25 ÷ 55
Operating humidity (RH max) (%)	25 ÷ 95
Environmental class	IV
CE certifications	EMC 2014/30/UE (EN 61000-6-1:2007 , EN 61000-6-3:2007+A1:2011), RED 2014/53/UE (EN 60950-1:2006+A11:2009+A1:2010+A12:2011

### MAIN FUNCTIONS

Door opener	Yes
Number of auxiliary relays (n°)	1
Input for local door release button	Yes
Visual indications of system status	Yes
Acoustic signals of system status	Yes
Speech synthesis of system status	Yes