

4G Series Digital GSM

Vandal Resistant 4G 4812 Series Digital GSM Panels



Vandal Resistant Panel

Panels are manufactured from 316 marine grade brushed stainless steel.

2G, 3G and 4G Compatible

All 4G GSM panel versions are compatible with 2G, 3G and 4G networks and designed for global use.

Blue Backlit 128x64 Graphical LCD Display

Graphical DDA compliant call progress indication with integrated voice annunciation and acoustic signals.

Built-in RFID proximity reader

Program key fobs via SMS text messages, PC software or VINDEX GSM mobile Apps to operate the relay.

750 or 1000 Users

Panels with 750 programmable user or 1000 programmable user options available.

Up to 32 Temporary Dial to Open Numbers

In addition to the standard dial to opens, store up to 32 temporary dial to open numbers programmable from 1 - 255 hours.

With 4G GSM comes freedom. Answer calls from your door or gate from any telephone number including your mobile and from anywhere in the world.

The latest VINDEX digital 4G GSM can call up to 750 apartments each with a divert facility to call up to 3 additional numbers should the first be busy or unanswered (1000 user option is also available with only 2 programmable numbers per user).

Vandal Resistant panel variants include a large blue backlit graphical LCD display, illuminated numerical keypad with additional apartment search/scroll buttons or alpha keys A-F.



THE POWER TO SECURE

4G Digital GSM Key Features

- Vandal resistant 316 grade stainless steel panels with onscreen programming menus.
- Graphical call progress, voice annunciation & acoustic signals.
- Blue backlit 128x64 pixel graphical display and alpha-numeric keypad.
- Micro-USB and RS485 BUS connection for ease of programming using the **GSMSK** PC software.
- Facility to remotely program the digital GSM "over the air".
- RS485 BUS can also be used for parallel connection of **Art.4850R** proximity reader or **Art.4903** keypad.
- 750 programmable users (each with 4 numbers, 1 primary and 3 diverts), 1000 user option also available.
- 750 programmable access codes (1 per user), 1000 user option also available.
- Automatic time correction feature and daylight saving time adjustments.
- Dial to open facility for up to 3000 stored numbers including feature to store up to 32 temporary dial to open numbers.



Part Code	Series	Description
4812/4G	Digital GSM	Vandal Resistant 4000 series 4G Digital GSM panel (A-F) requires 4882 (surface) or 4852 (flush) box
4812R/4G		Vandal Resistant 4000 series 4G Digital GSM panel (search) requires 4882 (surface) or 4852 (flush) box
VR4812/4G		Vandal Resistant 4G Digital GSM panel (A-F) with flush bezel back box
VR4812R/4G		Vandal Resistant 4G Digital GSM panel (search) with flush bezel back box
4882	4000 series modular	4000 series 2 module surface back box
4852		4000 series 2 module flush back box
4892		4000 series 2 module surface rainshield
4872		4000 series 2 module flush rainshield
VRDSB140x280	VR Panel Accessories	Stainless steel surface box for VR4812/4G and VR4812R/4G panels
HDR-15-12	GSM Accessories	Slim line 12Vdc, 1.25A power supply
434		GSM antenna with magnetic base (inc. L bracket)
434/BLOCK		Block GSM antenna (inc. SMA-M connector)
434/HG/5M		High Gain GSM antenna with 5m cable length
434/HG/15M		High Gain GSM antenna with 15m cable length
955/T		Blue VIDEX proximity fob
955/C		0.75mm thick white VIDEX proximity card
GSMSK		GSM PC programming software
PROX-USB		Deskmount proximity reader for programming

Download the
VIDEX GSM
mobile apps from
Google Play or
the App Store



Vindex GSM Mobile Apps

Two GSM smartphone apps are available: the **SMS Wizard** app for users and the **SMS Wizard PRO** app for installers and engineers, both of which are available to download for **FREE** for both Android and iOS devices from Google Play or the App Store.



VIDEX SECURITY LTD.

Main UK Office

1 Osprey, Trinity Park, Trinity Way,
London, E4 8TD
tel: 0370 300 1240 - fax: 020 8523 5825

www.videxuk.com

Northern UK Office

Unit 4-7 Chillingham Ind. Estate, Chapman Street,
Newcastle Upon Tyne, NE6 2XX
tel: 0370 300 1240 - fax: 0191 224 1559

