

4000 Series Button Modules

4000 Series Button Expansion Modules



**BUTTON
MODULE**



| Art. | 4842 | 4842D | 4843 | 4843D | 4844 | 4844D | 4845 | 4845D |
|-------------------------------|---|------------|-----------------------|--------------------|-----------------------|----------------------------|-----------------------|-------------------------------------|
| DESCRIPTION | Modular 4000 series button expansion modules | | | | | | | |
| NO. OF BUTTONS | 2 | 4 | 3 | 6 | 4 | 8 | 5 | 10 |
| FRONT FASCIA OPTIONS | Stainless Steel (standard), /A Anodized Aluminium, /HB High Brass | | | | | | | |
| NAME PLATE & BACK LIGHT | Yes: 2 (backlit blue) | | Yes: 3 (backlit blue) | | Yes: 4 (backlit blue) | | Yes: 5 (backlit blue) | |
| MODULE SIZE | 1 module 4000 series: 103 (W) x 120 (L) x 30 (D) mm | | | | | | | |
| BUTTON ISOLATION JUMPERS (JP) | JP: 2C | JP: 2C, 7C | JP: 2C, 3C | JP: 2C, 3C, 7C, 8C | JP: 2C, 3C, 4C | JP: 2C, 3C, 4C, 7C, 8C, 9C | JP: 2C, 3C, 4C, 5C | JP: 2C, 3C, 4C, 5C, 7C, 8C, 9C, 10C |
| SYSTEM COMPATIBILITY | Compatible with all systems except the IP video system | | | | | | | |
| WORKING VOLTAGE | 12Vdc (for name plate illumination) | | | | | | | |
| POWER CONSUMPTION | Max. During Operation: 45mA | | | | | | | |
| WORKING TEMP. | -10° to +50°C | | | | | | | |