



# MINI SWITCH MONITOR

## DESCRIPTION

Apollo's new Mini Switch Monitor\* is a miniature interface with an entirely new housing. The unit is designed to fit into equipment with limited space or mounted within an enclosure such as a manual call point. The interface can also be fitted onto a standard 35mm DIN-rail using a twist-click motion\*

## FUNCTION

The unit is designed to monitor the state of one or more single-pole, volt-free contacts and reports the contact status to Apollo compatible control panels.

## FEATURES

The Mini Switch Monitor measures just 39mm x 39mm x 20mm. This makes it ideal for use where space is limited. It can also be mounted into other equipment.

The device also features a short-circuit isolator as standard.

The Mini Switch Monitor can be used as an interrupt or non-interrupt device. The interrupt feature means the unit can be used where a priority response is required, in particular for monitoring an individual or a zone of conventional manual call points.

In addition to 'normal', 'fault' and 'alarm' states, the unit also provides a 'pre-alarm' state which allows the investigation of a potential alarm in order to help prevent false alarms.



Part no 55000-760

The unit has three status LEDs. Red illuminates when in alarm, green means the device is polling and yellow can mean either a short-circuit on loop-wiring (constant) or a fault on the monitored circuit (pulsing). Different coloured LEDs mean clearer status indication.

**Dimensions and weight of Mini Switch Monitor:**  
39 x 39 x 20mm 30g

\* Patents applied for



INVESTOR IN PEOPLE



A HALMA COMPANY

© Apollo Fire Detectors Limited 2008

### Overseas offices:

America | China | Germany | Ireland | Spain

36 Brookside Road, Havant,  
Hampshire, PO9 1JR, UK.

Tel: +44 (0)23 9249 2412  
Fax: +44 (0)23 9249 2754

Email: [sales@apollo-fire.co.uk](mailto:sales@apollo-fire.co.uk)  
Web: [www.apollo-fire.co.uk](http://www.apollo-fire.co.uk)