

XTL-60041610

XTRALIS-ADPRO iFT 16IP, includes
6TB HDD - 8I/4O, includes 16 IP
channels

Intrusion/LoiterTrace Licenses NOT
included

Offers up to 32 IP channels (With
analytics 16+16)

Compatibility with the leading camera
brands: Safire, Avigilon, Axis, Bosch,
Hikvision, Hikvision AVE, Honeywell...

Compatibility with ONVIF S-profile

Video recording, video analysis and
streaming (ready for complete remote
monitoring)



XTRALIS-ADPRO iFT 16IP, includes 16 IP channels

Includes 6TB HDD

Provides up to 32 IP channels that can hold up to 16 IP channels with 16 video analytics channels (exchanging 1 IP channel for 1 video analytics channel)

Loiter and IntrusionTrace licenses are NOT included

Compatibility with main camera brands and ONVIF S-Profile

Compatibility with 360° cameras + correction of spherical aberration of images.

Video recording, video analysis and streaming (ready for complete remote monitoring)

Expandable: Up to 156 inputs and 140 outputs (8 inputs / 4 outputs in the box)

Reliable data storage: supports up to 3 x 10 TB HDD, support for RAID 1 (requires minimum 2 identical hard drives)

Remote Deployment: Commissioning, installation, configuration and management

Field programmability using the Xchange licensing tool from Xtralis: Fast implementation of Xtralis xTrace Analytics applications (pay-per-use), video licenses, and firmware upgrades

Mobile applications for monitoring, verification and remote control

Compliance with BS 8418:2015

DGUV-UVV Kassen certification

Specifications

Operating system	ADPRO® XO™ Security operating system, based on Linux
Video input	1–32 IP cameras (For optimal performance, disable monitor output when using more than 16 IP cameras)
Video output	XGA – Multiple matrix views
Video compression	H.264/H.265 (H.265 supported with Safire, Hikvision and generic controllers)
Video Resolution	Up to HD/MP resolution (Depending on the camera)
Images/second	Full HD @25/30 ips – Megapixels: ips is depending on the camera
Bandwidth Capacity	32 x 5 Mbps
Bandwidth Management	Configurable bitrate constant or variable / Bandwidth limiter configurable
Audio input	Supports built-in audio input (Depending on the camera)
Audio output	Standard: 1 line output. Optional: Up to 1 per camera via audio switcher audio. Audio output in IP cameras (depending on the camera) with ONVIF Profile S controller
Command inputs	8 box inputs (supervised) + 20 inputs (supervised) with interface module USB XO I/O via Net I/O module with PoE: Up to 128 (Supervised or unsupervised inputs depending on hardware and firmware V2 of Net I/O)
Relay outputs	4 outputs in the box (SPDT) + 8 outputs (SPDT) with USB XO I/O interface module via Net I/O module with PoE: Up to 128 (SPDT)
Web server	XO Client - Integrated Web Client Application (ActiveX)
Ethernet	2 x 100/1000BASE-T, autodetection, full duplex, RJ45
Recording Type	Schedule / Detection / Event
IP Camera Integration	Brand specific driver, generic or with ONVIF S-profile driver (Depending on the camera)
Management	Web client interface (XO client), ADPRO VideoCentral Platinum, HeiTel Event Management Software, third-party software (available SDK) and iTrace App for iOS/Android
Power supply	100–240 VCA, 50/60 Hz
Operating temperature	5–40 °C
Humidity	20-93 % relative humidity without condensation
Disk Capacity	Max. 3 x SATA 10 TB HDD. Compatibility with RAID 1. 2 HDD (min. 2 identical HDDs)
Warranty	2 years
Dimensions (W x H x L)	441 x 88 x 305 mm
Video Analysis	Basic motion detection (VMD), camera sabotage detection. Up to 32 IntrusionTrace™ and LoiterTrace™ analysis channels (datasheets available separately)
Mobile Apps	iTrace, iPIR and iCommission