

# FirePower



## CO<sub>2</sub> EXTINGUISHERS

- Squeeze grip operation
- Non-magnetic model supplied with blue handle
- CO<sub>2</sub> harmless to machinery
- 2kg model supplied with frost free horn as standard
- Polished aluminium model has clear polyester powder coating
- Complete with wall bracket

Type	CO <sub>2</sub> Aluminium	CO <sub>2</sub> Aluminium	CO <sub>2</sub> Polished Aluminium	CO <sub>2</sub> Aluminium Non-Magnetic
Capacity (kg)	2	5	2	2
Fire rating	34B	70B	34B	34B
Height (mm)	490	750	490	490
Cylinder diameter (mm)	117	152	117	117
Overall width (mm)	180	310	180	180
Filled weight (kg)	4.91	11.43	4.91	4.91
Range of throw (m)	>4	>4	>4	>4
Duration of discharge (secs)	8	14	8	8
Working pressure (at 20°C)	56 bar	56 bar	56 bar	56 bar
Temperature range (°C)	-30 to 60	-30 to 60	-30 to 60	-30 to 60
BS EN3 approved	✓	✓		✓
MED approved		✓		
Part number	9705/00	9706/00	9705/06	9705/65
Model number	FPC2SC	FPC5C	FPC2SC	FPC2SC



Tel: 0161 654 2222 | Freefax: 0800 281 035

Website: [www.thomas-glover.co.uk](http://www.thomas-glover.co.uk) | Email: [tgsales@tgproducts.co.uk](mailto:tgsales@tgproducts.co.uk)



TG Products Ltd, Parkfield House, Manchester Old Road, Middleton, Manchester, M24 4DY