

Features

- Powder Coated Steel Construction
- Mounting holes to mount the unit securely by its base
- Vented both sides for improved airflow
- Anti drill radial lock for added security
- Easy cable access at rear, eg BNCs, IEC plugs and data cables
- LDVE, LDVR2 & LDVR2-F have an aperture for our rack mount surge protection units
- VDC, LDVR1, LDVR1-F, LDVR2 & LDVR2-F have added front vent for HDD ventilation
- LDVR1-F 1 x 12v fans expelling hot air from the cabinet @ 35CFM includes 12v PSU
- LDVR2-F 2 X 12v fans expelling hot air from the cabinet @ 70CFM includes 12v PSU

HAY-LDVR1 & LDVR1-F



HAY-LDVE



HAY-V1100-200



HAY-LDVR2



HAY-LDVR2-F

	DEPTH	WIDTH	HEIGHT	WEIGHT
--	-------	-------	--------	--------

HAY-LDVE	External	540mm	510mm	183mm	10.9kgs
	Internal	510mm	506mm	155mm	10.9kgs
HAY-V1100-200	External	450mm	260mm	238mm	6.2kgs
	Internal	428mm	244mm	233mm	6.2kgs
HAY-LDVR1	External	445mm	404mm	120mm	6.0kgs
	Internal	400mm	354mm	91mm	6.0kgs
HAY-LDVR1-F	External	445mm	404mm	120mm	6.3kgs
	Internal	400mm	354mm	91mm	6.3kgs
HAY-LDVR2	External	595mm	510mm	220mm	16.1kgs
	Internal	560mm	506mm	185mm	16.1kgs
HAY-LDVR2-F	External	595mm	510mm	220mm	16.4kgs
	Internal	560mm	476mm	185mm	16.4kgs