

Code: OCTOPUSDQ

CEILING PIR DETECTOR **OCTOPUSDQ** PYRONIX

Passive Infra Red detector to ceiling mount.



| | |
|-----------------------------------|--|
| Application: | Indoor |
| Pyroelectric sensor: | quadruple |
| Sensor type: | Passive Infra Red (PIR) |
| Range: | 12 m |
| Sensitivity adjustment: | <ul style="list-style-type: none"> • Automatic, • 2 - step, manual |
| Pet immunity: | — |
| Maximal outputs load: | 50 mA / 60 V DC |
| Digital temperature compensation: | ✓ |
| Alarm output: | NC / EOL-NC / 2EOL-NC |
| Power supply: | 9 ... 16 V DC / 15 mA at 12 V (max) |
| Target speed range: | 0.3 ... 3 m/s |
| Protection class (Grade): | Grade 2 |
| Operation temp: | -10 °C ... 40 °C |
| Weight: | 0.06 kg |
| Dimensions: | Ø 94 x 33 mm |
| Manufacturer / Brand: | PYRONIX |
| SAP Code: | 361300181 |



DATA SHEET

| | |
|----------------------|------------|
| Manufacturer's code: | OCTOPUS DQ |
| Guarantee: | 5 years |

