

# MOULDED CABINET

## Loudspeakers



➤ **PBC6/T**

➤ **PBC6/TC**

### TECHNICAL SPECIFICATIONS

Rated power, Watts	6
Tappings 100 volt line, Watts	6 / 3 / 1.5 / 0.75 / 0.25
Transformer Impedance, Ohms, 100V	1.67k/3.33k/6.66k/13.3k/39.9k
Tappings 70.7 volt line, Watts	3 / 1.5 / 0.75 / 0.25 / 0.125
Driver impedance, Ohms	8
Effective frequency range, Hz (BSEN60268-5)	160 – 18,000
S.P.L. @ 1m, 1 watt, dB, Test Signal Bandwidth 100Hz-10 kHz	96
S.P.L. @ Full power Octave Bandwidth, dB	104
Acoustic Power (dB-PWL@1 watt) 1 k/2kHz, dB	94/95
Dispersion at 1k/2k Hz, Degrees	180/120
Directivity Axial Q factor, 1 k/2kHz	3.6/5.8
Dimensions, front & depth, mm	330 x 240 x 90
Net weight, Kgs	1.15
Colour/Finish	White
Material	ABS moulding with UV inhibitors Steel mesh
Mounting	Keyhole and/or screws

➤ PBC6/TC is BS5839 Part 8 voice alarm compliant


EASE, CATT, ULYSSES and Architectural specifications are supplied on the disc inserted at the back of this folder  
Manufacturer reserves the right to alter specifications without notice – March 2007

# PBC6/T PBC6/TC

MOULDED CABINET LOUDSPEAKERS


## front view

unit: mm




## top view

unit: mm




## circuit diagram

### PBC6/TC



## speech octave band sensitivity



Effective Frequency Range **PBC6/T PBC6/TC** 160Hz - 18,000Hz



**Penton UK Ltd**

Unit 2 Teville Industrials | Dominion Way | Worthing | West Sussex | BN14 8NW

T: +44 (0)1903 215315 | F: +44(0)1903 215415 | E: SALES@PENTONUK.CO.UK

[www.pentonuk.co.uk](http://www.pentonuk.co.uk)