

# Conventional Weatherproof Beacon

## CWST-RR-W5



### Features

- ▶ Approved to EN54-23, C & W categories
- ▶ Advanced optics ensures superior light coverage at low current draw
- ▶ Synchronised flash exceeds EN54-23 standard
- ▶ Red light flash
- ▶ Soft start feature reduces power surges during system start-up
- ▶ IP65

### Description

CWST-RR-W5 features high output LEDs, advanced optics and an innovative lens design, providing outstanding Omni-directional light coverage at low current draw. Specifically designed for, and approved to meet EN54-23, the CWST-RR-W5 delivers outstanding quality, reliability and long operational life. Weatherproof base provides IP65 for external use applications.

### Specification

Ordering Codes	CWST-RR-W5
Case Colour	Red
Lens Colour	Clear
LED Colour	Red
Cable Terminal Size	0.5-2.5 mm <sup>2</sup>
Material	Lens: PC Body: PC-ABS
Weight (g)	171
Dimensions	Ø 100 mm x H 97 mm
Operating Temperature	-25 °C to 70 °C
Relative Humidity	93% ±3% non-condensing
Ingress Protection	IP65
Operating Voltage EN54-23	12 to 29 V dc
Average Current Consumption	26 mA @ 29 V dc

## Product Performance

	Wall mount W Class	Wall Mount W Class	Ceiling Mount C Class	Ceiling Mount C Class
LED Colour	White	Red	White	Red
EN54-23 Coverage Volume Code	W-2.4-9.0	W-2.4-6.2	C-3-9.5 C-6-9.5 C-9-9.5	C-3-9.4 C-6-8.6
Installation Height (X)	2.4 m	2.4 m	3 m 6 m 9 m	3 m 6 m
EN54-23 Coverage (Y)	Cube YY 9.0 m	Cube YY 6.2 m	Cylinder Ø 9.5 m	Cylinder Ø 9.5 m 8.6 m
EN54-23 Coverage Volume	194 m <sup>3</sup>	92 m <sup>3</sup>	213 m <sup>3</sup> 425 m <sup>3</sup> 638 m <sup>3</sup>	208 m <sup>3</sup> 348 m <sup>3</sup>
Flash Rate	0.5 Hz	0.5 Hz	0.5 Hz	0.5 Hz
Operating Voltage Range	12 to 29 V	12 to 29 V	12 to 29 V	12 to 29 V
Synchronisation	Automatically on power up, exceeds EN54-23 standard			

## The Range

Part No.	Body Colour	Flash (LED) Colour	Base Option	Lens Colour
CWST-RW-S5	Red	White	Low Profile	Clear
CWST-RW-W5	Red	White	IP65/Deep	Clear
CWST-RR-S5	Red	Red	Low Profile	Clear
CWST-RR-W5	Red	Red	IP65/Deep	Clear
CWST-WW-S5	White	White	Low Profile	Clear
CWST-WW-W5	White	White	IP65/Deep	Clear
CWST-WR-S5	White	Red	Low Profile	Clear
CWST-WR-W5	White	Red	IP65/Deep	Clear