

DL 8

Door loop

Technical data

| | |
|------------------------------|------------------------------------|
| Outer diameter mm | 8 |
| Inner diameter mm | 6 |
| Max cable diameter mm | 4 |
| Length mm | DL 8-40 - 400 mm, DL 8-60 - 600 mm |
| Mounting plate dimensions mm | 29.5 x 29.5 x 10 mm |



The DL 8 series of door loops is used to protect and simplify transmission of signals with a cable from windows and doors to the frame. The loops consist of a long, stainless steel armoured flexi-tube, with two end caps with locking grooves to secure the flexi-tube and provide a safe installation. The stainless steel flexitube is available in 2 lengths - 400 mm and 600 mm. The cable is protected against the sharp edges of the metal flexi-tube at each end with a plastic conduit that allows a maximum cable diameter of 4 mm. The flexi-tube has an outer diameter of 8 mm and an inner diameter of 6 mm. The door loops are available in a nickel-plated design or an either white or brown plastic coating. Delivered complete with 4 screws.

ORDERING INFORMATION

| Code | Description |
|------------|------------------------------------|
| DL 8-40 | Door loop, 400 mm, stainless steel |
| DL 8-40 W | Door loop, 400 mm, white |
| DL 8-40 B | Door loop, 400 mm, brown |
| DL 8-40 BL | Door loop, 400 mm, black |
| DL 8-60 | Door loop, 600 mm, stainless steel |
| DL 8-60 W | Door loop, 600 mm, white |
| DL 8-60 B | Door loop, 600 mm, brown |
| DL 8-60 BL | Door loop, 600 mm, black |