

**KAE5061****5-wire single-family audio kit. Extra-Mini.**

The kit includes: one Mini series door-entry phone art. 2702W, one transformer art. 1200, one Extra series external unit with 1 call button art. ET5001. The kit can be expanded with another door-entry phone. The external unit can be surface-mounted or flush-mounted using the relevant accessories supplied with the kit.

AWARDS



KAE5061

5-wire single-family audio kit. Extra-Mini.

PRODUCTS IN THE KIT



ET5001 Extra 4+N. series entrance panel kit. 1 button

Extra series external unit with 1 call button. Stainless steel cover and blue nameplate backlighting. Complete with flush-mount box and wall bracket. Dimensions 95 x 135 x 6.5 mm (flush) - 25 mm (surface). 5-Wire cabling.

GENERAL DATA	
Type	Monoblock
Flush-mounted	Yes
Wall-mounted	Yes
HARDWARE FEATURES	
Clamps	~* ~ 2 3 4 S1 S2
ENVIRONMENTAL AND COMPLIANCE FEATURES	
Operating temperature (°C)	-25 ÷ 55



KAE5061

5-wire single-family audio kit. Extra-Mini.



2702W 2-BUTTON MINI DOOR-ENTRY PHONE, TRADITIONAL

MINI series door-entry phone for traditional system with electronic call and key button. Call volume and privacy adjustment by means of 3-position selector. Privacy activation is indicated by a red light.
Dimensions: 105x191x28 mm

GENERAL DATA	
Height (mm)	190
Width (mm)	105
Depth (mm)	28
Product color	White
Type of finishing materials	Plastic
Product weight (g)	260
Wall-mounted	Yes
Desk base-mounted	Yes

COMPATIBLE SYSTEMS	
Traditional system	Yes

AUDIO FEATURES	
Microphone	4mm (Ø), Omnidirectional
Loudspeaker	0.50mm, 0.5W

ELECTRICAL CHARACTERISTICS	
Supply voltage	15÷16VDC
Absorption in stand-by (W)	3
Maximum absorption (W)	6

HARDWARE FEATURES	
Type of buttons	Mechanical
Service buttons	Lock-release



KAE5061

5-wire single-family audio kit. Extra-Mini.

HARDWARE FEATURES

Clamps	S 2 3 4 P1 P2
Total buttons (n°)	2

ENVIRONMENTAL AND COMPLIANCE FEATURES

IP protection rating	IP30
Operating temperature (°C)	-5 ÷ 55
Operating humidity (RH max) (%)	25 ÷ 95
Environmental class	III
CE certifications	RoHS II - 2011/65/UE (EN IEC 63000:2018), EMC 2014/30/UE (EN 61000-6-1:2007 , EN 61000-6-3:2007+A1:2011)

GENERAL FEATURES

Door opener	Yes
Silent mode (Privacy)	Yes
Ringtone volume control	Yes
Electronic bell	Yes



KAE5061

5-wire single-family audio kit. Extra-Mini.



1200 **TRANSFORMER 10VA 0-230V/0-12V**

Transformer with 230V primary winding, 12V AC / 900 mA secondary winding for continuous use. Dimensions: 53x95x65 mm (3 DIN modules).

MAIN FEATURES	
Supply voltage	230
Applicable to DIN rail	Yes
Number of DIN modules (n°)	3
Max. current delivered (A)	0.9
GENERAL DATA	
Height (mm)	95
Width (mm)	53
Depth (mm)	65
Type of finishing materials	Plastic
Operating temperature (°C)	-5 ÷ 40
COMPATIBILITY	
Simplebus 2 audio/video system	Yes
Building Kit audio/video system	Yes
Simplebus 2 audio system	Yes
Simplebus 1 audio system	Yes
Vip system	Yes
Kit audio/video system	Yes
Traditional system	Yes
Simplified system	Yes
ELECTRICAL SPECIFICATIONS	
Maximum power delivered (W)	15

**KAE5061****5-wire single-family audio kit. Extra-Mini.****ACCESSORIES****ET9150 Flush-mounted box for Extra entrance panel kit**

Flush-mounted box for Extra series external unit art. ET5001 - ET5002 - ET0001. Dimensions: 134.5 x 93.5 x 25 mm

**ET9160 Wall bracket for Extra entrance panel kit**

Wall housing for Extra series external unit art. ET5001 - ET5002 - ET0001. Dimensions: 94 x 134 x 19 mm

**1229 EXTENSION SOUNDER**

Additional bell for call repetition can be controlled directly from terminals S- and S+ of the brackets and/or from the telephones. Surfacemounted or on civil series 503 box. Dimensions: 110X75X29 mm.