

Wireless Receivers

Connect any control panel* to
Enforcer two-way wireless devices



PCX-RIX32-WE

UR2-WE
Universal Reciever

Connecting Enforcer Two Way Wireless devices to ALL brands of control panels* is now a reality, offering the ultimate in flexibility whether it be for new or existing systems.

No longer are you constrained by the type of panel you purchase, simply fit either the PCX-RIX32-WE or UR2-WE to Pyronix PCX commercial panels or any brand of wired panels respectively to allow connectivity to the full range of Enforcer two-way wireless devices.

 **Pyronix**
www.pyronix.com


* With a set/unset output

Features and Specifications

Making Wired Systems Wireless

Connecting PCX commercial panels to the Enforcer two way wireless range.



| PCX RIX32-WE | |
|---|------------|
| Type of module | |
| Wired input expander module | × |
| Two-way wireless input expander module | ✓ |
| Output expander module | ✓ |
| Technical characteristics | |
| Wired inputs (NC/DEOL/3-EOL) | × |
| Roller shutter inputs (NC/DEOL) | × |
| Outputs | × |
| Relay outputs | × |
| Two-way wireless inputs | 32 |
| Two-way wireless keyfobs | 32 |
| Two-way wireless sirens | 2 |
| Plastic housing with tamper protection | ✓ |
| Metal housing with tamper protection | × |
| Integrated power supply | × |
| Certifications and warranty | |
| Electrical conformity | CE |
| EN50131 | Grade 2 |
| Environmental class | II |
|  | CA12.01439 |
| Warranty | 2 years |

Connecting ALL brands of wired control panels* to the Enforcer two way wireless range.



| UR2-WE | |
|---|----------------|
| Technical characteristics | |
| Output relay exchange (NC/NO) | 2 |
| Channels | 2 |
| Two-way wireless detectors | 10 per channel |
| Two-way wireless keyfobs | 6 per channel |
| Fault signalling (dedicated output relay) | 1 |
| System ARM / DISARM input | 1 |
| Alarm indication (7 segment display) | 1 |
| Certifications and warranty | |
| Electrical conformity | CE |
| Environmental class | II |
| Warranty | 2 years |

Compatible with
ANY BRAND of wired
alarm control panel*

Fully Two Way wireless Technology for Extra Security

Each wireless device on the Enforcer is both a transmitter and a receiver.

Instant Two Way Device Control (ITDC)

Enables the instant wake up and instant sleep of each wireless device on the system. No more frustrating sleep timers on detectors.

Quick to Learn Devices

Simple one button learning feature for easy installation.


Ease of Site Survey

The Signal Strength Indicator (SSI) allows installers, during installation, to view the radio transmission signal strength on both the control panel and wireless devices in real time, aiding a fast and professional installation.

Low Battery Consumption

Devices are told to sleep or wake up by the panel using our unique two way wireless technology, conserving battery life and allowing for maximum power output for range and reliability.

Available In The Enforcer Range



Smoke
Detector



Carbon Monoxide
Detector



Motion
Detector



Deltabell



Shock Sensor



Keyfob

* With a set/unset output

PCX RIX32-WE compatible with the PCX-46 S PCX-46 L PCX-162i Control Panels.



Pyronix Ltd, Braithwell Way, Hellaby Industrial Estate, Rotherham, South Yorkshire, S66 8QY

www.pyronix.com. marketing@pyronix.com. 01709 700100