

HDMI SPLITTER X 2

Product Code - WBXHDMIS2

HDMI SPLITTER 1 X 2

The Full 3D 1x2 HDMI Splitter uses a single HDMI source, accessing to multiple HDMI sinks. The Splitter allows one HDMI devices to be split easily to two HDMI compatible monitors or projectors. The Splitter can also be placed at the end of a long HDMI cable to regenerate the HDMI signal.

1. Supports 3D video format
2. HDR 4K*2K
3. HDMI 1.4 HDCP1.4
4. RGB Format



| | |
|----------------------------|---|
| HDMI version | HDMI 1.4 |
| HDMI resolution | up to 3840x2160P/30Hz |
| Support video color format | 8/10/12/24/48 bit deep color |
| Support audio format | DTS-HD/Dolby-trueHD/DTS/Dolby-AC3/DSD HD(HBR) |
| Max bandwidth | 768MHz |
| Max baud rate | 10.2Gbps |
| Input/Output TMDS signal | 0.5~1.5Volts p-p(TTL) |
| Input/Output DDC signal | 5Volts p-p (TTL) |
| Input cable distance | ≤15m AWG26 HDMI standard cable |
| Output cable distance | ≤20m AWG26 HDMI standard cable |
| Max working current | 1200mA |
| Power Adapter Format | output: DC5V/1A |
| Material | Iron |
| Color | Gold/Grey/Black |
| Dimension (L x W x H) | 65x60x20mm |
| Weight | 200g |
| Warranty | 36 months |

