Speaker Cable 4 Core Black PE

PRODUCT OVERVIEW

This professional-grade speaker cable is designed for high-end domestic sound installations, delivering superior performance and reliability.

Constructed with oxygen-free copper strands, it ensures low resistance and optimal sound quality at all times. The use of polyethylene plastic enhances its durability, making it suitable for both external above-ground applications and below-ground installations within ducting.

ADI-SPKPRO4CPEBLK100

FEATURES

100m 4 Core Speaker Cable, professional grade speaker cable

Bare Copper & Oxygen Free Copper conductors

100 metre reels

Black RAL 9005

Reaction for Fire Rating - Fca (CPR Rating)

Cotton Rope Filler

Manufactured and tested to CE2014/30/EU, RoHS2 2011/65/EU

Rated voltage 300/500V

Webbed in the centre of strands for ease of separation

10 Year Warranty

For more information contact your ADI sales person

Rev: v1 November 24

Speaker Cable 4 Core Black PE

CROSS-SECTION DIAGRAM





PRODUCT SPECIFICATIONS

Construction: 4 Cores

Conductor: Bare Copper, Oxygen Free

Conductor Size: 0.25 ±0.008 x 30(1.31mm²) 16 AWG

Overall Diameter (mm): 7.50 ±0.20

Insulation: LSZH

Insulation Thickness (mm): 0.31

Insulation Thickness 2 Diameter (mm): 2.25 ±0.10

Insulation Colour(s): Red, Black, White, Green

Jacket: PE

Jacket Thickness (mm): 0.60 ±0.01

Rated Temperature: -20°C to 80°C

ADI-SPKPRO4CPEBLK100

For more information contact your ADI sales person

Rev: v1 November 24

Speaker Cable 4 Core Black PE

CONSTRUCTION PRODUCTS REGUALTIONS (CPR)

EURO CLASS (ca:cable)	CLASSIFICATION CRITERIA: FIRE RATING	CPR Description
Reaction to Fire BS EN ISO 1716		
A_{ca}	Does not contribute to the fire	Due to availability, it will be almost impossible for a cable to meet Aca, so they should only be specified with extreme caution.
Reaction to Fire BS EN 50399		
$B1_{ca}$	Minimum contribution to the fire	It's highly unlikely the commonly-used cables will be classified to Class B1ca.
$B2_{ca}$	Combustible, low flame spread & heat release contribution to the fire	Similar to Class Cca, although a lower acceptable heat release rate and burn measurement. In practice, this is likely to be the highest class cables will meet.
C_{ca}	Combustible, moderate flame spread & heat release	This is a more rigorous test than Class Dca, this is widely accepted across Europe as the 'go to' classification, but be aware, many cables do not meet Class Cca though availability is improving.
D_{ca}	Combustible, moderate flame spread & heat release	This classification has relatively little use or acceptance within specifying/contracting organisations. This is because no large scale fire growth is measured.
Reaction to Fire BS EN 60332-1-2		
E_{ca}	Combustible, limited fire spread of less than 425mm	A basic test for vertical flame propagation for a single insulated wire or cable using a 1 KW pre-mixed flame. Note: This test does not measure heat release, toxic fumes or smoke.
F_{ca}	Combustible, fire spread of more than 425mm	Cables classified to Class Fca may have high levels of flammability due to the materials they are made of. This does not mean that the cable cannot be used, it is more likely to be used external.

CPR GUIDE

SUBCLASSIFICATIONS FOR EUROCLASSES Bca to Dca

(S) SMOKE PRODUCTION	(D) FLAMING DROPLETS	(A) SMOKE ACIDITY
BS EN 50399/BS EN 61034-2	BS EN 50399	BS EN 60754-2
s1a: s1 + transmittance >=80% (BS EN 61034-2)	d0: No fall of droplets or flaming particles, times for 1200 seconds	a1: Very low acidity (conductivity <2.5 µS/mm & pH >4.3)
s1b: s1 + transmittance >=60% <80% (BS EN 61034-2)	d1: Fall of droplets or flaming particles that persist for less than 10 seconds, timed for 1200 seconds	a2: low acidity (conductivity <10 µS/mm & pH >4.3)
s1: Low production of slow propagation of smoke		
s2: Intermediate production & propagation of smoke		
s3: None of the above	d2: None of the above	d2: None of the above

Visit us online:
www.adiglobal.com

Classes A to E have to be tested by an independent authorised laboratory. Most cables will fall into classes B2ca to Eca.

For a cable to meet Aca, B1ca, B2ca or Cca, there also needs to be regular on-going factory audits.

This product is rated CPR Euroclass Eca for its reaction to fire.

This product should only be installed by a qualified installer, adhering to local wiring regulations relevant to the application.

It is the responsibility of the installer to ensure that the CPR Class installed meets the requirements for the application in their country.

ADI-SPKPRO4CPEBLK100

For more information contact your ADI sales person

Rev: v1 November 24

CONSTRUCTION PRODUCT REGULATION EURO CLASSES

Visit us online:
www.adiglobal.com