Qing Cables
Malmesbury Road,
Kingsditch Industrial Estate,
Cheltenham, Glos, GL51 9PL. UK

Lifetime GUARANTEE



QUALITY CONNECTIVITY

H03VV-F

218_Y – 300/300V Mains Flexibles

<HAR> Approved - BS6500, VDE0281-5

Physical Characteristics

		0.5mm²	0.75mm²
Conductor:		Bare Copper	Bare Copper
Insulation:		PVC Ø1.9mm	PVC Ø2.10mm
Outer Sheath:	2182Y	PVC Ø5.0mm	n/a
	2183Y	PVC Ø5.3mm	PVC Ø5.6mm
Sheath Colours:		Black White	Black White
Weight:	2182Y	38kg/KM	n/a
	2183Y	45kg/KM	56kg/KM
EN50575 CPR Class:		E_{ca}	E_{ca}
CIBSE TM65 Embodied Carbon [kgCO2e/1000m]		172	255

Electrical Characteristics

Conductor DC Resistance BS EN 60228	<39 [Ω/km]	<26 [Ω/km]
Current Rating	3 Amps	6 Amps
Rated Temperature	-30°C - +80°C	-30°C - +80°C
Rated Voltage	300V/300V	300V/300V
Test Voltage	AC 2kV	AC 2kV

Colour Code

	2 Core	3 Core
Core 1	Blue	Blue
Core 2	Brown	Brown
Core 3		Green/Yellow
Core 4		

Quality Connectivity

HDBT™ MEMBER KNX RoHS UK CA CE EN50575:2014 CPR Compliant

nqa. ISO 9001 QUALITY MANAGEMENT UKAS MANAGEMENT SYSTEMS 0015

T: 01242 224141
F: 01242 224134
www.qingcables.com
enquire@qingcables.co.uk

This specification and images
© Qing Cables Ltd

CPR Rating
A_{ca}
$B1_{ca}$
$B2_{ca}$
C_{ca}
D_{ca}
E_{ca}
F_{ca}

Our full product range includes:

COAXIALS: RG / URM Digital / Satellite (incl Sky+) [CAI Approved] CCTV RF / Microwave
TELECOM: CW1308LSF CW1308LSZH CW1308B CW1128 CW1128/1198 CW1128/1252 Dropwire Jumper Wire CW1311 3002 Coax Flat Cordage
STRUCTURED WIRING: CAT5e UTP & FTP CAT6 UTP & FTP CAT6A U-UTP & U-FTP CAT7A S-FTP [PVC LSZH External UV PE SWA Versions]
DATA: Single Pair Shielded/Unshielded Overall Shielded Core Overall Shielded Pairs Foil & Braid Shield Individual Shielded Pairs Twinax [Belden Equivalents]
DEF STANDARD: 7/0.2 Unscreened / Screened 16/0.2 Unscreened / Screened
CCTV / SECURITY: RG/URM Coaxial Video/Door Entry Composites BS4737 Alarm Flex Mains Flex PH30/PH120 Fire Performance Cable
FIBRE OPTICS: Singlemode/Multimode Loose Tube/Tight Buffer Internal/External LSZH Corrugated Armour/SWA
SPEAKER FLEX: "QCSound" Pro Grade OFC Cores LSZH Sheaths External Grade
CONNECTED HOME: QCMC5 [2x HDTV Coax] + [2x CAT6] + [1x CAT5e]
CONTROL BUS CABLES: KNX/EIB Bus Cables DataBus® DiviceNet™ PROFIBUS Lutron Grafik Eye® CRESSNET® SIMMTRONIC - EBus / MBus / OBus Echelon LonWorks® Mode Lighting
MAINS FLEX: H03VV-F H03VVH2-F H05VV-F H05Z1Z1-F BS6500/BS7919 Arctic Grade H07RN-F
SOLAR: TUV Approved PV Cable.

All our products are RoHS2 [2015/863] and REACH Compliant unless stated otherwise

Every care is taken to ensure all information contained in this publication is correct.
No legal responsibility can be accepted for any inaccuracy.
The company reserves the right to alter or modify the information without notice.
Any images are for illustration purposes only.
Registered in England & Wales No. 2181405 Directors: M.L.G.Taylor, L.J.Taylor, K.M.Wylde

Statement of Conformance
It is hereby certified that any goods supplied that reference those above, conform to this specification unless otherwise noted